




### **SPECIFICATIONS**

Material	Aluminum		
Lens	Polycarbonate		
Diameter	12" / 20" / 28"		
Height	3"		
Input Voltage	110-277V, 50-60 Hz		
Light Source Type	LED		
Power	15W / 20W / 25W / 30W		
LED Output	120 lm/W		
CCT	2700K / 3000K / 4000K		
CRI	90		
Dimming & Driver	Integral, 0-10V		
Light Distribution	Beam Down / Symmetrical		
IP Rating	IP 20		
Warranty	5 years		
Finishes	27 RAL finishes 8 wood-effect finishes 12 metallic finishes Custom on request*		

### **GENERAL INFORMATION**

The SOLE ceiling fixture is a sleek and minimal luminaire designed for modern interiors. With its slim profile and symmetrical downlight distribution, it provides uniform illumination that works equally well in residential, hospitality, and commercial applications. Crafted from durable aluminum with a polycarbonate diffuser, the SOLE combines performance with refined simplicity. A wide selection of RAL, metallic, and wood-effect finishes ensures seamless integration into any design concept.



### **OTHER VERSIONS AVAILABLE**









### **CERTIFICATION**





Project		
Notes		

## **Ordering Information**


Select one item from each category below. If your desired option is unavailable, please contact our team for support or custom solutions.

Code	Diameter Ø / Height	Wattage / Lumens	ССТ
SLE Ceiling	12	15	27 2700K  30 3000K  40 4000K  Cus Custom on request
Dimming	Finish Options		
NN Non-Dimmable DM 0-10V	ST Standard  WE Wood effect  MC Metallic  Cus Cus Custom on request		

### **Finishes**

### Standard finishes





### Wood-effect finishes

















# RAL K7 CLASSIC COLORS (80-95% GLOSS): RAL\_\_\_\_

All RAL Classic colors are available with no setup fee.

On your specification submittal, choose your RAL color by entering the 4-digit RAL code (e.g., RAL 3003).



#### Metallic finishes























