





SPECIFICATIONS

Material	Aluminum, 100% P.E.T. Felt		
Lens	Polycarbonate		
Diameter	23.6" / 35.4" / 47.2" / 59"		
Height	1.5"		
Width	1.3"		
Input Voltage	110-277V, 50-60 Hz		
Light Source Type	LED		
Power	40W / 50W / 80W / 100W		
LED Output	85 lm/W		
ССТ	3000K / 3500K / 4000K		
CRI	90		
Dimming & Driver	Integral, 0-10V		
Light Distribution	120° (Beam Down)		
IP Rating	IP 20		
Finishes	38 acoustic fiber finishes		
Warranty	5 years		

GENERAL INFORMATION

The VIBRA is a contemporary acoustic pendant designed to elevate both lighting performance and spatial comfort. Its streamlined circular form integrates high-density acoustic fiber with a refined aluminum frame, delivering effective sound absorption while providing soft, controlled illumination. Engineered for modern hospitality, workspace, and residential environments, VIBRA offers multiple diameters, color temperatures, and finish options—allowing it to adapt seamlessly to projects that demand both visual elegance and acoustic enhancement.





OTHER VERSIONS AVAILABLE













CERTIFICATION







Project	
Notes	

Ordering Information

Code	Diameter Ø / Wa	ССТ	
VBR Acoustic / Pendant	34 23.6" / 40 W / 3400 lm	68 47.2" / 80 W / 6800 lm	30 3000К
	42 35.4" / 50 W / 4250 lm	85 59" / 100 W / 8500 lm	35 3500К
			40 4000К
Light Distribution	Dimming	Profile Finish Option	Acoustic Fiber Finish Option
BD 120° (Beam Down)	NN Non-Dimmable	WH White	AF Acoustic fibers
	DM 0-10V	BL Black	
Canopy Finish Option	Cord Length	Cord Finish Option	Mounting
ST Standard	L5 59" (adjustable)	SVW White	CT Central Canopy Suspension
	Cus Custom on request	SVB Black	MO Multi-Point Suspension
		SVT Transparent	

Finishes

Acoustic fiber finishes



Standard finishes



Cord finishes





RAL K7 CLASSIC COLORS (80-95% GLOSS): RAL_ _ _ _

All RAL Classic colors are available with no setup fee.

On your specification submittal, choose your RAL color by entering the 4-digit RAL code (e.g., RAL 3003).

