

SPECIFICATIONS


Material	Aluminium
Lens	Acrylic
Height	23.6" / 31.5"
Length	2.60"
Width	3.15"
Light Source Type	LED
Power	5W
Input Voltage	110-277V, 50-60 Hz
LED Output	120 lm/W
CCT	3000K / 4000K / 6000K
CRI	80
Dimming & Driver	Integral, 0-10V
Light Distribution	Type V – symmetrical, downward
IP Rating	IP 65
Warranty	5 years
Finishing	34 RAL finishes

GENERAL INFORMATION

STATUM B is a compact outdoor bollard luminaire defined by its monolithic vertical form and recessed light aperture, creating a calm yet authoritative architectural presence. The solid aluminum body emphasizes clarity of proportion and material integrity while ensuring durability in exterior environments. Designed to deliver controlled, downward illumination with a symmetrical Type V distribution, STATUM is ideal for pathways, entrances, and landscape settings where visual guidance, glare control, and understated contemporary design are required.



OTHER VERSIONS AVAILABLE



CERTIFICATION



Ordering Information

Select one item from each category below. If your desired option is unavailable, please contact our team for support or custom solutions.

Code	Height	Material	CCT
<input checked="" type="checkbox"/> STM-B Bollard	<input type="checkbox"/> 23 23.6"	<input checked="" type="checkbox"/> AL Aluminium	<input type="checkbox"/> 30 3000K
	<input type="checkbox"/> 31 31.5"		<input type="checkbox"/> 40 4000K
			<input type="checkbox"/> 60 6000K
Wattage / Lumens	Light Distribution	Dimming	Body Finish Option
<input checked="" type="checkbox"/> 6 5 W / 600 lm	<input checked="" type="checkbox"/> LD5 Type V – symmetrical, downward	<input type="checkbox"/> NN Non-Dimmable	<input type="checkbox"/> ST Standard
		<input type="checkbox"/> DM 0-10V	<input type="checkbox"/> Cus Custom on request
Finish Type	Mounting		
<input type="checkbox"/> GL Glossy	<input checked="" type="checkbox"/> SM Surface-mounted		
<input type="checkbox"/> MT Matte			

Finishes

Standard finishes

