



GENERAL INFORMATION

The CIRQA R pendant is a sculptural luminaire handcrafted from natural alabaster, offering a refined balance of elegance and functionality. Designed for residential and hospitality applications, its minimalist ring form provides soft, symmetrical illumination with a warm, ambient glow. Available in a range of sizes and CCTs, CIRQA R delivers high-performance output with discreet integral 0-10V dimming. Suspended by slender cables and paired with customizable canopy and cord finishes, it complements both modern and transitional interiors with timeless materiality and presence.

SPECIFICATIONS

| | |
|--------------------|---|
| Material | Alabaster |
| Lens | N/A |
| Diameter | 15.7" / 19.7" / 23.6" / 27.6" / 31.5" / 35.4" |
| Profile Height | 3.2" |
| Input Voltage | 110-277V, 50-60 Hz |
| Light Source Type | LED |
| Power | 25W / 32W / 38W / 44W / 50W / 57W |
| LED Output | 120 lm/W |
| CCT | 2700K / 3000K / 4000K |
| CRI | 90 |
| Dimming & Driver | Integral, 0-10V |
| Light Distribution | Symmetrical (360°) |
| IP Rating | IP 20 |
| Finishes | 7 RAL standard finishes 12 metallic finishes |
| Warranty | 5 years |

OTHER VERSIONS AVAILABLE



CERTIFICATION



Ordering Information

Select one item from each category below. If your desired option is unavailable, please contact our team for support or custom solutions.

| Code | Diameter / Wattage / Nominal Lumens | | Profile Height |
|--|---|--|--|
| <input type="checkbox"/> CRQ-R Pendant | <input type="checkbox"/> 16 Ø 15.7" / 25 W / 3000 lm | <input type="checkbox"/> 31 Ø 31.5" / 50 W / 6000 lm | <input type="checkbox"/> 3 3.2" |
| | <input type="checkbox"/> 20 Ø 19.7" / 32 W / 3840 lm | <input type="checkbox"/> 35 Ø 35.4" / 57 W / 6840 lm | |
| | <input type="checkbox"/> 23 Ø 23.6" / 38 W / 4560 lm | <input type="checkbox"/> Cus Custom on request | |
| | <input type="checkbox"/> 27 Ø 27.6" / 44 W / 5280 lm | | |
| | | | |
| CCT | Light Distribution | Dimming | Canopy Finish Options |
| <input type="checkbox"/> 27 2700K | <input checked="" type="checkbox"/> SLD 360° symmetrical light distribution | <input type="checkbox"/> NN Non-Dimmable | <input type="checkbox"/> ST Standard |
| <input type="checkbox"/> 30 3000K | | <input type="checkbox"/> DM 0-10V | <input type="checkbox"/> MC Metallic |
| <input type="checkbox"/> 40 4000K | | | <input type="checkbox"/> Cus Custom on request |
| Cord Finish Options | Mounting | Cord Length | |
| <input type="checkbox"/> STV Standard Vinyl | <input checked="" type="checkbox"/> SM Suspended-mounted | <input type="checkbox"/> L11 118" (adjustable) | |
| <input type="checkbox"/> DB Decorative Braided | | <input type="checkbox"/> Cus Custom on request | |
| <input type="checkbox"/> Cus Custom on request | | | |

Finishes

Standard finishes



RAL K7 CLASSIC COLORS
(80-95% GLOSS): RAL_ _ _ _

All RAL Classic colors are available with no setup fee.

On your specification submittal, choose your RAL color by entering the 4-digit RAL code (e.g., RAL 3003).



Metallic finishes



Cord finishes

