




GENERAL INFORMATION

RONEX SM is a clean, architectural ceiling fixture designed to provide uniform illumination with a refined, minimal presence. Its slim circular profile delivers soft, diffused light while maintaining a modern and versatile aesthetic suitable for a wide range of interiors. Constructed from aluminum with a frosted acrylic diffuser, RONEX SM offers balanced ambient lighting with optional direct or direct/indirect distribution. Available in multiple sizes and finishes, it adapts easily to residential, hospitality, and commercial environments. Designed for flexibility and performance, RONEX SM combines simplicity, efficiency, and contemporary design in a compact ceiling-mounted solution.



SPECIFICATIONS

Material	Aluminum
Diffuser	Acrylic, Frosted
Diameter	11.8" / 15.7" / 18.9" / 23.6" / 35.4" / 47.2" / 59"
Height	3.7"
Input Voltage	110-277V
Light Source	LED
Power	15W / 20W / 25W / 40W / 90W / 150W / 200W
LED Output	85 lm/W
CCT	3000K / 3500K / 4000K
CRI	90
Dimming & Driver	Integral, 0-10V
Light Distribution	Direct / Direct + Indirect
IP Rating	IP 20
Warranty	5 years
Finishes	White / Black 23 RAL finishes

OTHER VERSIONS AVAILABLE



CERTIFICATION



Ordering Information

Select one item from each category below. If your desired option is unavailable, please contact our team for support or custom solutions.

Code	Diameter Ø / Wattage / Lumens		CCT
<input checked="" type="checkbox"/> RNX-SM Ceiling	<input type="checkbox"/> 11-D 11.8" / 15W / ↓1275 lm	<input type="checkbox"/> 18-ID 18.9" / 50W / ↓2550 lm + ↑1700 lm	<input type="checkbox"/> 30 3000K
	<input type="checkbox"/> 15-D 15.7" / 20W / ↓1700 lm	<input type="checkbox"/> 23-ID 23.6" / 80W / ↓4250 lm + ↑2550 lm	<input type="checkbox"/> 35 3500K
	<input type="checkbox"/> 18-D 18.9" / 25W / ↓2125 lm	<input type="checkbox"/> 35-ID 35.4" / 120W / ↓6800 lm + ↑3400 lm	<input type="checkbox"/> 40 4000K
	<input type="checkbox"/> 23-D 23.6" / 40W / ↓3400 lm	<input type="checkbox"/> 47-ID 47.2" / 150W / ↓8,500 lm + ↑4250 lm	
	<input type="checkbox"/> 35-D 35.4" / 90W / ↓7650 lm	<input type="checkbox"/> 59-ID 59" / 200W / ↓11,050 lm + ↑5950 lm	
	<input type="checkbox"/> 47-D 47.2" / 150W / ↓12,750 lm		
	<input type="checkbox"/> 59-D 59.2" / 200W / ↓17,000 lm		
Dimming	Body Finish Option		
<input type="checkbox"/> NN Non-Dimmable	<input type="checkbox"/> ST Standard		
<input type="checkbox"/> DM 0-10V	<input type="checkbox"/> RAL RAL finishes		

Finishes

Standard finishes



RAL finishes



RAL K7 CLASSIC COLORS (80-95% GLOSS): RAL_ _ _ _

All RAL Classic colors are available

On your specification submittal, choose your RAL color by entering the 4-digit RAL code (e.g., RAL 3003).

