



GENERAL INFORMATION

VECTA RUST B is an outdoor bollard defined by its slim vertical form and precise directional light output. The linear illuminated surface creates a clean beam of light, delivering controlled asymmetrical downward distribution that enhances pathways while minimizing glare and light spill. Designed for landscape and architectural applications, VECTA RUST B provides functional guidance lighting with a refined, minimal presence. Its rust-effect metal finish introduces a natural, textured character that integrates seamlessly into outdoor environments, combining durability with a strong contemporary aesthetic.



SPECIFICATIONS

Material	Metal
Lens	Acrylic
Height	23.6"
Length	2.36"
Width	3.94"
Light Source Type	LED
Power	12W
Input Voltage	110-277V, 50-60 Hz
LED Output	120 lm/W
CCT	3000K / 4000K / 6000K
CRI	80
Dimming & Driver	Integral, 0-10V
Light Distribution	Type II – asymmetric, downward
IP Rating	IP 65
Warranty	5 years
Finishing	Rust Effect
Operating Temp.	-40°C to +50°C (-40°F to +122°F)

OTHER VERSIONS AVAILABLE



CERTIFICATION



Project

Notes

Ordering Information

Select one item from each category below. If your desired option is unavailable, please contact our team for support or custom solutions.

Code	Height / Length / Width	Material	CCT
<input checked="" type="checkbox"/> VCTR-B Bollard	<input checked="" type="checkbox"/> 23 23.6" / 2.36" / 3.94"	<input checked="" type="checkbox"/> ML Metal	<input type="checkbox"/> 30 3000K <input type="checkbox"/> 40 4000K <input type="checkbox"/> 60 6000K
Wattage / Lumens	Light Distribution	Dimming	Body Finish Option
<input checked="" type="checkbox"/> 14 12 W / 1440 lm	<input checked="" type="checkbox"/> LD2 Type II – asymmetric, downward	<input type="checkbox"/> NN Non-Dimmable <input type="checkbox"/> DM 0-10V	<input type="checkbox"/> REF Rust Effect
Mounting			
<input checked="" type="checkbox"/> SM Surface-mounted			

Finishes

