



DURABUILT™
WINDOWS & DOORS

Alpha & Omega Size Guide

Series	Single Window Type	Min width (in)	Max width (in)	Min height (in)	Max height (in)	Min area (s/ft)	Max area Dual pane (s/ft)	Max area Triple pane (s/ft)	Max weight (lbs)	Min radius (in)
Alpha	Single hung (O/X)	14	48	26.5	83	1.3 (sash)	12 (sash)	12 (sash)	75 (sash)	-
	Slider (XO OX)	20	110 ⁽²⁾	13.5	72	1.3 (sash)	18 (sash)	16 (sash)	90 (sash)	-
	Direct Set (O)	13.5	84	13.5	84	1.27	49	30	250	-
	Double Slider (XX)	20	72	14	62	1.3 (sash)	9 (sash)	9 (sash)	50 (sash)	-
Omega	Casement	12.625	36 ⁽⁶⁾	18	90	1.7	18	18	120	-
	Awning	17	60 ⁽³⁾	13	48	1.7	18.25	16	120	-
	Picture	7 ⁽¹⁾	108 ⁽⁴⁾	7 ⁽¹⁾	108 ⁽⁴⁾	0.69	49	32	250	14.5
	Direct Set	10 ⁽¹⁾	108 ⁽⁵⁾	10 ⁽¹⁾	108 ⁽⁵⁾	1.5	63	42	250	-
	Fixed / Fixed Sosh	10 ⁽¹⁾	108 ⁽⁵⁾	10 ⁽¹⁾	108 ⁽⁵⁾	1.5	63	42	250	-

COMBINATION WINDOWS

Alpha and Omega

Monoframe and Continuous 4 3/8" Alpha frame and 3 1/4" Omega frame with Common mullion(s)
Cannot exceed 120" x 96" or 96" x 120" and stay within the individual window minimum / maximum size, area and weight limitation. Combination window maximum weight - 250lbs *.

Box-to-Box Mull

Cannot exceed 168" x 104" or 104" x 168" and stay within the individual window minimum / maximum size, area and weight limitation. Combination window maximum weight - 250lbs *.

Note: Continuous frame combination can be mullled to on individual frame.

*Site glazing of gloss can be used to reduce the combination window weight.

Conditions ⁽¹⁾

- (1) Welds are not warranted under 12"
- (2) Maximum sash width of 30" (offset sash) if greater than 72" width
- (3) Maximum height of 40" if greater than 55" width
- (4) Maximum height/width of 60"
- (5) Maximum height/width of 72" when width/height is over 72"
- (6) Maximum width of 26" if triple pane and greater than 80" height

Casement windows over 72" high and over 23" wide will have Roto® Corner Drive

all about you.