



Dental Air Compressors



eurocompress

DENTAL DIVISION

Dental oilless series

Si



Cod.	DENTAL OILLESS MODEL	Units	Tank	dB (A)	air displacement		F.A.D.		HP KW		volt	Hz	type	cyl.	R.P.M.	bar	psi	cm. a x b x c	kg.	Lbs
					lt/min	cfm	lt/min	cfm	HP	KW										
350.130	24/100	1	24	57	100	3,5	65	2,3	0,75	0,55	230/50		GMS 100	1	1400	8	114	50x61x72	55	121
356.002	24/100 DRY	1	24	57	100	3,5	65	2,3	0,75	0,55	230/50		GMS 100	1	1400	8	114	50x74x72	63	139
350.135	24/114	1	24	57	105	3,5	65	2,3	1	0,75	230/50		F 114	1	1400	8	114	50x61x72	54	119
356.001	24/114 DRY	1	24	57	105	3,5	65	2,3	1	0,75	230/50		F 114	1	1400	8	114	50x74x72	62	137
350.140	24/150	1-2	24	60	150	5,3	110	3,9	1,5	1,1	230/50		GMS 150	1	1400	8	114	50x61x72	60	132
356.003	24/150 DRY	1-2	24	60	150	5,3	110	3,9	1,5	1,1	230/50		GMS 150	1	1400	8	114	50x74x72	68	150
350.145	24/150V	2	24	58	200	7	125	4,4	1,5	1,1	230/50		EXTREME	2v	1400	8	114	50x61x72	60	132
356.004	24/150V DRY	2	24	58	200	7	125	4,4	1,5	1,1	230/50		EXTREME	2v	1400	8	114	50x74x72	68	150
350.150	24/200V	2-3	24	62	200	7	150	5,3	2	1,5	230/50		VS 204	2v	1400	8	114	50x61x72	66	145
356.005	24/200V DRY	2-3	24	62	200	7	150	5,3	2	1,5	230/50		VS 204	2v	1400	8	114	50x74x72	74	163
350.154	50/150	1-2	50	60	150	5,3	110	3,9	1,5	1,1	230/50		GMS 150	1	1400	8	114	50x61x102	77	170
356.006	50/150 DRY	1-2	50	60	150	5,3	110	3,9	1,5	1,1	230/50		GMS 150	1	1400	8	114	50x74x102	85	187
350.156	50/150V	2	50	58	200	7	125	4,4	1,5	1,1	230/50		EXTREME	2v	1400	8	114	50x61x102	77	170
356.007	50/150V DRY	2	50	58	200	7	125	4,4	1,5	1,1	230/50		EXTREME	2v	1400	8	114	50x74x102	85	187
350.155	50/200V	2-3	50	62	200	7	150	5,3	2	1,5	230/50		VS 204	2v	1400	8	114	50x61x102	82	180
356.008	50/200V DRY	2-3	50	62	200	7	150	5,3	2	1,5	230/50		VS 204	2v	1400	8	114	50x74x102	90	198
350.157	50/250V	3	50	62	250	8,8	190	6,8	2,5	1,8	230/50		VS254	2v	1400	8	114	50x61x102	82	180
356.009	50/250V DRY	3	50	62	250	8,8	190	6,8	2,5	1,8	230/50		VS254	2v	1400	8	114	50x61x102	90	198

By request: Volt 230/60 Hz - Volt 115/60 Hz



Cod.	SHARK OILLESS MODEL	Units	Tank	dB (A)	air displacement	F.A.D.	HP KW	volt Hz	type	cyl.	R.P.M.	bar psi	cm. a x b x c	kg. Lbs
370.010	24/100	1	24	70	100 3,5	65 2,3	0,75 0,55	230/50	GMS100	1	1400	8 114	41x40x64	26 57
385.002	24/100 DRY	1	24	70	100 3,5	65 2,3	0,75 0,55	230/50	GMS100	1	1400	8 114	49x55x64	32 70

24/100



Cod.	SHARK OILLESS MODEL	Units	Tank	dB (A)	air displacement	F.A.D.	HP KW	volt Hz	type	cyl.	R.P.M.	bar psi	cm. a x b x c	kg. Lbs
370.005	24/114	1	24	70	105 3,7	65 2,3	1 0,75	230/50	F114	1	1400	8 114	41x40x68	25 55
385.001	24/114 DRY	1	24	70	105 3,6	65 2,3	1 0,75	230/50	F114	1	1400	8 114	49x55x68	31 68

24/114



Cod.	SHARK OILLESS MODEL	Units	Tank	dB (A)	air displacement lt/min cfm	F.A.D. lt/min cfm	HP KW	volt Hz	type	cyl.	R.P.M.	bar psi	cm. a x b x c	kg. Lbs
370.020	24/150	1-2	24	75	150 5,3	121 4,3	1,5 1,1	230/50	GMS150	1	1400	8 114	41x40x65	31 68
385.003	24/150 DRY	1-2	24	75	150 5,3	121 4,3	1,5 1,1	230/50	GMS150	1	1400	8 114	49x55x65	37 81

at 5 bar

24/150



Cod.	SHARK OILLESS MODEL	Units	Tank	dB (A)	air displacement lt/min cfm	F.A.D. lt/min cfm	HP KW	volt Hz	type	cyl.	R.P.M.	bar psi	cm. a x b x c	kg. Lbs
370.025	24/150V	2	24	68	200 7	125 4,4	1,5 1,1	230/50	EXTREME	2v	1400	8 114	41x43x61	31 68
385.004	24/150V DRY	2	24	68	200 7	125 4,4	1,5 1,1	230/50	EXTREME	2v	1400	8 114	49x56x61	37 81

at 5 bar

24/150V



Cod.	SHARK OILLESS MODEL	Units	Tank	dB (A)	air displacement lt/min cfm	F.A.D. lt/min cfm	HP KW	volt Hz	type	cyl.	R.P.M.	bar psi	cm. a x b x c	kg. Lbs
370.030	24/200V	2-3	24	75	200 7	150 5,3	2 1,5	230/50	VS 204	2v	1400	8 114	41x43x62	36 79
385.005	24/200V DRY	2-3	24	75	200 7	150 5,3	2 1,5	230/50	VS 204	2v	1400	8 114	49x56x62	42 92

24/200V



Cod.	SHARK OILLESS MODEL	Units	Tank	dB (A)	air displacement lt/min cfm	F.A.D. lt/min cfm	HP KW	volt Hz	type	cyl.	R.P.M.	bar psi	cm. a x b x c	kg. Lbs
370.027	24/230V	3	24	68	250 8,8	180 6,4	2 1,5	230/50	EXTREME	2v	1400	8 114	41x43x63	33 72
385.012	24/230V DRY	3	24	68	250 8,8	180 6,4	2 1,5	230/60	EXTREME	2v	1400	8 114	49x56x63	39 86

24/230V



Cod.	SHARK OILLESS MODEL	Units	AIRI Tank	dB (A)	air displacement lt/min cfm	F.A.D. lt/min cfm	HP KW	volt Hz	type	cyl.	R.P.M.	bar psi	cm. a x b x c	kg. Lbs
370.034	50/150	1-2	50	75	150 5,3	121 4,3	1,5 1,1	230/50	GMS 150	1	1400	8 114	46x45x94	40 88
385.006	50/150 DRY	1-2	50	75	150 5,3	121 4,3	1,5 1,1	230/50	GMS 150	1	1400	8 114	46x58x94	45 110
370.036	50/150V	2	50	68	200 7	125 4,4	1,5 1,1	230/50	EXTREME	2v	1400	8 114	46x45x91	40 88
385.007	50/150V DRY	2	50	68	200 7	125 4,4	1,5 1,1	230/50	EXTREME	2v	1400	8 114	46x58x91	45 99
370.035	50/200V	2-3	50	75	200 7	150 5,3	2 1,5	230/50	VS 204	2v	1400	8 114	46x45x91	45 99
385.008	50/200V DRY	2-3	50	75	200 7	150 5,3	2 1,5	230/50	VS 204	2v	1400	8 114	46x58x91	50 110
370.037	50/230V	3	50	68	250 8,8	180 6,4	2 1,5	230/50	EXTREME	2v	1400	8 114	46x45x92	42 92
385.013	50/230V DRY	3	50	68	250 8,8	180 6,4	2 1,5	230/50	EXTREME	2v	1400	8 114	46x58x92	47 103
370.039	50/250V	3	50	75	250 8,8	190 6,8	2,5 1,8	230/50	VS 254	2v	1400	8 114	46x45x91	45 99
385.017	50/250V DRY	3	50	75	250 8,8	190 6,8	2,5 1,8	230/50	VS 254	2v	1400	8 114	46x58x91	50 110
370.038	50/280V	4	50	70	400 14	250 8,8	2,5 1,8	230/50	EXTREME	4v	1400	8 114	46x61x95	49 108
385.014	50/280V DRY	4	50	70	400 14	250 8,8	2,5 1,8	230/50	EXTREME	4v	1400	8 114	46x61x95	54 119

TANK LT 50



Cod.	SHARK OILLESS MODEL	Units	AIRI Tank	dB (A)	air displacement lt/min cfm	F.A.D. lt/min cfm	HP KW	volt Hz	type	cyl.	R.P.M.	bar psi	cm. a x b x c	kg. Lbs
370.031	50/300	3-4	50	78	300 10,6	242 8,6	1,5+1,5 1,1+1,1	230/50	GMS 150	1+1	1400	8 114	86x42x76	58 154
385.009	50/300 DRY	3-4	50	78	300 10,6	242 8,6	1,5+1,5 1,1+1,1	230/50	GMS 150	1+1	1400	8 114	86x54x76	68 176
370.031.1	50/300V	4	50	72	400 14	250 8,8	1,5+1,5 1,1+1,1	230/50	EXTREME	2+2	1400	8 114	86x42x72	58 154
385.009.1	50/300V DRY	4	50	72	400 14	250 8,8	1,5+1,5 1,1+1,1	230/50	EXTREME	2+2	1400	8 114	86x54x72	68 176
370.032	100/400V	6	100	78	400 14	300 10,6	2+2 1,5+1,5	230/50	VS 204	2+2	1400	8 114	115x44x81	90 198
385.011	100/400V DRY	6	100	78	400 14	300 10,6	2+2 1,5+1,5	230/50	VS 204	2+2	1400	8 114	115x56x81	100 220
370.033	100/460V	7-8	100	72	500 17,6	360 12,8	2+2 1,5+1,5	230/50	EXTREME	2+2	1400	8 114	115x44x82	87 190
385.015	100/460V DRY	7-8	100	72	500 17,6	360 12,8	2+2 1,5+1,5	230/50	EXTREME	2+2	1400	8 114	115x56x82	97 213
370.040	100/500V	7-8	100	78	500 18	380 13,5	2,5+2,5 1,8+1	230/50	VS 254	2+2	1400	8 114	115x44x81	87 190
385.016	100/500V DRY	7-8	100	78	500 18	380 13,5	2,5+2,5 1,8+1	230/50	VS 254	2+2	1400	8 114	115x56x81	97 213

TANDEM

ent

Power oilless series



Cod.	POWER OILLESS MODEL	Units	Tank	dB (A)	air displacement lit/min cfm		F.A.D. lit/min cfm		HP KW		volt	Hz	type	cyl.	R.P.M.	bar	psi	cm. a x b x c	kg. lbs	
390.010	24/100	1	24	59	100	3,5	65	2,3	0,75 0,55		230/50		GMS 100	1	1400	8	114	51x59x82	30	66
398.001	24/100 DRY	1	24	59	100	3,5	65	2,3	0,75 0,55		230/50		GMS 100	1	1400	8	114	63x59x82	36	79
390.020	24/114	1	24	59	105	3,5	65	2,3	1 0,75		230/50		F 114	1	1400	8	114	51x59x82	31	68
398.002	24/114 DRY	1	24	59	105	3,5	65	2,3	1 0,75		230/50		F 114	1	1400	8	114	63x59x82	37	81
390.030	24/150	1-2	24	62	150	5,3	110	3,9	1,5 1,1		230/50		GMS 150	1	1400	8	114	51x59x82	35	77
398.003	24/150 DRY	1-2	24	62	150	5,3	110	3,9	1,5 1,1		230/50		GMS 150	1	1400	8	114	63x59x82	41	90
390.040	24/150V	2	24	60	200	7	125	4,4	1,5 1,1		230/50		EXTREME	2v	1400	8	114	51x59x82	35	77
398.004	24/150V DRY	2	24	60	200	7	125	4,4	1,5 1,1		230/50		EXTREME	2v	1400	8	114	63x59x82	41	90
390.050	24/200V	2-3	24	64	200	7	150	5,3	2 1,5		230/50		VS 204	2v	1400	8	114	51x59x82	40	88
398.005	24/200V DRY	2-3	24	64	200	7	150	5,3	2 1,5		230/50		VS 204	2v	1400	8	114	63x59x82	46	101
390.055	24/230V	3	24	60	250	8,8	180	6,4	2 1,5		230/50		EXTREME	2v	1400	8	114	51x59x82	37	81
398.010	24/230V DRY	3	24	60	250	8,8	180	6,4	2 1,5		230/50		EXTREME	2v	1400	8	114	63x59x82	43	94
390.060	50/150	1-2	50	62	150	5,3	110	3,9	1,5 1,1		230/50		GMS 150	1	1400	8	114	51x59x106	46	101
398.006	50/150 DRY	1-2	50	62	150	5,3	110	3,9	1,5 1,1		230/50		GMS 150	1	1400	8	114	51x59x106	51	112
390.070	50/150V	2	50	60	200	7	125	3,9	1,5 1,1		230/50		EXTREME	2v	1400	8	114	51x59x106	46	101
398.007	50/150V DRY	2	50	60	200	7	125	3,9	1,5 1,1		230/50		EXTREME	2v	1400	8	114	51x59x106	51	112
390.080	50/200V	2-3	50	64	200	7	150	5,3	2 1,5		230/50		VS 204	2v	1400	8	114	51x59x106	51	112
398.008	50/200V DRY	2-3	50	64	200	7	150	5,3	2 1,5		230/50		VS 204	2v	1400	8	114	51x59x106	56	123
390.090	50/230V	3	50	60	250	8,8	180	6,4	2 1,5		230/50		EXTREME	2v	1400	8	114	51x59x106	48	105
398.011	50/230V DRY	3	50	60	250	8,8	180	6,4	2 1,5		230/50		EXTREME	2v	1400	8	114	51x59x106	53	116
390.093	50/250V	3	50	64	250	8,8	190	6,8	2,5 1,8		230/50		VS 254	2v	1400	8	114	51x59x106	51	112
398.014	50/250V DRY	3	50	64	250	8,8	190	6,8	2,5 1,8		230/50		VS 254	2v	1400	8	114	51x59x106	56	123
390.091	100/400V	6	100	66	400	14	300	10,6	2+2 1,5+1,5		230/50		VS 204	2+2	1400	8	114	115x59x92	98	216
398.012	100/400V DRY	6	100	66	400	14	300	10,6	2+2 1,5+1,5		230/50		VS 204	2+2	1400	8	114	115x59x92	108	238
390.092	100/460V	7-8	100	62	500	17,6	360	12,8	2+2 1,5+1,5		230/50		EXTREME	2+2	1400	8	114	115x59x92	95	209
398.013	100/460V DRY	7-8	100	62	500	17,6	360	12,8	2+2 1,5+1,5		230/50		EXTREME	2+2	1400	8	114	115x59x92	105	231
390.094	100/500V	7-8	100	66	500	18	380	13,5	2,5+2,5 1,8+1		230/50		VS 254	2+2	1400	8	114	115x59x92	98	216
398.015	100/500V DRY	7-8	100	66	500	18	380	13,5	2,5+2,5 1,8+1		230/50		VS 254	2+2	1400	8	114	115x59x92	108	238

By request: Volt 230/60 Hz - Volt 115/60 Hz

all over the world



■ Eurocompress distributors



eurocompress

DENTAL DIVISION

20090 Trezzano sul Naviglio (MI) ITALY - Via Brunelleschi, 16/20
Tel.: +39/02.44.54.656 - 02.44.50.027 - Fax: +39/02.44.50.027
E-mail: eurocompress@eurocompress.it - <http://www.eurocompress.it>