


Key **Features**

- Write Away quick-start annotation, enhanced by 50-point touch and palm rejection for precise writing.
- 70W total output power speaker system with built-in 8-microphone array, for rich, immersive audio
- EDLA-Certified with Android 14, integrated ViewSonic Education Software for seamless functionality.
- NFC and SSO sign-in for swift access to the intuitive launcher and personal settings.
- EPEAT Silver certified for enhanced energy efficiency and sustainability.



Product **Description**

Bring energy-efficient performance to your classroom with the ViewBoard® IFP51 Series, available in sizes from 55" to 98" to suit any setup. Seamless interactivity is at your fingertips, thanks to its ultra-responsive 50-point touch technology and instant 'write away' annotation. Powered by Android 14 and EDLA-Certified, it offers secure access to Google Play apps, while NFC and SSO sign-in ensure instant access to personalized settings. Integrated ViewSonic Education Software completes the experience with tools for whiteboarding, casting, and device management—delivering a more dynamic and efficient teaching experience.



Visit Us

www.viewsonic.com

| Panel Size: | 65" |
|---|--|
| Panel Type: | TFT LCD Module with DLED Backlight. |
| Display Area (mm): | 1428.48mm(H) x 803.52mm(V) (64.5") |
| Aspect Ratio: | 16:9 |
| Resolution: | UHD 3840x2160 |
| Colors: | 1.07G colors |
| Brightness: | 400 nits (typ.) |
| Contrast Ratio: | 1200:1 (typ.) / 5000:1 (DCR) |
| Response Time: | 6.5 ms |
| Viewing Angles: | H = 178, V = 178 typ. |
| Backlight Life: Surface Treatment: | 50,000 Hours (Min) Hardness:9H, AG+AF |
| Orientation: | Landscape |
| PLATFORM | Zanoscape |
| Processor: | Octa-Core CPU |
| RAM: | 16GB |
| Storage: | 128GB |
| тоисн | |
| Type/ Tech: | Ultra Fine Touch Techology (IR Recognition) |
| Touch Resolution: | 32767 x 32767 |
| Touch Point: | EDLA/Android/Windows: 50 points of touch Yes |
| Palm Rejection: INPUT | Yes |
| HDMI: | x4 (Frontx2:HDMI2.1 with CEC,HDCP; Rearx2: [(HDMI2 with CEC, HDCP)x1+(HDMI2.1 with CEC, HDCP, ARC)x1 |
| RGB / VGA: | x1 |
| DisplayPort: | x1 |
| Audio: | x1 |
| RS232: | x1 |
| SD/SDHC: | TF Card Slot(Micro SD) |
| OPS: | x1 PC Slot |
| OUTPUT | |
| HDMI: | x1 (HDMI 2.1, HDCP 1.x) |
| Audio: SPDIF: | x1 (Line out) x1 (optical) |
| LAN | XI (optical) |
| RJ45: | x2 |
| USB | |
| Туре А: | x5 (Front $x2$ and Rear x 2 with USB3.2 Gen 1, all suppor SmartPort USB ; Rear x 1 with USB 2.0 for system updated to x |
| Type B: | x2 (Front x 1 and Rear x 1 with USB3.2 Gen 1) x3 (Frontx1 with USB3.2 Gen 1, DP1.2, Ethernet 100M, |
| Type C: SPEAKERS | PD 65W; Rearx1 with USB3.2 Gen 1, DP1.2, Ethernet 100M, PD 15W; Topx1 with USB3.2 Gen 1, PD 15W) |
| | |
| 25W x 2 front soundbar + 20W x 1 | subwoofer |
| | subwoofer |
| 25W x 2 front soundbar + 20W x 1 | subwoofer |
| 25W x 2 front soundbar + 20W x 1 | subwoofer |
| 25W x 2 front soundbar + 20W x 1 MICROPHONE Built-in 8-array microphone TOP CAMERA PLATE | subwoofer |
| 25W x 2 front soundbar + 20W x 1 MICROPHONE Built-in 8-array microphone TOP CAMERA PLATE Yes COMPATIBILITY RGB PC/HDMI PC: | 1920x1080 @ 60Hz |
| 25W x 2 front soundbar + 20W x 1 MICROPHONE Built-in 8-array microphone TOP CAMERA PLATE Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: | 1920x1080 @ 60Hz 3840x2160 |
| 25W x 2 front soundbar + 20W x 1 MICROPHONE Built-in 8-array microphone TOP CAMERA PLATE Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: | 1920x1080 @ 60Hz |
| 25W x 2 front soundbar + 20W x 1 MICROPHONE Built-in 8-array microphone TOP CAMERA PLATE Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS | 1920x1080 @ 60Hz 3840x2160 |
| 25W x 2 front soundbar + 20W x 1 MICROPHONE Built-in 8-array microphone TOP CAMERA PLATE Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: | 1920x1080 @ 60Hz 3840x2160 |
| 25W x 2 front soundbar + 20W x 1 MICROPHONE Built-in 8-array microphone TOP CAMERA PLATE Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Android 14 | 1920x1080 @ 60Hz 3840x2160 |
| 25W x 2 front soundbar + 20W x 1 MICROPHONE Built-in 8-array microphone TOP CAMERA PLATE Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Android 14 BUNDLE SOFTWARE | 1920×1080 @ 60Hz 3840×2160 3840×2160 |
| 25W x 2 front soundbar + 20W x 1 MICROPHONE Built-in 8-array microphone TOP CAMERA PLATE Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Android 14 BUNDLE SOFTWARE Basic Annotation Software: | 1920x1080 @ 60Hz 3840x2160 3840x2160 myViewBoard for Android |
| 25W x 2 front soundbar + 20W x 1 MICROPHONE Built-in 8-array microphone TOP CAMERA PLATE Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Android 14 BUNDLE SOFTWARE Basic Annotation Software: Pro Annotation Software: | 1920x1080 @ 60Hz 3840x2160 3840x2160 myViewBoard for Android myViewBoard for Windows (embedded in VPC) |
| 25W x 2 front soundbar + 20W x 1 MICROPHONE Built-in 8-array microphone TOP CAMERA PLATE Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Android 14 BUNDLE SOFTWARE Basic Annotation Software: Pro Annotation Software: Wireless Presentation: | 1920x1080 @ 60Hz 3840x2160 3840x2160 myViewBoard for Android myViewBoard for Windows (embedded in VPC) AirSync |
| 25W x 2 front soundbar + 20W x 1 MICROPHONE Built-in 8-array microphone TOP CAMERA PLATE Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Android 14 BUNDLE SOFTWARE Basic Annotation Software: Pro Annotation Software: Wireless Presentation: Device Management: ViewSonic Launcher: SPECIAL FEATURES | 1920x1080 @ 60Hz 3840x2160 3840x2160 myViewBoard for Android myViewBoard for Windows (embedded in VPC) AirSync Manager Yes |
| 25W x 2 front soundbar + 20W x 1 MICROPHONE Built-in 8-array microphone TOP CAMERA PLATE Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Android 14 BUNDLE SOFTWARE Basic Annotation Software: Pro Annotation Software: Wireless Presentation: Device Management: ViewSonic Launcher: SPECIAL FEATURES All-in-one USB port: | 1920x1080 @ 60Hz 3840x2160 3840x2160 myViewBoard for Android myViewBoard for Windows (embedded in VPC) AirSync Manager Yes USB 3.2 Gen 1 "SmartPort USB" to all channels |
| 25W x 2 front soundbar + 20W x 1 MICROPHONE Built-in 8-array microphone TOP CAMERA PLATE Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Android 14 BUNDLE SOFTWARE Basic Annotation Software: Pro Annotation Software: Wireless Presentation: Device Management: ViewSonic Launcher: SPECIAL FEATURES All-in-one USB port: Simple LAN sharing between IFP and slot-in device: | 1920x1080 @ 60Hz 3840x2160 3840x2160 myViewBoard for Android myViewBoard for Windows (embedded in VPC) AirSync Manager Yes USB 3.2 Gen 1 "SmartPort USB" to all channels 10/100/1000M (USB Type-C 10/100, Android & PC 10/100/10000) |
| 25W x 2 front soundbar + 20W x 1 MICROPHONE Built-in 8-array microphone TOP CAMERA PLATE Yes COMPATIBILITY RGB PC/HDMI PC: HDMI: DisplayPort: EMBEDDED OS EDLA-Certified with Android 14 BUNDLE SOFTWARE Basic Annotation Software: Pro Annotation Software: Wireless Presentation: Device Management: ViewSonic Launcher: SPECIAL FEATURES All-in-one USB port: Simple LAN sharing between IFP | 1920x1080 @ 60Hz 3840x2160 3840x2160 myViewBoard for Android myViewBoard for Windows (embedded in VPC) AirSync Manager Yes USB 3.2 Gen 1 "SmartPort USB" to all channels 10/100/1000M (USB Type-C 10/100, Android & PC |

POWER

Voltage: 100-240V AC +/- 10% Wide Range Consumption: On: 94.51 W ; Off:< 0.5 W **ERGONOMICS** 600 x 400 Wall Mount (VESA ${\it \circledR}$): **OPERATING CONDITIONS** Temperature (° C): 0°C to 40°C 20% ~ 80% RH non-condensing Humidity: DIMENSIONS (W X H X D) Physical (inch / mm): $58.6 \times 35.99 \times 3.36 \text{ in} / 1488.4 \times 914.2 \times 85.3 \text{ mm}$ Packaging (inch / mm): 64.09 x 40.16 x 7.28 in / 1628 x 1020 x 185 mm WEIGHT

Gross (lb / kg): REGULATIONS

Net (lb / kg):

cTUVus, FCC/ICES003, Energy Star 8.0, EMC/CE, CB/LVD, GOST-R/EAC, UkrSEPRO, EPEAT, Mexico NOM, Mexico Energy, UKCA, UK-EEL, BSMI, BIS, LBL(Low Blue Light Certification), Flicker Free, Green BOM, RoHS, ErP-Eco, REACH, SCIP, WEEE, TPCH, Packing waste, CA65, PAIA

76.15 lb / 34.54 kg

93.28 lb / 42.31 kg

PACKAGE CONTENTS

- 1. Power Cord x1 3 meters,

 2. USB Type-C cable x1 1.8 meters

 , USB-IF certified

 3. USB Touch cable x1 3 meters

 4. Touch pen (Passive pen) x 2

 5. Quick Start Guide

 6. RS232 adapter x1

 7. Clamp x 5

 8. Camera Plate x1

 9. Screw x 8 (camera 2+2, wall mount 4)

 10. HDMI cable x1 3meters,

 (HDMI LA certified)

 11. Remote controller x1

 12 AAA battery x2
- 14. Warranty card (only for VSCN)

 COMPATIBLE SLOT-IN PC

13. Compliance statement

VPCF5-W33-G1, VPC37-W53-G1, VPC35-W53-G1, VPC-A31-O1