



SOUND CURTAINS
BY SOUND SEAL

PIPE & DUCT NOISE CONTROL

SPEC DATA SHEET **LAG**



B-10 LAG

ACOUSTICAL PIPE & DUCT WRAP

A flexible one-pound per square foot reinforced-foil-faced loaded vinyl noise barrier used to wrap noisy pipes, ducts, valves and fan housings.

FEATURES:

- Excellent acoustical performance (STC-27)
- Flammability: UL 94: meets VO | FMVSS 302: Pass
- Temperature range: -10° to +180° F
- Nominal Thickness: 0.10"
- The reinforced foil exterior readily accepts matching lag tape for easy installation
- Also available with a 1" or 2" thick quilted fiberglass decoupler

APPLICATIONS:

- Used to wrap noisy pipes and ducts to block the noise that transmits through the walls of the pipe or duct as air or other contents move through it



B-10 LAG ACOUSTICAL PIPE & DUCT WRAP

ACOUSTICAL PERFORMANCE

Sound Absorption Coefficients at the Octave Band Frequencies

Frequency (Hz)	125	250	500	1K	2K	4K	STC
B-10 LAG	15	18	22	27	32	37	27

ASTM E 90 & E 413

SPECIFICATIONS:

Visit www.soundseal.com
or call **1.800.569.1294**

soundseal.com/lag



SIZING

Standard rolls measure 54" x 30'L



www.soundseal.com



A CATALYST ACOUSTICS GROUP BRAND