



SOUND CURTAINS
BY SOUND SEAL

PIPE & DUCT NOISE CONTROL

SPEC DATA SHEET **LAG**



B-10 LAG/QFA-3

ACOUSTICAL PIPE & DUCT WRAP

A composite material featuring a flexible one-pound per square foot reinforced foil-faced loaded vinyl noise barrier bonded to a 1" thick quilted fiberglass sound absorber used to wrap noisy pipes, ducts, valves and fans housings.

FEATURES:

- Excellent acoustical performance (STC-29)
- Flammability: Class A (or 1) Per ASTM E84
- Smoke Density Index: 19.5 | Flame Spread Index: 12.5
- Temperature range: -20° to +220° F
- Nominal Thickness: 1.00"
- Weight: 1.2lb psf
- The reinforced foil exterior readily accepts matching lag tape for easy installation

APPLICATIONS:

- Used to wrap noisy pipes and ducts to block the noise that transmits through the walls of the pipe or duct as air or other contents move through it
- The quilted fiberglass decoupler improves the performance of the noise barrier and provides sound absorption and thermal insulation around the pipe ductwork



B-10 LAG/QFA-3 ACOUSTICAL PIPE & DUCT WRAP

ACOUSTICAL PERFORMANCE

Sound Absorption Coefficients at the Octave Band Frequencies

Frequency (Hz)	125	250	500	1K	2K	4K	STC
B-10 LAG/QFA-3	18	18	23	30	39	46	29

ASTM E 90 & E 413

SPECIFICATIONS:

Visit www.soundseal.com
or call **1.800.569.1294**

soundseal.com/lag



SIZING

Standard rolls measure 54" x 30'L



www.soundseal.com |



A CATALYST ACOUSTICS GROUP BRAND