



**SOUND CURTAINS**  
BY SOUND SEAL

PIPE & DUCT NOISE CONTROL

SPEC DATA SHEET **LAG**



## **B-10 LAG/QFA-9**

### ACOUSTICAL PIPE & DUCT WRAP

A composite material featuring a flexible one-pound per square foot reinforced foil-faced loaded vinyl noise barrier bonded to a 2" thick quilted fiberglass sound absorber used to wrap noisy pipes, ducts, valves and fans housings.

#### **FEATURES:**

- Excellent acoustical performance (STC-30)
- Flammability: Class A (or 1) Per ASTM E84
- Smoke Density Index: 19.5 | Flame Spread Index: 12.5
- Temperature range: -20° to +350° F
- Nominal Thickness: 2.00"
- Weight: 1.45lb psf
- The reinforced foil exterior readily accepts matching lag tape for easy installation
- Suitable for both indoor and outdoor applications

#### **APPLICATIONS:**

- Used to wrap noisy pipes and ducts to block the noise that transmits through the walls of the pipe or duct as air or other contents move through it
- The quilted fiberglass decoupler improves the performance of the noise barrier and provides sound absorption and thermal insulation around the pipe ductwork



# B-10 LAG/QFA-9 ACOUSTICAL PIPE & DUCT WRAP

## ACOUSTICAL PERFORMANCE

Sound Absorption Coefficients at the Octave Band Frequencies

Frequency (Hz)	125	250	500	1K	2K	4K	STC
B-10 LAG/QFA-9	19	20	23	33	44	53	30

ASTM E 90

## SPECIFICATIONS:

Visit [www.soundseal.com](http://www.soundseal.com)  
or call **1.800.569.1294**

[soundseal.com/lag](http://soundseal.com/lag)



## SIZING

Standard rolls measure 54" x 30'L



[www.soundseal.com](http://www.soundseal.com) |



A CATALYST ACOUSTICS GROUP BRAND