



**SOUND CURTAINS**  
BY SOUND SEAL

PIPE & DUCT NOISE CONTROL

SPEC DATA SHEET **LAG**



## **B-20 LAG**

### ACOUSTICAL PIPE & DUCT WRAP

A flexible two-pound per square foot reinforced-foil-faced loaded vinyl noise barrier used to wrap noisy pipes, ducts, valves and fans housings.

#### **FEATURES:**

- Excellent acoustical performance (STC-31)
- Flammability: UL 94: meets VO | FMVSS 302: Pass
- Temperature range: -10° to +180° F
- Nominal Thickness: 0.20"
- The reinforced foil exterior readily accepts matching lag tape for easy installation
- Available with a 1" or 2" thick quilted fiberglass decoupler

#### **APPLICATIONS:**

- Used to wrap noisy pipes and ducts to block the noise that transmits through the walls of the pipe or duct as air or other contents move through it
- The 2 lb psf offers greater sound attenuation than the 1 lb psf version



## B-20 LAG ACOUSTICAL PIPE & DUCT WRAP

### ACOUSTICAL PERFORMANCE

Sound Absorption Coefficients at the Octave Band Frequencies

Frequency (Hz)	125	250	500	1K	2K	4K	STC
B-20 LAG	16	22	26	32	35	40	31

ASTM E 90 & E 413

### SPECIFICATIONS:

Visit [www.soundseal.com](http://www.soundseal.com)  
or call **1.800.569.1294**

[soundseal.com/lag](http://soundseal.com/lag)



### SIZING

Standard rolls measure 54" x 30'L



[www.soundseal.com](http://www.soundseal.com) |



A CATALYST ACOUSTICS GROUP COMPANY