



SOUND CURTAINS
BY SOUND SEAL

PIPE & DUCT NOISE CONTROL

SPEC DATA SHEET **LAG**



B-20 LAG/QFA-3

ACOUSTICAL PIPE & DUCT WRAP

A composite material featuring a flexible two-pound per square foot reinforced foil faced loaded vinyl noise barrier bonded to a 1" thick quilted fiberglass sound absorber.

FEATURES:

- Excellent acoustical performance (STC-32)
- Flammability: Class A (or 1) Per ASTM E84
- Smoke Density Index: 19.5 | Flame Spread Index: 12.5
- Nominal Thickness: 1.00"
- Weight: 2.20lb psf
- The reinforced foil exterior readily accepts matching lag tape for easy installation

APPLICATIONS:

- Used to wrap noisy pipes and ducts to block the noise that transmits through the walls of the pipe or duct as air or other contents move through it
- The quilted fiberglass decoupler improves the performance of the noise barrier and provides sound absorption and thermal insulation around the pipe ductwork



B-20 LAG/QFA-3 ACOUSTICAL PIPE & DUCT WRAP

ACOUSTICAL PERFORMANCE

Sound Absorption Coefficients at the Octave Band Frequencies

Frequency (Hz)	125	250	500	1K	2K	4K	STC
B-20 LAG/QFA-3	20	23	28	37	48	56	32

ASTM E 90 & E 413



SPECIFICATIONS:

Visit www.soundseal.com
or call **1.800.569.1294**

soundseal.com/lag



SIZING

Standard rolls measure 54" x 30'L



www.soundseal.com |



A CATALYST ACOUSTICS GROUP BRAND