



Memtech Acoustics Linear straight-line baffles provide excellent sound control and a modern appearance. Highly customizable options, such as signature profiles and a T-shaped design, offer optimum form and function in lobbies and entries, open-plan offices, museums and entertainment facilities, showrooms, lecture halls, worship centers and more.

Memtech Acoustics Linear Absorbers are easy to install using channel trim and adhesive.

Advantages

- Streamlined appearance
- Excellent sound absorption
- Mold resistant
- Custom sizes, profiles and colors
- Easy installation

Memtech Acoustics
 2175 Avon Industrial Drive
 Rochester Hills, MI 48309
 (248) 289-1123
sales@memtechacoustics.com
www.memtechacoustics.com

Linear Absorber Materials

- Made from WILLTEC™ foam
- Natural white or light grey
- Water-based acoustic coated in standard, premium and custom colors for easy cleaning and durability
- T-shape linear profile design options and custom straight linear shapes available

C-channel Material

- C-channel trims fasten directly to wall and ceiling substrates
- Roll-formed painted steel with hemmed edges
- Length: Up to 10 feet (3.05 m)
- Flanges: 15/16 x 1-15/16 inch (24 x 49 mm) ID

Sizes

- Length: Up to 96 inches (2438 mm)
- Depth: 6 to 24 inch (152 to 610 mm)
- Thickness: 2 inches (51 mm)


Applications

- Flat or sloped ceilings and walls
- Recessed pocket areas within drywall surrounds
- Create or suit ceiling elevation changes
- Tailor depths of linear sections by design, plan and dimension
- Peak visual interest within various spaces

Installation

- First fasten the c-channel trims* directly to the wall or ceiling substrates
- Run a continuous bead of acoustic adhesive within the c-channel before slip-fitting Memtech Acoustics linear baffle absorber into the c-channel
- Before butting baffles tight in continuous rows, apply short beads of acoustic adhesive to baffle ends; then spread using a 1-inch putty knife

Ceiling Sections



Physical Data — WILLTEC™ foam

Material	Open-cell melamine-based foam
Density	0.5 to 0.7 lbs./cubic ft. (ASTM D3574-77)
Long-Term Service Temperature	302°F (150°C)
Flame Spread and Smoke Density	Passes Class A per ASTM E 84 (all finishes) Passes CAN ULCS-102
Microbial Growth	Passes UL 181, section 11
Fungus Resistance	Rating 0 per ASTM G21
Toxicity	Passes University of Pittsburgh Toxicity of Smoke Emission test
Absorber Finishes	Natural white, grey or water-based acoustic coating (standard, premium and custom colors)

Sound Absorption


(In sabins) Test ASTM C423-90a

Frequency (Hz)	12 x 96 x 2 inches (305 x 2438 x 51 mm), Natural white
125	1.0
250	5.4
500	10.8
1K	16.3
2K	18.7
4K	24.0
Average sabines per baffle	12.7

Ceiling Sections



T-shaped Profiles



Additional ceiling sections, ceiling elevations and T-shaped profile ideas are available on our linear design options sheet.

Other products

- Direct-Apply Ceiling and Wall Panels
- Suspended Ceiling Clouds and Baffles
- Suspended Grid Lay-in Panels
- Barriers, Foam and Composites

Memtech Acoustics
 2175 Avon Industrial Drive
 Rochester Hills, MI 48309
 (248) 289-1123
 sales@memtechacoustics.com
 www.memtechacoustics.com