



QFA-10

QUILTED FIBERGLASS ABSORBER


Quilted Fiberglass Sound Absorbers reduce the reflection of sound waves by adding soft, porous, open-celled materials to any environment. Sound Seal's **QFA-10** consists of a durable vinyl coated fiberglass cloth facing quilted to both sides of a two-inch thick fiberglass batting. Wall panels and overhead baffles are constructed with all edges bound and grommets across the top.

FEATURES:

- Excellent acoustical performance (NRC .85)
- Class A fire rated per ASTM E-84
- Flame Spread: 17.66
- Smoke Density: 22.75
- Temperature Range: -20° to +180° F
- Weight: 0.45 lb psf
- Available in bound or unbound rolls @ 4' x 25'

APPLICATIONS:

- Used to reduce the reverberant noise energy in an enclosure, room or building
- Can supplement plywood structures on job sites to improve transmission loss of the wood and reflected noise on the construction side





QFA-10 QUILTED FIBERGLASS ABSORBER

ACOUSTICAL PERFORMANCE

Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	125	250	500	1K	2K	4K	NRC
QFA-10	.19	.99	.96	.80	.57	.33	.85

ASTM C 423

SIZING

All standard curtains are manufactured at 48" wide x any desired length up to 25' long with a 2" nominal thickness. Custom width panels and special options are available upon request.

AVAILABLE STITCHING

Diamond or straight-stitch pattern

AVAILABLE COLORS




Grey



Black



Tan



White

Color Disclaimer – Due to inconsistencies of various monitors, lighting sources, digital photography and fabric dye lot variations, we cannot guarantee that the color you see on your screen accurately portrays the true color of the product. Screen images are intended as a guide only. Swatch samples available upon request.



MORE SPECIFICATIONS:
Visit memtechacoustics.com
or call **248.289.1123**



www.memtechacoustics.com

