



# BSC-25

## NOISE BARRIER/ SOUND ABSORBER COMPOSITE

The barrier septum configuration of Memtech's **BSC-25** product offers the benefits of both a sound absorber and noise barrier. Each curtain is custom fabricated to include a non-reinforced 1-lb psf loaded vinyl noise barrier sandwiched between two layers of 1" thick acoustical fiberglass sound absorbers. Each panel is finished with a quilted, vinyl-coated-fiberglass-cloth facing, grommets across the top, and vertical-mating Velcro along the edges for easy installation.

### FEATURES:

- Excellent acoustical performance (STC-29/NRC .75)
- Class A fire rated per ASTM E-84
- Flame Spread: 22.78
- Smoke Density: 30.56
- Temperature Range: -20° to +180° F
- Weight: 1.50 lb psf
- Available in bound or unbound rolls @ 4' x 25'

### APPLICATIONS:

- Commonly used in manufacturing spaces
- Curtain panels in an acoustical enclosure
- Free-hanging noise barrier/sound absorber composite wall
- Divider partition between noise sources
- Wall or ceiling lining in a mechanical room or building



# BSC-25 NOISE BARRIER/SOUND ABSORBER COMPOSITE

## ACOUSTICAL PERFORMANCE

Sound Transmission Loss Coefficients at the Octave Band Frequencies (Hz)							
Frequency (Hz)	125	250	500	1K	2K	4K	STC
BSC-25	12	16	27	40	44	43	29

ASTM E-90 & E 413



Sound Absorption Coefficients at the Octave Band Frequencies							
Frequency (Hz)	125	250	500	1K	2K	4K	NRC
BSC-25	.45	.96	.87	.66	.47	.30	.75

ASTM C 423

## SIZING

All standard curtains are manufactured at 48" x any desired length up to 25' with 2" nominal thickness. Custom width panels and special options are available upon request.

## AVAILABLE COLORS



**Color Disclaimer** — Due to inconsistencies of various monitors, lighting sources, digital photography and fabric dye lot variations, we cannot guarantee that the color you see on your screen accurately portrays the true color of the product. Screen images are intended as a guide only. Swatch samples available upon request.



**MORE SPECIFICATIONS:**  
Visit [memtechacoustics.com](http://memtechacoustics.com)  
or call **248.289.1123**



[www.memtechacoustics.com](http://www.memtechacoustics.com)

