



TRI-HEX[®]

PET ACOUSTICAL PANEL

Sleek and Angular. Our Tri-Hex panel is the perfect signature piece to complement any space. These panels are designed to fit tightly together, making it effortless to create custom geometric patterns.

FEATURES:

- Quick-Mount installation
- Design friendly felt material
- Wide variety of color choices
- Multiple configurations

COMPOSITION:

- 100% Polyethylene Terephthalate (PET)
- 55% recycled content

ENVIRONMENTAL FACTORS:

- 100% recyclable
- Low VOC emissions
- ASTM – D5116
- LEED – MRc4

TRI-HEX ACOUSTICAL PANEL

SPECIFICATIONS

- **Standard Panel Size:** 13" x 15"
- **Thickness:** 5/8" (0.625")
- **Weight:** 1 lb/tile
- **Edge Detail:** Square
- **Fire Rating:** Class A per ASTM E-84

COLORS

See color chart for wide variety of color options:

ACOUSTICAL PERFORMANCE

Frequency (Hz)	125	250	500	1K	2K	4K	NRC
5/8" Thickness	.03	.07	.29	.60	.76	.86	.45

Tested as Type "A" Mounting

INSTALLATION METHODS

Construction panel adhesive or carpet glue





TRI-HEX ACOUSTICAL PANEL



MORE SPECIFICATIONS:
Visit memtechacoustics.com
or call **248.289.1123**

