DATA SHEET
CAMBRIDGE Qt X 600/600D
SOUND MASKING CONTROL MODULE





The Cambridge Qt™ X 600/600D control module is a sound masking generator, controller, third octave band equalizer and amplifier, with two auxiliary audio inputs to allow for distribution of audio from paging controllers and/or (background) music players. The Qt X 600/600D controls up to 6 zones of Qt Standard or Active emitters. The Qt X 600/600D control module is a compact six-zone networkable controller suitable for installations of up to 72,000 square feet (6,690 m^2). Each zone can be independently adjusted for masking and aux audio levels and spectra. When multiple controllers are included in a single system audio inputs can be shared across all controllers via AVB or Dante (600/D).

FEATURES

- Compatible with Qt Standard emitters and Qt Active emitters.
- Supports up to 6 zones
- AVB or Dante (600/D) media network
- 2 audio inputs for paging and music
- Contact closure integrates with fire alarm systems
- Front panel with LCD
- Front Panel Lock (via software control)
- Auto ramping
- Event scheduling
- Adjustable equalizer for masking and audio inputs
- 4 non-correlated sound masking audio sources per zone
- Built-in clock with system NTP support
- Wall mount bracket included, optional rack mount bracket also available
- Dual network ports (media / control)
- Web interface control by any web-enabled device
- Third party control API/Ethernet
- CE marked, UL listed, and RoHS compliant
- Met Works with WELL licensing criteria for sound masking
- Covered by Biamp Systems' five-year warranty
- Manufactured in the U.S.A.
- TAA compliant
- GSA eligible

ARCHITECTS & ENGINEERS SPECIFICATION

The controller shall consist of all electronics required for operating a sound masking system from a single accessible location. Systems with distributed electronic packages above ceilings are not acceptable. The controller shall permit password protected access for control and monitoring via LAN/browser interface. The controller shall provide six zones and shall be sufficient to generate sound masking, audio control and audio power for up to 72,000 square feet (6,690 m^2) of coverage. The unit shall be capable of time-of-day masking level control; per-zone settings shall be available for day/night levels and start times, ramping interval, and weekday/Sat/Sun behavior. Each audio output shall provide 4 non-correlated channels of masking noise to minimize comb filtering. The unit shall meet all requirements of Underwriters Laboratories, the US and Canadian National Electrical Codes, FCC Part 15, and all pertinent UK and EU codes. The controller shall be CE marked, UL listed, and shall be compliant with the RoHS directive. Warranty shall be 5 years. The controller shall be Qt X 600/600D.

Memtech Acoustics
SALES@MEMTECHACOUSTICS.COM 248.289.1123 MEMTECHACOUSTICS.COM
2175 Avon Industrial Dr., Rochester Hills, MI 48309 | Rev 0 | OCT 2026
Drawings and product details are for information and/or illustrative purposes only, and may vary. Please contact your local Memtech representative for the most current product information.

Qt X 600/600D SPECIFICATIONS

ACTIVE EMITTERS

Max Emitter/Device Capacity:	50 Qt Active Emitters per cable run
Max Emitter Cabling Distance:	800 feet (243m) per cable run
Frequency Response[1]	
Sound Masking:	125Hz to 6.3kHz
Music/Paging:	115Hz to 12kHz
SPL[1]	
Minimum Masking SPL (@ 1m):	30dBA
Maximum Masking SPL (@ 1m):	55dBA
Maximum Music/Paging SPL (@ 1m):	74dBA
Equalization	
Sound Masking (125Hz - 6.3kHz):	ISO 1/3 Octave Bands
Music/Paging (200Hz - 8kHz):	ISO 1/1 Octave Bands

STANDARD EMITTERS

Max Emitter/Device Capacity:	60 Qt Emitters per cable run
Max Emitter Cabling Distance:	1000 feet (300m) per cable run
Frequency Response[1]	
Sound Masking:	200Hz to 6.3kHz
Music/Paging:	200Hz to 10kHz
SPL[1]	
Minimum Masking SPL (@ 1m):	30dBA
Maximum Masking SPL (@ 1m):	55dBA
Maximum Music/Paging SPL (@ 1m):	56dBA
Equalization	
Sound Masking (200Hz - 6.3kHz):	ISO 1/3 Octave Bands
Music/Paging (200Hz - 8kHz):	ISO 1/1 Octave Bands

Masking

Number of Masking Zones:	6 (2 cable runs per zone)
Number of Non-Correlated Masking Sources:	4 per zone
Masking Level Adjustment:	0.5dB steps

Audio Inputs

Input Connector Type:	Captive Screw Terminal
Number of Inputs:	2 (Mono)
Input Level:	+24dBu (12.3VRMS max)
Input Gain Range:	6dB steps
Input Level Adjustment:	1dB steps
Input Impedance:	8kΩ
Phantom Power:	+48VDC (7mA/input)

Remote Control

Connector Type:	Captive Screw Terminal
Input Type:	Contact Closure (Normally Open)
Number of Inputs:	2
Output Type:	Logic Status (5VDC)
Number of Outputs:	2 2 Channels GPIO
Output Connections:	6 RJ-45
Minimum Output Impedance:	2Ω (per channel)

Power Supply

Operating Voltage:	100-240VAC 50/60Hz
Current Draw:	1.25A
Output:	24VDC @ 2.7A
Max. Power Consumption (24VDC):	30W
Included Accessories:	ACT Hole Saw Wall Bracket

Overall Dimensions

Height:	3.5 inches (89mm)
Width:	14 5/8 inches (371.5mm)
Depth:	3.8 inches (97mm)
Weight:	4.2 lbs (1.9 kg) (with surface mount bracket installed)

Environmental:

Ambient Operating Temperature Range:	40 - 104° F (4 – 40° C)
Humidity:	0-95% relative humidity (non-condensing)
Altitude:	0-6,600 ft (0-2000m) MSL

Compliance:

FCC Part 15B (USA)
UL Listed (USA and Canada)
CE Marked (Europe)
RoHS Directive (Europe)

[1] Specifications based on use of Qt Emitters / Qt Active Emitter array and based on published layout practices

Qt X 600/600D BACK PANEL



Biamp, Qt, and Qt X are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.

Drawings and product details are for information and/or illustrative purposes only, and may vary. Please contact your local Memtech representative for the most current product information.