CONSTRUCTION/ASSEMBLY NOTES:

1. PANEL SURFACES: SOLID STEEL FACE IS 16 GA. (MIN.). PERFORATED STEEL FACE IS 22 GA. (MIN.) WITH 3/32" HOLES ON 3/16" STAGGERED CENTERS. PANEL CONSTRUCTION IS AVAILABLE IN "PAINT READY" A-60 GALVANNEAL OR G-90 GALVANIZED STEEL.
2. PANEL FILL: HIGH DENSITY, SEMI-RIGID, NON-HYGROSCOPIC FIBERGLASS. THE MAXIMUM UNSUPPORTED HEIGHT OF FILL SHALL NOT EXCEEDS 23½".
3. FINISH: THERMOSETTING TGIC POLYESTER POWDER COATING IN COLOR SELECTED BY ARCHITECT/CUSTOMER FROM STANDARD COLOR CHART SUPPLIED BY MEMTECH ACOUSTICS. COLOR TO BE: _____
4. PANELS SHALL BE LOWERED CONSECUTIVELY BETWEEN VERTICAL WIDE FLANGED BEAMS. BARRIER WALL SHALL BE DESIGNED TO WITHSTAND WINDLOAD IN ACCORDANCE WITH THE SPECIFIED LOCAL CODE REQUIREMENTS OF THE PROJECT. REFER TO INSTALLATION DETAILS 'OPTION 1' & 'OPTION 2' FOR ALTERNATES.
5. THE BARRIER PANEL ARE DESIGNED TO WITHSTAND WIND LOADS OF 40 POUNDS PER SQUARE FOOT, BOTH NEGATIVE AND POSITIVE.
6. STRUCTURAL STEEL COLUMNS (IF SCHEDULED) CAN BE PROVIDED IN EITHER HOT-DIPPED GALVANIZED, PRIME PAINTED (STD. GREY), OR FINISH PAINTED IN COLOR TO MATCH PANELS.
7. FINISHED PANEL WEIGHT = 5.5 lbs/sq.ft.

BARRIER PANEL ACOUSTIC PERFORMANCE

SOUND TRANSMISSION LOSS, dB


OCTAVE BAND CENTER FREQUENCIES (Hz)	125	250	500	1K	2K	4K	STC
QUIETLINE 'V-STACK' PANEL (STEEL)	*23*	*31*	*40*	*49*	*56*	*62*	*42*


**All data in accordance with ASTM E90-99 and E413-87*

SOUND ABSORPTION COEFFICIENTS


OCTAVE BAND CENTER FREQUENCIES (Hz)	125	250	500	1K	2K	4K	NRC
QUIETLINE 'V-STACK' PANEL (STEEL)	*0.68*	*1.06*	*1.12*	*1.08*	*1.03*	*0.98*	0.95 (1.15)

**All data in accordance with ASTM C423-90a and E795-00*






WALL SECTION DETAIL



SECTION A-A - OPTION #2

WIDE FLANGED BEAM DETAIL FOR HIGH WIND LOADS, TALL WALLS, AND POST SPACING APPLICATIONS



SECTION A-A - OPTION #1

WIDE FLANGED BEAM DETAIL FOR STANDARD APPLICATIONS

QUITELINE 'V-STACK' STEEL BARRIER PANEL

PROJECT:	MEMTECH ACOUSTICS STANDARD DETAILS
SUBMITTED BY:	DATE:
APPROVED BY:	DATE:
	SHEET:

NOTICE

Drawings and product details are for information and/or illustrative purposes only, and may vary. Please contact your local Memtech representative for the most current product information.

Memtech Acoustics
2175 Avon Industrial Dr.
Rochester Hills, MI 48309
248.289.1123
memtechacoustics.com