


H/H-50 PANEL

QuietMOD H/H-50 PANEL DESCRIPTION:

- PANEL IS 4" THICK WITH SOLID SKIN BOTH SIDES.
- ENTIRE PANEL IS CONSTRUCTED WITH "PAINT READY" A-60 GALVANNEAL OR G-90 GALVANIZED STEEL
- FACE SHEETS ARE SPOT WELDED TO THE PANEL FRAMING CHANNEL
- ALL STIFFENERS AND CHANNEL FRAMING ARE FORMED FROM A MINIMUM OF 18 GA. STEEL

SOUND TRANSMISSION LOSS, dB

OCTAVE BAND CENTER FREQUENCIES (Hz)	125	250	500	1K	2K	4K	STC
QuietMOD H/H-50 PANEL	26	44	50	54	57	64	50

*All testing conducted by Riverbank Acoustical Laboratories
*All data in accordance with ASTM E90-99 and E413-87

weight = 6.7 lbs/sq.ft.

NOTICE

Drawings and product details are for information and/or illustrative purposes only, and may vary. Please contact your local Memtech representative for the most current product information.

QUIETMOD H/H-50 ACOUSTIC WALL PANEL DETAIL

PROJECT:			TYPE:
SUBMITTED BY:		DATE:	ISSUE:
APPROVED BY:		DATE:	PROJECT No.:
PROJ. MGR.	SHEET:		

Memtech Acoustics
2175 Avon Industrial Dr.
Rochester Hills, MI 48309
248.289.1123
memtechacoustics.com