IMPACTA
Acoustical Floor Underlayments

Jumpax®



FAST-TRACK FLOOR PREP SYSTEM FOR VINYL AND CARPETS!

- Instant dry floor leveling of most substrates
- Cost-effective solution to problem floors
- Exceptionally stable, free floating underlay system
- Provides a super smooth finish
- Ready for glue-down of all resilients and carpets
- Increased thermal insulation due to product design
- Quick and easy to fit and handle

SAME DAY TURN-AROUND!

Jumpax® instantly provides a smooth, stable base onto which all top floors and carpets can be laid and glued directly. The twin layers of Jumpax panels utilize an overlap joint configuration to produce a seamless surface. Jumpax creates the ideal sub-floor for carpet, linoleum, vinyl, rubber, cork etc.

Jumpax is simple to install and is quicker and easier to use than a traditional smoothing compound or plywood. It is an entirely dry process so it is clean and does not require specially skilled installers. Jumpax requires no setting time and allows the flooring to be removed and replaced in the same day. Jumpax is designed for increased thermal insulation, enabling your valuable heat energy to pass quickly and easily through to the surface for a fast warm up time and maximum comfort.

Jumpax is composed of high quality, TSCA Certified MDF and the 3 mm baseboards and 4 mm top boards are each coated with a special interactive contact adhesive to give a strong, permanent full-surface bond. Strict quality controls during production guarantee excellent results and a trouble-free installation every time. Combined with various subfloor materials, Jumpax fitted out with LVT's, achieves an impact sound reduction of no less than 21 dB.







IMPACTA

Acoustical Floor Underlayments

Jumpax®



SAME DAY TURN-AROUND!

SPECIFICATIONS

- Thickness: 10 mm – 3/8”
- Board Size: 23-5/8” x 47-1/4”
- Boards per package: 4 each top & bottom
- Quantity per package: 31 sf
- Weight per package: 42 lbs

FEATURES

- Eliminates significant floor prep
- Dry-leveling, free floating
- Super smooth surface
- Time saving installation
- Impact Sound Reduction IIC and FIIC 55-60+
- Outstanding floor leveling (up to 2mm over 3 ft)
- Provides thermal insulation

APPLICATION

- Acoustic, fast track subfloor preparation system for the immediate gluedown of all resilient flooring, carpet & carpet tiles.



Memtech Acoustics

www.memtechacoustics.com

248-289-1123 | sales@memtechacoustics.com