Memtech Acoustics

SPEC DATA SHEET **SQ-113**



C-200 & C-200B
ACOUSTICAL CEILING TILES

Sound Quality® Ceiling Tiles are offered as both a sound absorbing as well as a combination sound absorbing/sound blocking tile.

C-200 Ceiling Tiles have a white nubby cloth facing adhered to a 1" or 2" thick rigid fiberglass board and have excellent sound absorption (NRC) ratings.


C-200B Ceiling Tiles take the standard C-200 tile and add a 1# foil backed mass-loaded vinyl to the backside of the tile for high sound absorption (NRC) and high sound blocking (STC) requirements.

FEATURES:

- White nubby cloth facing
- Custom sizes available
- Excellent acoustical values
- Offered with a vinyl noise barrier for high STC requirements

APPLICATIONS:

- Restaurants
- Office spaces
- Schools
- Auditoriums
- Interior adjoining spaces where privacy needs to be added





C-200 & C-200B ACOUSTICAL CEILING TILES

MORE SPECIFICATIONS:
Visit **memtechacoustics.com**
or call **248.289.1123**

SIZING

23-¾" x 23-¾" or 23-¾" x 47-¾" to fit into a standard 15/16" ceiling grid

THICKNESS

1" or 2" thicknesses available

WEIGHTS

- C-200 Tile: .75 lbs / square foot (based on 1" thick)
- C-200 B Tile: 1.75 lbs / square foot (based on 1-1/8" thick)

SUBSTRATES

6-7# PCF rigid fiberglass core
* C-200 B adds a vinyl noise barrier

FINISHES

White nubby cloth facing

EDGE DETAIL

Square

MOUNTING OPTIONS

Grid supplied by others

Memtech Acoustics