



GAF
Safety Data Sheet
SDS # 4098
SDS Date: April 2022

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Streetbond Pro 250 Bright Green

1.2. Intended Use of the Product

Parapro Liquid Resin System. For professional use only.

1.3. Name, Address, and Telephone of the Responsible Party

Company

GAF

1 Campus Drive, Parsippany, NJ 07054

877-GAF-ROOF

1.4. Emergency Telephone Number

Emergency Number : 800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Flam. Liq. 2 H225

Acute Tox. 2 (Inhale) H330

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Skin Sens. 1 H317

Muta. 1B H340

Carc. 1A H350

Carc 2 H351

STOT SE 3 H336

STOT SE 3 H335

STOT RE 1 H372

Aquatic Acute 3 H402

Aquatic Chronic 3 H412

2.2. Label Elements

Hazard Pictograms:



Signal Word: Danger

Hazard Statements:

H225 - Highly flammable liquid and vapor.

H301 - Toxic if swallowed.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H335 - May cause respiratory irritation.

H336 - May cause drowsiness or dizziness.

H340 - May cause genetic defects.

H350 - May cause cancer.
 H360 - May damage fertility or the unborn child.
 H372 - Causes damage to organs through prolonged or repeated exposure.
 H402 - Harmful to aquatic life.
 H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statements :

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 - Keep container tightly closed.
 P240 - Ground/bond container and receiving equipment.
 P241 - Use explosion-proof electrical, ventilating, and lighting equipment.
 P242 - Use only non-sparking tools.
 P243 - Take action to prevent static discharges.
 P260 - Do not breathe vapors, mist, or spray.
 P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
 P270 - Do not eat, drink or smoke when using this product.
 P271 - Use only outdoors or in a well-ventilated area.
 P272 - Contaminated work clothing should not be allowed out of the workplace.
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves, protective clothing, and eye protection.
 P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P312 - Call a POISON CENTER or doctor if you feel unwell.
 P314 - Get medical advice/attention if you feel unwell.
 P321 - Specific treatment (see Section 4 on this SDS).
 P330 - Rinse mouth.
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P362+P364 - Take off contaminated clothing and wash it before reuse.
 P370+P378 - In case of fire: Use appropriate media (see Section 5) to extinguish.
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 - Store in a well-ventilated place. Keep cool.
 P405 - Store locked up.
 P501 - Dispose of contents/container in accordance with local, regional, national, provincial, territorial and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture

| Name | Product Identifier | % | GHS Ingredient Classification |
|---------------------|--------------------|------|--|
| Methyl methacrylate | (CAS-No.) 80-62-6 | 5-10 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 3, H402 |

| | | | |
|--|----------------------|-------|---|
| 2-Ethylhexyl acrylate | (CAS-No.) 103-11-7 | 5-10 | Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412 |
| Yellow Oxide | (CAS-No.) 5567-15-7 | 1 - 5 | |
| Quartz | (CAS-No.) 14808-60-7 | 40-50 | Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372 |
| Aluminum Oxide | (CAS-No.) 1344-28-1 | 20-30 | |
| Silane, dichlorodimethyl-, reaction products with silica | (CAS-No.) 68611-44-9 | 0 - 2 | Acute Tox. 2 (Inhalation: dust, mist), H330 |

Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate the suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench the affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation. May cause drowsiness and dizziness. Toxic if swallowed. Skin sensitization. May cause genetic defects. May cause cancer. May damage fertility. May damage the unborn child. Causes damage to organs through prolonged or repeated exposure.

Inhalation: Irritation of the respiratory tract and the other mucous membranes. High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a seriously disabling and fatal lung disease.

Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Ingestion: This material is toxic in small amounts orally, and can cause adverse health effects or death. **Chronic Symptoms:** May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES**5.1. Extinguishing Media**

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Highly flammable liquid and vapor.

Explosion Hazard: May form flammable or explosive vapor-air mixture.

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Under fire conditions, may produce fumes, smoke, oxides of carbon and hydrocarbons.

Other Information: Do not allow run-off from firefighting to enter drains or water courses.

Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal Precautions, Protective Equipment and Emergency Procedures**

General Measures: Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges. Do not breathe vapor, mist or spray. Do not handle until all safety precautions have been read and understood.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Ventilate area. Eliminate ignition sources.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for Safe Handling**

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable. Product may polymerize at >60°C (>140°F), causing an exothermic reaction which may cause container damage or fire. May react with peroxides, oxidizers, and incompatibilities.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid contact with eyes, skin and clothing. Handle empty containers with care because they may still present a hazard. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin, eyes and clothing.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions For Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and

receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place. Store locked up.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Parapro Liquid Resin System. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in Section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

| Methyl methacrylate (80-62-6) | | |
|-------------------------------|--------------------------------------|---|
| USA ACGIH | ACGIH TWA (ppm) | 50 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 100 ppm |
| USA ACGIH | ACGIH chemical category | dermal sensitizer, Not Classifiable as a Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 410 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 410 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (ppm) | 100 ppm |
| USA IDLH | US IDLH (ppm) | 1000 ppm |
| Alberta | OEL STEL (mg/m ³) | 410 mg/m ³ |
| Alberta | OEL STEL (ppm) | 100 ppm |
| Alberta | OEL TWA (mg/m ³) | 205 mg/m ³ |
| Alberta | OEL TWA (ppm) | 50 ppm |
| British Columbia | OEL STEL (ppm) | 100 ppm |
| British Columbia | OEL TWA (ppm) | 50 ppm |
| Ontario | OEL STEL (ppm) | 100 ppm |
| Ontario | OEL TWA (ppm) | 50 ppm |
| Québec | VEMP (mg/m ³) | 205 mg/m ³ |
| Québec | VEMP (ppm) | 50 ppm |

| Quartz (14808-60-7) | | |
|---------------------|--------------------------------------|---|
| USA ACGIH | ACGIH TWA (mg/m ³) | 0.025 mg/m ³ (respirable particulate matter) |
| USA ACGIH | ACGIH chemical category | A2 - Suspected Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 50 µg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 0.05 mg/m ³ (respirable dust) |

| | | |
|------------------|------------------------------|---|
| USA IDLH | US IDLH (mg/m ³) | 50 mg/m ³ (respirable dust) |
| Alberta | OEL TWA (mg/m ³) | 0.025 mg/m ³ (respirable particulate) |
| British Columbia | OEL TWA (mg/m ³) | 0.025 mg/m ³ (respirable) |
| Ontario | OEL TWA (mg/m ³) | 0.1 mg/m ³ (designated substances regulation-respirable) |
| Québec | VEMP (mg/m ³) | 0.1 mg/m ³ (respirable dust) |

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Wear fire/flamm resistant/retardant clothing.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State : Heavy liquid

Appearance : Bright Green

Odor : Light Floral Scent

Odor Threshold : Not available

pH : Not available

Evaporation Rate : Not available

Melting Point : Not available

Freezing Point : Not available

Boiling Point : Not available

Flash Point : 10 °C (50 °F)

Auto-ignition Temperature : Not available

Decomposition Temperature : Not available

Flammability (solid, gas) : Not applicable

Lower Flammable Limit : Not available

Upper Flammable Limit : Not available

Vapor Pressure : > 1000 hPa @50°C (122°F)

Relative Vapor Density At 20°C : Not available

Relative Density : Not available

Density : 0.97 - 1.4 g/l @21°C(69.8°F)

VOC: <50 g/l

Solubility : Insoluble in water

Partition Coefficient:N-Octanol/Water : Not available

Viscosity : 25- 42(dPa*s @20°C(68°F))

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.
- 10.2. Chemical Stability:** Highly flammable liquid and vapor. May form flammable or explosive vapor-air mixture.
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization may occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** None expected under normal conditions of use.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects-Product

- Acute Toxicity (Oral):** Oral: Toxic if swallowed.
- Acute Toxicity (Dermal):** Not classified
- Acute Toxicity (Inhalation):** Not classified
- LD50 and LC50 Data:**

| | |
|--------------------------|--------------------------|
| StreetBond Pro 220 & 250 | |
| ATE US/CA (oral) | 215.73 mg/kg body weight |

- Skin Corrosion/Irritation:** Causes skin irritation.
- Eye Damage/Irritation:** Causes serious eye irritation.
- Respiratory or Skin Sensitization:** May cause an allergic skin reaction.
- Germ Cell Mutagenicity:** May cause genetic defects.
- Carcinogenicity:** May cause cancer.
- Specific Target Organ Toxicity (Repeated Exposure):** Causes damage to organs through prolonged or repeated exposure.
- Reproductive Toxicity:** May damage fertility or the unborn child.
- Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness or dizziness. May cause respiratory irritation.
- Aspiration Hazard:** Not classified
- Symptoms/Injuries After Inhalation:** Irritation of the respiratory tract and the other mucous membranes. High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a seriously disabling and fatal lung disease.
- Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.
- Symptoms/Injuries After Eye Contact:** Contact causes severe irritation with redness and swelling of the conjunctiva.
- Symptoms/Injuries After Ingestion:** This material is toxic in small amounts orally, and can cause adverse health effects or death.
- Chronic Symptoms:** May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

11.2. Information on Toxicological Effects-Ingredient(s)

LD50 and LC50 Data:

| | |
|---|--------------------|
| 2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3) | |
| LD50 Oral Rat | 25 - 200 mg/kg |
| Methyl methacrylate (80-62-6) | |
| LD50 Oral Rat | 8420 - 10000 mg/kg |
| LD50 Dermal Rabbit | 5000 - 7500 mg/kg |
| LC50 Inhalation Rat | 29 mg/l/4h |
| LC50 Inhalation Rat | 7093 ppm/4h |

| | |
|---|---|
| 2-Ethylhexyl acrylate (103-11-7) | |
| LD50 Oral Rat | 4435 mg/kg |
| LD50 Dermal Rabbit | 7522 mg/kg |
| 2,2,4-Trimethyl-1,3-pentanediol diisobutyrate (6846-50-0) | |
| LD50 Oral Rat | > 3200 mg/kg |
| LC50 Inhalation Rat | > 5.3 mg/l (Exposure time: 6 h) |
| Quartz (14808-60-7) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rat | > 5000 mg/kg |
| Silica, amorphous (7631-86-9) | |
| LD50 Oral Rat | 7900 mg/kg |
| LD50 Dermal Rabbit | > 2000 mg/kg |
| LC50 Inhalation Rat | > 2.2 mg/l (Exposure time: 1 h) |
| 2-Hydroxy-4-methoxybenzophenone (131-57-7) | |
| LD50 Oral Rat | > 12.8 g/kg |
| LD50 Dermal Rabbit | > 16 g/kg |
| Disodium carbonate (497-19-8) | |
| LD50 Oral Rat | 4090 mg/kg |
| LC50 Inhalation Rat | 2300 mg/m ³ (Exposure time: 2 h) |
| Naphtha, petroleum, hydrodesulfurized heavy (64742-82-1) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rabbit | > 3160 mg/kg |
| Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite (68953-58-2) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LC50 Inhalation Rat | > 12.6 mg/l/4h |
| Paraffin waxes and Hydrocarbon waxes (8002-74-2) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rabbit | > 3600 mg/kg |
| Propylene glycol monomethyl ether (107-98-2) | |
| LD50 Oral Rat | 5000 mg/kg |
| LD50 Dermal Rabbit | 13 g/kg |

| | |
|--|---------------------------------|
| LC50 Inhalation Rat | 27.3 mg/l/4h |
| LC50 Inhalation Rat | > 7559 ppm (Exposure time: 6 h) |
| Solvent naphtha, petroleum, light aromatic (64742-95-6) | |
| LD50 Oral Rat | 8400 mg/kg |
| LD50 Dermal Rabbit | > 2000 mg/kg |
| LC50 Inhalation Rat | 3400 ppm/4h |
| Silane, dichlorodimethyl-, reaction products with silica (68611-44-9) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LC50 Inhalation Rat | 0.45 mg/l/4h |
| Silica, amorphous, fumed, crystalline-free (112945-52-5) | |
| LD50 Oral Rat | 3160 mg/kg |

| | |
|---|---|
| Methyl methacrylate (80-62-6) | |
| IARC Group | 3 |
| 2-Ethylhexyl acrylate (103-11-7) | |
| IARC Group | 3 |
| Quartz (14808-60-7) | |
| IARC Group | 1 |

| | |
|---|---|
| National Toxicology Program (NTP) Status | Known Human Carcinogens. |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |
| Silica, amorphous (7631-86-9) | |
| IARC Group | 3 |
| Silica, amorphous, fumed, crystalline-free (112945-52-5) | |
| IARC Group | 3 |

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

| | |
|--|---------|
| 2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3) | |
| LC50 Fish 1 | 17 mg/l |

| | |
|--|--|
| EC50 Daphnia 1 | 28.8 mg/l |
| Methyl methacrylate (80-62-6) | |
| LC50 Fish 1 | 243 - 275 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1 | 69 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC50 Fish 2 | 125.5 - 190.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| 2-Ethylhexyl acrylate (103-11-7) | |
| EC50 Daphnia 1 | 17.45 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| 2,2,4-Trimethyl-1,3-pentanediol diisobutyrate (6846-50-0) | |
| LC50 Fish 1 | 6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 Daphnia 1 | > 1.46 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| Silica, amorphous (7631-86-9) | |
| LC50 Fish 1 | 5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static]) |
| EC50 Daphnia 1 | 7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia) |
| 2-Hydroxy-4-methoxybenzophenone (131-57-7) | |
| ErC50 (algae) | 0.67 mg/l |
| Disodium carbonate (497-19-8) | |
| LC50 Fish 1 | 300 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |
| EC50 Daphnia 1 | 265 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC50 Fish 2 | 310 - 1220 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| Propylene glycol monomethyl ether (107-98-2) | |
| LC50 Fish 1 | 20.8 g/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 Daphnia 1 | 23300 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| Solvent naphtha, petroleum, light aromatic (64742-95-6) | |
| LC50 Fish 1 | 9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss) |
| | |
| EC50 Daphnia 1 | 6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| Silane, dichlorodimethyl-, reaction products with silica (68611-44-9) | |
| LC50 Fish 1 | > 10000 mg/l Brachydanio rerio, OECD Guide-line 203 |
| EC50 Daphnia 1 | > 10000 mg/l OECD Guide-line 202 |
| ErC50 (algae) | <= 10000 mg/l Scenedesmus subspicatus, OECD Guide-line 201 |

12.2. Persistence and Degradability

| | |
|-------------------------------|---|
| StreetBond Pro 220 & 250 | |
| Persistence and Degradability | May cause long-term adverse effects in the environment. |

12.3. Bioaccumulative Potential

| | |
|-------------------------------|------------------|
| StreetBond Pro 220 & 250 | |
| Bioaccumulative Potential | Not established. |
| Methyl methacrylate (80-62-6) | |

| | |
|--|-------------------------------|
| Log Pow | 0.7 |
| 2-Ethylhexyl acrylate (103-11-7) | |
| Log Pow | 4.64 (at 25 °C) |
| Silica, amorphous (7631-86-9) | |
| BCF Fish 1 | (no bioaccumulation expected) |
| 1-Methyl-2-pyrrolidone (872-50-4) | |
| Log Pow | -0.46 (at 25 °C) |
| Disodium carbonate (497-19-8) | |
| BCF Fish 1 | (no bioaccumulation) |
| Propylene glycol monomethyl ether (107-98-2) | |
| BCF Fish 1 | < 2 |
| Log Pow | -0.437 |

12.4. Mobility in Soil

Not available

12.5. Other Adverse Effects**Other Information:** Avoid release to the environment.**SECTION 13: DISPOSAL CONSIDERATIONS****13.1. Waste treatment methods****Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.**Additional Information:** Handle empty containers with care because residual vapors are flammable. **Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.**SECTION 14: TRANSPORT INFORMATION**The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued. **14.1. In****Accordance with DOT****Proper Shipping Name :** FLAMMABLE LIQUIDS, TOXIC, N.O.S., (METHYL METHACRYLATE, 2-PROPANOL, 1, 1'- [(4-METHYLPHENYL)IMINO]BIS-)

Hazard Class 3
 Identification Number : UN1992
 Label Codes : 3, 6.1
 PackingGroup II
 ERG Number 131



14.2. In Accordance with IMDG

Proper Shipping Name : FLAMMABLE LIQUIDS, TOXIC, N.O.S., (METHYL METHACRYLATE, 2-PROPANOL, 1,1' - [(4-METHYLPHENYL)IMINO]BIS-)
 Hazard Class Number
 Identification : 3 (6.1) : UN1992

Label Codes : 3, 6.1
 PackingGroup II
 EmS-No. (Fire) : F-E
 EmS-No. (Spillage) : S-D



14.3. In Accordance with IATA

Proper Shipping Name : FLAMMABLE LIQUIDS, TOXIC, N.O.S., (METHYL METHACRYLATE, 2-PROPANOL, 1,1' - [(4-METHYLPHENYL)IMINO]BIS-)
 Identification Number : 3 (6.1)
 Hazard Class : UN1992
 Label Codes : 3, 6.1
 PackingGroup II
 ERG Code (IATA) : 3HP



14.4. In Accordance with TDG

Proper Shipping Name : FLAMMABLE LIQUIDS, TOXIC, N.O.S., (METHYL METHACRYLATE, 2-PROPANOL, 1,1' - [(4-METHYLPHENYL)IMINO]BIS-)
 Hazard Class 3
 Identification Number : UN1992
 Label Codes : 3, 6.1
 PackingGroup II



SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

| | |
|--|---|
| StreetBond Pro 220 & 250 | |
| SARA Section 311/312 Hazard Classes | Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard |
| 2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Methyl methacrylate (80-62-6) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 | |
| CERCLA RQ | 1000 lb |
| SARA Section 313 - Emission Reporting | 1 % |
| 2-Ethylhexyl acrylate (103-11-7) | |

| | |
|--|--|
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| 2-Propenoic acid, 2-methyl-, polymer with Butyl 2-methyl-2-propenoate and Methyl 2-methyl-2-propenoate (28262-63-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| EPA TSCA Regulatory Flag | XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e., Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)). |
| 2-Propenoic acid, 2-methyl-, oxybis(2,1-ethanediyl) ester (109-17-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| 2,2,4-Trimethyl-1,3-pentanediol diisobutyrate (6846-50-0) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Quartz (14808-60-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

| |
|---|
| Silica, amorphous (7631-86-9) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |

| |
|---|
| 2-Hydroxy-4-methoxybenzophenone (131-57-7) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |
| Disodium carbonate (497-19-8) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |
| Naphtha, petroleum, hydrodesulfurized heavy (64742-82-1) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |
| Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite (68953-58-2) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |
| Paraffin waxes and Hydrocarbon waxes (8002-74-2) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |
| Propylene glycol monomethyl ether (107-98-2) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |
| Solvent naphtha, petroleum, light aromatic (64742-95-6) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |
| 2,6-Di-tert-butyl-p-cresol (128-37-0) |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |

| | |
|---|--|
| Silane, dichlorodimethyl-, reaction products with silica (68611-44-9) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| 2-Propenoic acid, 2-methyl-, 2-[2-(2-methoxyethoxy)ethoxy]ethyl ester (24493-59-2) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Polyethylene (9002-88-4) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| EPA TSCA Regulatory Flag | XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e., Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)). |
| CERCLA RQ | 100 lb |
| SARA Section 313 - Emission Reporting | 1 % |

15.2. US State Regulations

| | |
|--|---|
| Quartz (14808-60-7) | |
| U.S. - California - Proposition 65 - Carcinogens List | WARNING: This product can expose you to chemicals including Silica which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |

| | |
|--|--|
| 2-Ethylhexyl acrylate (103-11-7) | |
| U.S. - California - Proposition 65 - Carcinogens List | WARNING: This product can expose you to chemicals including 2-Ethylhexyl acrylate which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |

| | |
|--|--|
| Methyl methacrylate (80-62-6) | |
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List | |
| 2-Ethylhexyl acrylate (103-11-7) | |
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List | |

| | |
|---|--|
| Quartz (14808-60-7) | |
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List | |

| |
|---|
| U.S. - Pennsylvania - RTK (Right to Know) List |
| Silica, amorphous (7631-86-9) |
| U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List |

| |
|---|
| Paraffin waxes and Hydrocarbon waxes (8002-74-2) |
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List |
| Propylene glycol monomethyl ether (107-98-2) |
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List |

15.3. Canadian Regulations

| |
|--|
| 2-Propanol, 1,1'-[(4-methylphenyl)imino]bis- (38668-48-3) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Methyl methacrylate (80-62-6) |
| Listed on the Canadian DSL (Domestic Substances List) |
| 2-Ethylhexyl acrylate (103-11-7) |
| Listed on the Canadian DSL (Domestic Substances List) |
| 2-Propenoic acid, 2-methyl-, polymer with Butyl 2-methyl-2-propenoate and Methyl 2-methyl-2-propenoate (28262-63-7) |
| Listed on the Canadian DSL (Domestic Substances List) |
| 2-Propenoic acid, 2-methyl-, oxybis(2,1-ethanediyl) ester (109-17-1) |
| Listed on the Canadian DSL (Domestic Substances List) |
| 2,2,4-Trimethyl-1,3-pentanediol diisobutyrate (6846-50-0) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Quartz (14808-60-7) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Silica, amorphous (7631-86-9) |
| Listed on the Canadian DSL (Domestic Substances List) |

| |
|---|
| 2-Hydroxy-4-methoxybenzophenone (131-57-7) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Disodium carbonate (497-19-8) |

| |
|---|
| Listed on the Canadian DSL (Domestic Substances List) |
| Naphtha, petroleum, hydrodesulfurized heavy (64742-82-1) |
| Listed on the Canadian DSL (Domestic Substances List) |

| |
|---|
| Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite (68953-58-2) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Paraffin waxes and Hydrocarbon waxes (8002-74-2) |
| Listed on the Canadian DSL (Domestic Substances List) |
| Propylene glycol monomethyl ether (107-98-2) |
| Listed on the Canadian DSL (Domestic Substances List) |

| |
|---|
| Silane, dichlorodimethyl-, reaction products with silica (68611-44-9) |
| Listed on the Canadian DSL (Domestic Substances List) |
| 2-Propenoic acid, 2-methyl-, 2-[2-(2-methoxyethoxy)ethoxy]ethyl ester (24493-59-2) |
| Listed on the Canadian NDSL (Non-Domestic Substances List) |
| Silica, amorphous, fumed, crystalline-free (112945-52-5) |
| Listed on the Canadian DSL (Domestic Substances List) |

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

ADDITIONAL COMMENTS: None

DATE OF PREVIOUS SDS: 7/4/2020

CHANGES SINCE PREVIOUS SDS: Conversion to GAF SDS.

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.