

StreetBond® Acrylic Textured White Line Paint

Technical Data Sheet



Description:

StreetBond® Acrylic Textured White Line Paint is a durable, 100% acrylic emulsion fortified with fine silica. This product is specially formulated for use on a variety of indoor and outdoor athletic and recreational surfaces, offering neat, clean, and long-lasting line markings. It's designed to be applied over all other StreetBond® Acrylic surfaces or uncoated asphalt surfaces, and can be used on properly prepared and primed surfaces.

Uses:

StreetBond® Acrylic Textured White Line Paint is used for line and event markings for athletic and recreational surfaces, including but not limited to basketball, hockey/in-line skating, pickleball, playground, running surface, shuffleboard, tennis, and multi-purpose courts. StreetBond® Acrylic Textured White Line Paint is part of the StreetBond® Athletic Surface System that may include resurfacer, filler, finish, and line striping.

Packaging:

- 5 gallon pails (18.9 L)
- 1 gallon pails (3.7 L)

Storage:

Store unopened containers between 40°F and 90°F (4°C and 32°C). Do not store in direct sunlight.

Limitations and Precautions:

- Do not apply StreetBond® Acrylic Textured White Line Paint when the surface temperature is below 50°F (10°C) or when surface temperature is above 130°F (55°C).
- Do not apply when rain, fog, or high humidity is imminent.

Application Instructions:

StreetBond® Acrylic Textured White Line Paint is to be applied over surfaces which have already received StreetBond® Acrylic coatings or uncoated asphalt surfaces. New asphalt pavement shall cure a minimum of 14 days before applying StreetBond® Textured White Line Paint. Can be used on properly prepared and primed concrete surfaces. The surface must be clean and free of grease, oil, and any other foreign material. StreetBond® Acrylic Textured White Line Paint is applied with a paint brush, roller, or other suitable paint application equipment. Clean equipment with water immediately after use.

- Approximately one gallon of StreetBond® Acrylic Textured White Line Paint can cover 500 linear feet at 2" wide. Uncoated asphalt surfaces may require two coats when striping. Do not apply over coal tar emulsions.

Product Characteristics

Type	Result	Test Method
VOC (calculated)	100 g/L maximum	
Rotational Viscosity, 77°F, 20 RPM	23,000 ± 5000	Brookfield
Density, lb./gal.	11.7 ± 0.5	ASTM 1475
pH	8.5 to 9.5	

Note: Values are approximate and subject to normal manufacturing variations. These values are not guaranteed and are provided solely as a guide.

Safety and Handling:

For specific information regarding safe handling of this material, please refer to the Safety Data Sheet (SDS).

Cleanup:

Thoroughly rinse application equipment with clean water before it dries.