


TECHNICAL DATA SHEET: SCREENING

Vulcan Screening is crafted from thermally modified New Zealand plantation timber, featuring a vertical grain construction for enhanced weather performance and stability.

The thermal modification and lamination process reduces resin content, improves durability, and delivers a rich, homogenous brown tone – all without the need for chemical preservatives.

Ideal for appearance-grade applications including joinery, pergolas, screening, façade fins, and balustrade infill.

PROFILES



42mm x 42mm

LENGTHS

Mixed Lengths 1200mm - 6000mm

*Lengths are subject to availability at time of order Product supplied as standard in mixed length. Specified fixed length orders may be available but are subject to conditions.

COLOURS

Colours are indicative only. Colour may change/fade as a part of the natural weathering process.

See Maintenance Guide. *Sioo:x is a specialist 3 oat exterior coating system for long term silver weathered look.



NERO



PATINA



TEAK



STRAW



SIOO:X (External Only)

SPECIFICATIONS

Performance

Durability: Class 1 (EN350-1), Class 2 above ground (AS5604).

Serviceable life: 30+ years (with correct maintenance).

Warranty: 25 years against fungal and termite attack (conditions apply).

Fire: Group 3 (AS5637)

Physical Properties

Density: ~420kg/m³

Hardness: 2.5kN Janka

Technical Details

Finish: Fine bandsawn (natural variation expected).

Treatment: Thermally modified (230°C), H3 LOSP treated (AS1604)

Moisture: ~7% MC (±2%) at dispatch.

Glue: PU adhesive (VOC/solvent/formaldehyde free)

Installation & Coating

Use: Above ground (residential and light commercial buildings)

Compatibility: Low corrosion, stainless steel fasteners recommended

Coating: Must be fully sealed on all sides

Sustainability

EPD registered

The trade mark Abodo is a registered trade mark owned by Abodo Wood Limited




GLOSSWOOD
ARCHITECTURAL
TIMBER®

SCREENING

42mm x 42mm

Scale 1:1



Glosswood x Abodo®

P: 1300 882 064
E: info@glosswood.com.au
W: glosswood.com.au