

ALTUS

GROUP 2 FIRE-RATED TIMBER

Natural Timber.
Greater design
freedom.



Altus is our Group 2 fire-rated Paulownia timber lining for interior walls and ceilings. Combining natural timber with enhanced fire performance, it gives architects and designers greater freedom to create considered architectural interiors.

A fire-retardant treatment made from 100% naturally derived substances is infused into the timber, preserving its natural grain and character.

01

GROUP 2 PERFORMANCE

Tested and assessed to AS ISO 9705.

02

100% Naturally Derived Treatment

Infused with a fire-retardant treatment made from naturally derived substances.

03

Lightweight & Prefinished

A refined architectural finish, ready for installation.

GLOSSWOOD®
ARCHITECTURAL TIMBER

Considered by nature. Designed to perform.

A NATURALLY DERIVED TREATMENT

100% naturally derived
Ingredients found in nature.

Non-toxic substances
No ingredients on the REACH SVHC list, as reported by the supplier.

Non-corrosive
No adverse effects on metals observed in supplier testing.

100% biodegradable
Treated timber degrades naturally.

pH neutral
Compatible with most adhesives and surface coatings.

No measurable VOC emissions
Reported for supplier-tested treated timber.

PROFILES



90mm Profile 90x9x3600mm (Board Cover 86mm)
130mm Profile 130x10x3600mm (Board Cover 125mm)


SPECIFICATIONS

Timber	Paulownia
Fire Rating	Group 2 AS ISO 9705
Application	Interior Walls and Ceilings
Weight per length	90mm: 1.1 kg 130mm: 1.65 kg


Weights are approximate and may vary due to natural variations in timber density

FINISHES


SATIN




Clear Ash FR




Blackbutt FR



Tas Oak FR




Cedar FR



Spotted Gum FR




White FR



Dist White FR



Limewash FR



Driftwood FR


MATTE




Raw FR




White Oak FR




Blackbutt FR




Spotted Gum FR




Cedar FR



Teak FR



Walnut FR



Charcoal FR

Expected service life: 50+ years* when installed in interior applications and fully shielded from the elements.

*Expected service life is indicative and depends on correct installation, protection from moisture and biological attack, and appropriate maintenance. It is not a warranty or a guarantee of ongoing fire performance.

**Treatment characteristics are based on supplier data and do not constitute certification of every finished Altus profile or coating.