

Hamilton Library. Image from Abodo

GW x VAARO® FIRE

EXTERNAL CLADDING

Australian fire compliance:
AS 3959, BAL-29

Combining the natural beauty of timber with enhanced durability and proven fire compliance*, GW x Vaaro is designed for projects where material performance and fire compliance are paramount.

GW x Vaaro has been extensively tested to major fire compliance standards* around the world, both before and after weathering, in uncoated and coated form.

*Abodo's Vaaro has been tested to and has achieved AS/NZS 3837:1998 Type A and ISO 9705:2003 Group 1-S (NZ), AS 3959:2018 BAL29 and AS 5637.1:2015 Group 1 (AU) **Testing may vary across markets.

SPECIFICATIONS

Species	New Zealand Radiata Pine
Finish	Fine bandsawn (natural variation expected).
Treatment	Thermally modified (230°C) & vacuum-pressure impregnate with Vaaro® fire-retardant system
Use	Above ground (cladding,soffits, interiors)
Durability	Class 1 (EN350-1)
Warranty	40 years against fungal (conditions apply).

PROFILE



138x18mm
(Board Cover 118mm)
1200mm - 5400mm Lengths

FINISHES


Nero


Teak


Straw


Patina

glosswood.com.au
1300 882 064 | info@glosswood.com.au

GLOSSWOOD®
ARCHITECTURAL TIMBER