# HP DesignJet T850 36-in Multifunction Printer



The world's easiest A3-A1 printing experience to maximize your team's agility<sup>1</sup>



\*Product image may differ from actual product

#### THE EASIEST<sup>1</sup>-Multi-size printing in one click

- Do it all-also print A3 jobs using the integrated input tray, without manually changing from roll to sheets.
- Achieve high-quality CAD and renders across print sizes with HP Flex Tech Inks.
- Avoid distractions with fewer ink interventions thanks to 130/300-ml cartridges.
- Simplify scan and copy workflows with personalized one-click shortcuts from the front panel.

#### **CONNECTED-Secure and seamless** collaboration

- Simplify printing with the new HP Click Print solutions - Save time with real-print preview.<sup>3</sup>
- Protect your printer and data from cyberthreats without any effort thanks to HP Wolf Pro Security.
- Stay on task with HP app<sup>2</sup>-manage your device and print from virtually anywhere using your mobile or tablet.
- Share drawings and collaborate with colleagues wherever they are with the easy-to-use front-loading scanner.

### GO BEYOND-Meet office and environmental needs

- Advance environmental goals-printer is made with at least 35% recycled plastics<sup>4</sup> and recyclable supplies<sup>5</sup>.
- Invest in a robust and compact plotter that's designed to last.
- Reduce energy and ink waste-auto schedule printer on/off usage and enjoy efficient ink maintenance routines.

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

## **Messaging Footnotes**

1 Based on test results using HP Click with the HP DesignJet T850. This solution enables printing in fewer steps compared to main competitor printing solutions. Printing a 5-page mixed job set with A1 and A3 takes 3 steps using HP Click vs. 12 steps with competitor A and 8 steps with competitor B. Testing performed by Sogeti, April 2023. Detailed test report is available upon request.

Requires HP app download available at https://www.hp.com/go/mobileprinting. Certain features are available in English language only and may vary by printer model/country, and between desktop/mobile applications.

HP reserves the right to introduce charges for use of functionality facilitated by the HP app. Internet access required and may not be available in all countries. HP account required for full functionality. List of supported operating systems available in app stores.

<sup>3</sup> HP One-click printing with HP Click software. HP Click software is only compatible with Original HP ink supplies. Applicable to PDF, JPEG, TIFF, DWF, and HP-GL/2 files. <sup>4</sup> Declared %RCP content is based on the quantity and weight of parts made with RCP resin over the total plastic parts.

<sup>5</sup> Program availability varies. See https://www.hp.com/go/recycle

For more information, please visit https://www.hp.com/go/designjet-t850-mfp

















## **Technical specifications**

Print	
Print speed	25 sec/page on A1, 90 A1 prints per hour <sup>1</sup>
Print resolution	Up to 2400 x 1200 optimized dpi
Technology	HP Thermal Inkjet
Margins (roll)	5x5x5x5mm
Margins (sheet)	5x5x5x5mm
Ink types	Pigment-based (C, M, Y, mK)
Print Cartridges/Bottle, Number	4 (C, M, Y, mK) cartridges
Print cartridge/bottle volume delivered	300 ml cartridge, 130 ml cartridge
Ink drop	6 pl (C, M, Y); 12.6 pl (mK)
Printheads	1 (C, M, Y, mK)
Printhead nozzles	1376 per color; 5504 in total
Line accuracy	±0.1% <sup>2</sup>
Minimum line width	0.02 mm (via raster driver)
Max optical density	15 L* min/1.7 D <sup>3</sup>
Scan and copy	
Linear scan speed	Up to 3.81 cm/sec (color, 200 dpi), up to 11.43 cm/sec (grayscale, 200 dpi) $$
Scan resolution	Up to 600 dpi
Technology	Sheetfed, CIS (Contact Image Sensor), media jam detection sensor, front feed scanning method
Scan format	JPEG, PDF, TIFF
Scan destinations	Scan to email, network, and USB. Scan to cloud, computer, and mobile through HP app.
Maximum scan width	914 mm x 2.77 m
Maximum scan length	$7 \mathrm{m}^4$
Original thickness	Up to 0.8 mm
Media	
Applications	Line drawings; Renderings; Presentations; Maps; Posters
Handling	Sheet feed, roll feed, input tray (50 sheet capacity), media bin, automatic horizontal cutter
Rolls	Media rolls: 1; Roll size: 369 to 914 mm; Maximum roll weight: 6.2 kg; Maximum roll diameter: 100 mm;
Maximum media width	914 mm
Sheet size	Input tray: 210 x 279 to 305 x 457 mm; Manual feed: 210 x 279 to 914 x 1676 mm
Standard sheets	Input tray: A4, A3; Manual feed: A4, A3, A2, A1, A0
Media Weight Recommended	60 to 280 g/m² (roll/manual feed); 60 to 220 g/m² (input tray)
Thickness	Up to 0.3 mm
Media types	Bond and coated paper (bond, coated, heavyweight coated, plain, bright white, blueprint), technical paper (natural tracing), film (clear, matte), photographic paper (ID satin, ID gloss), self-adhesive (adhesive matte/gloss, adhesive polypropylene gloss), Polypropylene (matte)
Embedded controller	
Memory	2 GB

Native print languages	TIFF, JPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n
Printing paths	Wi-Fi Direct, remote printing, HP Click App, HP Click Driver for Windows 11, Apple AirPrint and HP app for Android and iOS devices, Windows and macoS printer drivers, printing support for Chrome OS, print from USB pen drive
Remote print enabled	Yes
One-click multi-size printing	Yes
Drivers	Raster driver for macOS and Windows, HP Click Driver for Windows 11, HP-GL/2 driver for Windows
Security features	HP Secure Boot, Allowlisting, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSL, NTLM v2, HP Web JetAdmin, HP Security Manager, SIEM Integration
Dimensions (WxDxH)	
Product	1407 x 701 x 967 mm
Shipping	1575 x 570 x 650 mm
Weight	
Product	60 kg
Shipping	83.5 kg
Included	
What's in the box	HP DesignJet T850 MFP, printhead, introductory ink cartridges, printer stand, spindle, guide, warranty flyer, power cord
HP Software and solutions	HP Click App, HP Click Driver for Windows 11, HP app for Windows, macOS, Android, and iOS
Environmental ranges	
Operating temperature	5 to 40°C
Operating temperature Operating humidity	5 to 40°C 20 to 80% RH
Operating temperature Operating humidity Operating altitude	
Operating temperature Operating humidity	20 to 80% RH
Operating temperature Operating humidity Operating altitude	20 to 80% RH Up to 3000 m
Operating temperature Operating humidity Operating altitude Storage temperature Recycled plastic in printer Acoustics	20 to 80% RH Up to 3000 m -25 to 55°C 37%
Operating temperature Operating humidity Operating altitude Storage temperature Recycled plastic in printer Acoustics Sound pressure	20 to 80% RH Up to 3000 m -25 to 55°C
Operating temperature Operating humidity Operating altitude Storage temperature Recycled plastic in printer Acoustics	20 to 80% RH Up to 3000 m -25 to 55°C 37%
Operating temperature Operating humidity Operating altitude Storage temperature Recycled plastic in printer Acoustics Sound pressure Sound power Power	20 to 80% RH Up to 3000 m -25 to 55°C 37%  Printing: 42 dB(A) (operating), <16 dB(A) (idle)
Operating temperature Operating humidity Operating altitude Storage temperature Recycled plastic in printer Acoustics Sound pressure Sound power Power Consumption	20 to 80% RH Up to 3000 m -25 to 55°C 37%  Printing: 42 dB(A) (operating), <16 dB(A) (idle)
Operating temperature Operating humidity Operating altitude Storage temperature Recycled plastic in printer Acoustics Sound pressure Sound power Power Consumption Requirements	20 to 80% RH  Up to 3000 m  -25 to 55°C  37%  Printing: 42 dB(A) (operating), <16 dB(A) (idle)  Printing: 5.8 B(A) (operating), <3.4 B(A) (idle)  35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (off). Auto-
Operating temperature Operating humidity Operating altitude Storage temperature Recycled plastic in printer Acoustics Sound pressure Sound power Power Consumption Requirements Certification	20 to 80% RH  Up to 3000 m  -25 to 55°C  37%  Printing: 42 dB(A) (operating), <16 dB(A) (idle)  Printing: 5.8 B(A) (operating), <3.4 B(A) (idle)  35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (off). Autoscheduled printer on/off usage.  Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 A
Operating temperature Operating humidity Operating altitude Storage temperature Recycled plastic in printer Acoustics Sound pressure Sound power Power Consumption Requirements	20 to 80% RH  Up to 3000 m  -25 to 55°C  37%  Printing: 42 dB(A) (operating), <16 dB(A) (idle)  Printing: 5.8 B(A) (operating), <3.4 B(A) (idle)  35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (off). Autoscheduled printer on/off usage.  Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 A
Operating temperature Operating humidity Operating altitude Storage temperature Recycled plastic in printer Acoustics Sound pressure Sound power Power Consumption Requirements Certification	20 to 80% RH  Up to 3000 m  -25 to 55°C  37%  Printing: 42 dB(A) (operating), <16 dB(A) (idle)  Printing: 5.8 B(A) (operating), <3.4 B(A) (idle)  35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (off). Autoscheduled printer on/off usage.  Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 A max  USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina
Operating temperature Operating humidity Operating altitude Storage temperature Recycled plastic in printer Acoustics Sound pressure Sound power Power Consumption Requirements Certification Safety	20 to 80% RH  Up to 3000 m  -25 to 55°C  37%  Printing: 42 dB(A) (operating), <16 dB(A) (idle)  Printing: 5.8 B(A) (operating), <3.4 B(A) (idle)  35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (off). Auto-scheduled printer on/off usage.  Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 A max  USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant): Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS)  Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand
Operating temperature Operating humidity Operating altitude Storage temperature Recycled plastic in printer Acoustics Sound pressure Sound power Power Consumption Requirements Certification Safety  Electromagnetic	20 to 80% RH  Up to 3000 m  -25 to 55°C  37%  Printing: 42 dB(A) (operating), <16 dB(A) (idle)  Printing: 5.8 B(A) (operating), <3.4 B(A) (idle)  35 W (printing), <11 W (ready), <3.5 W (sleep), <0.1 W (off). Autoscheduled printer on/off usage.  Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 A max  USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS)  Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC)  ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEEE, RoHS, REACH, ErP). In compliance with applicable

## Ordering information

Hard disk

Product		
2Y9H2A	HP DesignJet T850 36-in Multifunction Printer	
Accessories		
698G7A	HP DesignJet Sheet Organizer	
698G8A	HP DesignJet Sheet Organizer and Stacker Kit	
B3Q37A	HP DesignJet 36-in Spindle	
Original HP printing supplies		
498N0A	HP 739 DesignJet Printhead Replacement Kit	
498N5A	HP 738 130-ml Cyan DesignJet Ink Cartridge	
498N6A 498N7A	HP 738 130-ml Magenta DesignJet Ink Cartridge HP 738 130-ml Yellow DesignJet Ink Cartridge	
498P2A	HP 738B 130-ml Hellow DesignJet Ink Cartriage	
498P6A	HP 738B 300-ml Black DesignJet Ink Cartridge	
676M6A	HP 738 300-ml Cyan DesignJet Ink Cartridge	
676M7A	HP 738 300-ml Magenta DesianJet Ink Cartridae	
676M8A	HP 738 300-ml Yellow DesignJet Ink Cartridge	

Use Original HP inks and printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit https://hp.com/go/OriginalHPinks Original HP large format printing materials

HP Universal Bond Paper (FSC\* certified)<sup>5</sup> (recyclable)<sup>6</sup>
HP Coated Paper (FSC\* certified)<sup>5</sup> (recyclable)<sup>6</sup>
HP Heavyweight Coated Paper (FSC\* certified)<sup>5</sup> (recyclable)<sup>6</sup>

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com. Service and Support

U56RTE HP 4-year Next Business Day HW Support U56RVE HP 5-year Next Business Day HW Support

HP Support Services offer installation and extended support services (e.g. 2, 3, 4, and  $5\,$ years). For more information, please visit http://www.hp.com/go/cpc

## **Specification Footnotes**

<sup>1</sup> Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper (bond) and Original HP inks.

2±01% of the specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Heavyweight Coated roll feed and Original HP inks.

3 With HP Universal Instant Dry Photo Gloss media with Original HP inks.

4 Scanned at 200 dpl using "Long Plot" setting.

5 BMG trademark license code FSC°-C115319, see http://www.fsc.org . HP trademark license code FSC°-C017543, see http://www.fsc.org

 $^{\rm 6}$  Can be recycled through commonly available recycling programs.

© Copyright 2025 HP Development Company, LP. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

