

# MOBILE POWER SOLUTION

- -Mobile Solar Lighting Trailer
- ·Mobile Solar Surveillance Trailer
- ·Mobile Solar Generator Trailer
- ·Mobile Solar Telecom Trailer
- . Mobile Camping Trailer



#### **Ecosight Power Technology Co.,Ltd**

Ecosight Power Technology Co.,Ltd.is a professional provider of innovative mobile solar trailer solutions, dedicated to delivering reliable, sustainable, and efficient power sources for a wide range of applications. Our company has been at the forefront of the renewable energy industry, combining cutting-edge technology with practical mobility to meet the diverse needs of our clients.

### Portab Tower

- Installation free
- ·Maintenance free
- ·Environmental friendly
- ·Affordable Price







#### PANEL ANGLE ADJUSTABLE

Specially designed durable solar panel mounting brackets with adjustable angle rotation Customers can adjust the solar panel angle according to the direction of the sun in order to make better use of solar energy.



#### SURVEILLANCE SOLUTION

The portable tower can be equipped with cameras security guard and remote monitoring for working site or events.

#### PRODUCT SKETCH

# 3850[12"-11 5/2"]

#### **MAIN FEATURES**

#### **CUSTOMIZED DESIGN**

- 1.Option1: we supply solar tower with cameras or lights according to customer's requirements. Option2:Customer can install cameras or lights on the solar tower locally
- 2. The solar panel can be angleadjustable by hand.
- 3. meter galvanized telescopic mast with manual lifting
- 4. Nice base for pouring sandsto keep stability
- 5. Durable base with 4 forkliftholes and HIAB hooks for easyrelocation
- 6. Customized colors to matchclient's requirement available

# Portable Tower

- ·Installation free
- ·Maintenance free
- ·Environmental friendly ·Affordable Price





PRODUCT SKETCH	TECHNICAL DA	ATA				
	Models	ES2P-G7EHCS	ES3P-G7EHCS	ES4P-G9EHCS	ES3P-G7EHCL400	ES4P-G9EHCL600
	Solar Panel Type	Monocrystalline Silicon	Monocrystalline Silicon	Monocrystalline Silicon	Monocrystalline Silicon	Monocrystalline Silicon
	Solar Panel Wattage	2*350W	3*350W	4*350W	3*350W	4*350W
	PV Controller	Epever/Victron MPPT	Epever/Victron MPPT	Epever/Victron MPPT	Epever/Victron MPPT	Epever/Victron MPPT
	Battery Type	Lead Acid Battery	Lead Acid Battery	Lead Acid Battery	Lead Acid Battery	Lead Acid Battery
	Battery QTY	4*150AH, DC12V	6*150AH, DC12V	8*150AH, DC12V	6*150AH, DC12V	8*150AH, DC12V
	Battery Capacity	7200Wh	10800Wh	14400Wh	10800Wh	14400Wh
	System Voltage	DC24V	DC24V	DC48V	DC24V	DC48V
	Devices	CCTV Mounting Box For Surveillance System			4*100WLED Lights, 60000Lums	4*150WLED Lights, 90000Lums
	Spring Cables	Network Cable+Power Cable	Network Cable+Power Cable	Network Cable+Power Cable	Power Cable	Power Cable
	Telescopic Mast	7 Meters	7 Meters	9Meters	7 Meters	9 Meters
	Lifting System	Electric Winch	Electric Winch	Electric Winch	Electric Winch	Electric Winch
	AC Charger	15KW	1.5KW/2.5KW	1.5KW/2.5KW	1.5kW/2.5kW	1.5kW/2.5KW
	Outrigger	4pcs Manual Outriggers, Foldable				
	Working Temperature	-25° C-60° ℃	-25C-60° ℃	-25° C-60°C	-25°C-60°C	-25° °C-60°C
	Charging Time	8.6 Hours(Theoretical)	8.6 Hours(Theoretical)	8.6 Hours(Theoretical)	8.6 Hours (Theoretical)	8.6 Hours (Theoretical)
	Running Time	72Hours for 80W	72Hours for 120W	72Hours for 120W	21.6 Hours for 400W	19.2 Hours for 600W
	Optional	Cameras, 4G Router, NVR, Speaker, Remote Control, Antenna, Inverter, 360° Rotation And 90° Tilt, Lithium Battery				
	Transport Dimensions	1362*1028*2176mm	1362*1028*2176mm	1362*1028*2176mm	1362*1028*2176mm	1362*1028*2176mm
	Operate Dimensions	4839*4148*7000mm	5155*4839*7000mm	5155*4839*7000mm	5155*4839*7000mm	5155*4839*7000mm
	Gross Weight	900KG	1000KG	1150KG	1000KG	1150KG
	Container Loading	20GP:8pcs, 40HQ:16pcs	20GP:8pcs, 40HQ:16pcs	20GP:8pcs,40HQ:16pcs	20GP:8pcs, 40HQ:16pcs	20GP:8pcs, 40HQ:16pcs

## MOBILE SOLAR LIGHT TOWER



#### HIGH EFFICIENCY LED LIGHT

HiLIGHT series solar lighting tower is equipped with high efficiency LED lood light to guarantee optimal use of the battery and solar system.

#### DIMMABLE LIGHTING

The lighting time and brightness can be setup by MPPT controller The lights can be equipped with motion sensor for dimming

#### 360° ROTATION & 90° TILT

All lights can be 360° rotated and 90° tilted Each light's angle is adjustable Customer can adjust ideal lighting angle according on-site situation.

#### **MOBILE SOLAR TRAILER**

The lighting tower is mounted on the mobile solar trailer so it can be easily transported and deployed for temporary work site. The whole system is heavy duty design for utility working

#### **PRODUCT SKETCH**

#### **TECHNICAL DATA**

Models	ES2P-ML400	ES3P-ML600	ES4P-ML600	ES6P-ML1200	ES8P-ML1500		
Light Wattage	4*100W LED Lights	4*150W LED Lights	4*150W LED Lights	6*200W LED Lights	6*250W LED Lights		
Lights Output	DC24V, 60000Lumens	DC24V, 90000Lumens	DC24V, 90000Lumens	DC48V, 180000Lumens	DC48V, 225000Lumens		
Solar Panel Type	Monocrystalline Silicon	Monocrystalline Silicon	Monocrystalline Silicon	Monocrystalline Silicon	Monocrystalline Silicon		
Solar Panel Wattage	2*435W	3*435W	4*435W	6*435W	8*435W		
PV Controller	MPPT 40A, 95% Efficiency	MPPT 60A, 95% Efficiency	MPPT 40A, 95% Efficiency	MPPT 60A, 95% Efficiency	MPPT 80A, 95% Efficiency		
Battery Type	Lead Acid Battery	Lead Acid Battery	Lead Acid Battery	Lead Acid Battery	Lead Acid Battery		
Battery QTY	4*150AH, DC12V	6*150AH, DC12V	8*150AH, DC12V	12*150AH, DC12V	16*150AH, DC12V		
Battery Capacity	7200WH	10800WH	14400WH	21600WH	28800WH		
System Voltage	DC24V	DC24V	DC48V	DC48V	DC48V		
Maximum Height	6 Meters	7 Meters	9 Meters	9 Meters	12 Meters		
Wind Rating Speed	117KM/H	117KM/H	117KM/H	117KM/H	117KM/H		
Lifting System	Manual	Manual	Electric	Hydraulic	Hydraulic		
Axle No.	Single	Single	Single	Dual	Dual		
Tyre and Rim	14 Inch	15 Inch	15 Inch	15 Inch	15 Inch		
Stabilizer Leg	4pcs Manual	4pcs Manual	4pcs Manual	4pcs Manual	4pcs Manual		
Tow Hitch	50mm Ball/ 70mm Ring	50mm Ball/ 70mm Ring	50mm Ball/ 70mm Ring	50mm Ball/ 70mm Ring	50mm Ball/ 70mm Ring		
Working Temperature	-25°C-60°C	-25°C-60°C	-25°C-60°C	-25°C-60°C	-25°C-60°C		
Charging Time	6.9 Hours	6.9 Hours	6.9 Hours	6.9 Hours	6.9 Hours		
Running Time	14.4 Hours	14.4 Hours	19.2 Hours	14.4 Hours	15.4 Hours		
Optional	360° Rotation And 90° Tilted, Lithium Battery, Battery Charger, Inverter, Remote Control, Back-up Generator, Wind Turbine						
Transport Dimensions	2900*1500*2500mm	3200*1600*2500mm	3250*2200*2700mm	3700*2300*2500mm	3700*2300*2500mm		
Operate Dimensions	2900*2500*6000mm	3200*3400*7000mm	3250*4400*9000mm	3700*6500*9000mm	4700*6500*12000mm		
Gross Weight	1000KG	1450KG	1600KG	2400KG	2860KG		
Container Loading	20GP: 6pcs, 40HQ: 14pcs	20GP: 3pcs, 40HQ: 7pcs	20GP: 2pcs, 40HQ: 5pcs	20GP: 2pcs, 40HQ: 4pcs	20GP: 2pcs, 40HQ: 4pcs		

# Mobile Solar CCTV Tower

public events orany off-grid location that requires video monitoring.

- ·Social events Temporary portable security
- ·parking lot security and remote monitoring
- Construction Site Security
- ·Solar Farms security and remote monitoring
- ·Farms security and remote monitoring
- ·Ports and Airports mobile Security
- \*Boarder patrollocations Monitoring
- ·Traffic Monitoring / Vehicle Counting









#### **CCTV MOUNTING**

CCTV mounting box is ready on top of the surveillance trailer tower Customer can mount bullet cameras and PTZ dome cameras as their like 4G Router. Antenna and Speaker can be mounted on the box too.



#### LIGHTS&CAMERAS MOUNTING

For comprehensive on-site working needs, we have specially designed the mounting box with arms for both lights and cameras mounting Net cable+ power cables are ready on the top of tower.



#### **BACK-UP GENERATOR**

Our mobile surveillance trailer can be equipped with back-up generator, so it can continuously work in rainy or cloudy days to protect your assets even there is no sun.




#### AC POWER INPUT&OUTPUT

International standard input plugs or output sockets are equipped. The inverter and battery charger are optional for customer's needs, so the trailer can be charged by utility AC power when there is no sun or supply power for charging other electronics.

#### **PRODUCT SKETCH**

#### **TECHNICAL DATA**



Models	ES1P-M	ES2P-M	ES3P-M	ES4P-M	ES6P-M		
Solar Panel Type	Monocrystalline Silicon	Monocrystalline Silicon	Monocrystalline Silicon	Monocrystalline Silicon	Monocrystalline Silicon		
Solar Panel Wattage	1*435W	2*435W	3*435W	4*435W	6*435W		
PV Controller	MPPT 40A, 95% Efficiency	MPPT 40A, 95% Efficiency	MPPT 60A, 95% Efficiency	MPPT 60A, 95% Efficiency	MPPT 80A, 95% Efficiency		
Battery Type	Lead Acid Battery	Lead Acid Battery	Lead Acid Battery	Lead Acid Battery	Lead Acid Battery		
Battery QTY	2*150AH, DC12V	4*150AH, DC12V	6*150AH, DC12V	8*150AH, DC12V	12*150AH, DC12V		
Battery Capacity	3600WH	7200WH	10800WH	14400WH	21600WH		
System Voltage	DC12V	DC24V	DC24V	DC48V	DC48V		
CCTV Mounting	Junction Box with PoE Switch	Junction Box with PoE Switch	Junction Box with PoE Switch	Junction Box with PoE Switch	Junction Box with PoE Switch		
Spring Cables	2*Cat6 + 2* Power Supply	2*Cat6 + 2* Power Supply	2*Cat6 + 2* Power Supply	2*Cat6 + 2* Power Supply	2*Cat6 + 2* Power Supply		
Maximum Height	6 Meters	6 Meters	7Meters	9 Meters	9 Meters		
Wind Rating Speed	117KM/H	117KM/H	117KM/H	117KM/H	117KM/H		
Lifting System	Manual	Manual	Manual	Electric	Electric		
Axle No.	Single	Single	Single	Single	Dual		
Tyre and Rim	14 Inch	14 Inch	15 Inch	15 Inch	15 Inch		
Stabilizer Leg	4pcs Manual	4pcs Manual	4pcs Manual	4pcs Manual	4pcs Manual		
Tow Hitch	50mm Ball/ 70mm Ring	50mm Ball/ 70mm Ring	50mm Ball/ 70mm Ring	50mm Ball/ 70mm Ring	50mm Ball/ 70mm Ring		
Working Temperature	-25°C-60°C	-25°C-60°C	-25°C-60°C	-25°C-60°C	-25°C-60°C		
Charging Time	6.9 Hours	6.9 Hours	6.9Hours	6.9 Hours	6.9 Hours		
Running Time	3 Days for 40W	3 Days for 80W	3 Days for 120W	3 Days for 160W	3 Days for 240W		
Optional	Cameras, 4G Router, NVR, Remote Control, Antenna, AC Battery Charger, Inverter, Back-up Generator, Lithium Battery						
Transport Dimensions	2900*1500*2500mm	2900*1500*2500mm	3200*1600*2500mm	3250*2200*2700mm	3700*2300*2500mm		
Operate Dimensions	2900*2500*6000mm	2900*2500*6000mm	3200*3400*7000mm	3250*4400*9000mm	3700*6500*9000mm		
Gross Weight	750KG	950KG	1300KG	1550KG	2350KG		
Container Loading	20GP: 6pcs, 40HQ: 14pcs	20GP: 6pcs, 40HQ: 14pcs	20GP: 3pcs, 40HQ: 7pcs	20GP: 2pcs, 40HQ: 5pcs	20GP: 2pcs, 40HQ: 4pcs		

# Mobile Solar Generator trailer

**POWER Mobile solar generator** is a portable power system that uses solar panels to convert sun's energy into DC electricity and store that electricity power in batteries for later use. With inverters, the power in batteries can be used for charging electronics.


ECOSIGHT mobile solar generator mounted on trailer has larger capacity to support your applications. It is a good alternative to diesel or petrol generator with clean, renewable energy and low maintenance, but longer life time.





#### PRODUCT SKETCH





#### **TECHNICAL DATA**

Models	ES8P-M				
Solar Panel Type	Monocrystalline Silicon				
Solar Panel Wattage	8*435W				
PV Controller	MPPT 80A, 95% Efficiency				
Battery Type	Lead Acid Battery				
Battery QTY	16*150AH,12V				
Battery Capacity	28800WH				
System Voltage	DC48V				
Inverter	8KW/8KW 50/60HZ, pure sine wave				
luput Plug	1xAC240V/AC120V				
Output Socket	3xAC240V/AC120V				
Axle No.	Dual				
Tyre and Rim	15 Inch				
Stabilizer Leg	4pcs Manual				
Tow Hitch	50mm Ball/ 70mm Ring				
Working Temperature	-25°C-60°C				
Charging Time	6.9 Hours				
Running Time	2.9 hrs for 8kW				
Optional	Antenna, Mast, Router, Wifi, GPRS, Battery Charger, Inverter, Back-up Generator, Wind Turbine				
Transport Dimensions	2600*2200*2200 mm				
Operate Dimensions	5800*6400*2300mm				
Gross Weight	2600KG				
Container Loading	20GP: 2pcs, 40HQ: 4pcs				

# **Camping Trailer**





#### **PRODUCT PICTURE**

#### **TECHNICAL DATA**



 Overall dimension:
 3000\*1600\*1620mm

 Box size:
 1500\*1000\*500mm

 Tool box size:
 890\*405\*490mm

 Payload:
 750KGS

Payload: 750KGS
Dead load: 526KGS
Shock absorption: independ

Shock absorption: independent suspension
Tyre: 235/75R15 Off-road tire
Rim: 15 "aluminum alloy rims

Guide Wheel Outrigger: 8"
Front support legs: 2
Traction: 2"

Braking: electromagnetic brake

Lamps and lanterns: 12V LED taillight, 7-pin plug

Cooking utensil: Draw integrated stainless steel kitchenware

 Cistern:
 40L

 Roof rack:
 1

 Spare tire:
 1

 Tent:
 1

 Safety chain:
 2

 Water pump:
 1

 Battery:
 No

Surface treatment: baking varnish

Colour: Light grey/dark grey(Optional)



ECOSIGHT POWER TECHNOLOGY CO.,LTD

www.ecosightpower.com www.ecosightpower.com

WhatsApp: +86 15217026015 Hot-Line: +86 15217026015

Email: info@ecosightpower.com

Add: #,2ndFloor,BlockBJianyeBuilding,No7Nonglin Road,FutianDistrict,henzhenCity,Guangdong,China