


Declaration of Performance

ABG33010607 / ABG330106075 / ABG33010608 / ABG330106085 / ABG33010609

Unique identification code of the product-type	6" Steel Reinforced Precast Concrete Lintels (2.13m to 2.74m)									
Intended use(s)	Product intended to be used in walls and partitions									
Manufacturer	Cementstone Manufacturing Company Ltd. C 7758 Attard Bros Group, 'MikeSand', Industrial Zone, Ta' Qali, Malta ATD 4000									
Notified Bodies	TZUS No. 1020, conducted load bearing capacity and short deflection assessment of performance by testing KIWA No. 0770, conducted fire resistance assessment of performance by calculation									
Authorised Representative	Andrew Vella									
System of AVCP	System 3									
Harmonised Standard	EN 845-2:2013+A1:2016									
			Essential Characteristics							
Characteristic	Clause	Units	Value							
Overall Lintel Length	5.2.1	[mm]	2130	2290	2450	2590	2740			
Load Bearing Capacity	5.3.1.3	[kN/m]	69.3	64.3	60.2	56.5	53.3			
Short Term Deflection	5.3.1.4	[mm]	2.7	3.3	4.1	4.9	5.8			
Water absorption	5.9	-	Not to be left exposed							
Water vapour permeability	5.10	-	$30 < \mu < 100$							
Direct airborne sound insulation / Mass per unit area	5.2.2	[kg/m ²]	NPD							
Thermal Resistance	5.6	[W/m.K]	$\lambda_{10, dry, mat} = 1.24$ (Concrete)							
Resistance to Fire	5.8	-	R30							
(Strength) Durability	5.4	-	Not to be left exposed Steel Grade: B500B; Concrete Grade C25/30							

X - not relevant

* Subject to normal maintenance

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued in accordance with the Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Andrew Vella at Cementstone Manufacturing Company Ltd, Attard Bros Group, Ta' Qali

on [date of issue] 24th July 2026



[signature]



Cementstone Manufacturing Company Ltd. C 7758
Attard Bros Group, 'MikeSand', Industrial Zone, Ta' Qali, Malta, ATD 4000

26

EN 845-2:2013+A1:2016

EN 845-2:2013+A1:2016

Product			6" Steel Reinforced Precast Concrete Lintels (2.13m to 2.74m)									
Product Code			ABG33010607 / ABG330106075 / ABG33010608 / ABG330106085 / ABG33010609									
Intended use			In Walls and Partitions									
Characteristics	Clause	Units	Value									
Overall Lintel Length	5.2.1	[mm]	2130	2290	2450	2590	2740					
Load Bearing Capacity	5.3.1.3	[kN/m]	69.3	64.3	60.2	56.5	53.3					
Short Term Deflection	5.3.1.4	[mm]	2.7	3.3	4.1	4.9	5.8					
Water Absorption	5.9	-	Not to be left exposed									
Water Vapour Permeability	5.10	-	30 < μ < 100									
Direct Airborne Sound Insulation / Mass per Unit Area	5.2.2	[kg/m2]	NPD									
Thermal Resistance	5.6	[W/m.K]	λ10,dry,mat = 1.24 (Concrete)									
Resistance to Fire	5.8	-	R30									
(Strength) Durability	5.4	-	Not to be left exposed Steel Grade: B500B; Concrete Grade C25/30									
X - not relevant * Subject to normal maintenance												
For other information visit our website: www.attardmaterials.com												