

MATERIAL SAFETY DATA SHEET

Date of issue: August 16, 1999

Revision Date: Feb 13, 2019

SECTION 01: PRODUCT INFORMATION

Manufactured For: Timber Pro Coatings Ltd
140 -12051 Horseshoe Way
Richmond, B.C.
V7A 4V4
(604) 270-4244

Product Name: Clean & Brite

Product Type: Wood Cleaner and Brightener

UN Number: Not applicable

Product Class: Cleaner

C.A.S. Number: Mixture

SECTION 02: HAZARDOUS INGREDIENTS

Component	CAS No.	Amount	LD50/LC50
Phosphoric Acid (corrosive)	7664-38-2	5-10%	Oral, rat: LD50 = 1530 mg/kg; Skin, rabbit: LD50 = 2740mg/kg

SECTION 03: PHYSICAL DATA

Physical State: Liquid	Solubility in Water: Soluble
Appearance: Blue	Odour Threshold: N/A
Odor: Phosphorous scent	Vapour Density: N/A
Evaporation Rate: N/A	Vapour Pressure: N/A
Boiling Point: 100°C (212°F)	PH: 1.0 +/- 0.5
Freezing/Melting Point: 0°C (32°F)	Acid Reserve: N/A
Coefficient of Oil/Water distribution: N/A	Specific Gravity: N/A
Viscosity: N/A	*N/A=No data available

SECTION 04: FIRE AND EXPLOSION DATA

Conditions of Flammability: May evolve hydrogen when in contact with chlorides and stainless steel.

Flash Point and Method of Determination: N/A

Lower Flammable (Explosive) Limit (LFL/LEL): N/A

Upper Flammable (Explosive) Limit (UFL/UEL): N/A

Auto-Ignition Temperature: N/A

Means of Extinction: Use media appropriate for containment. Cool off containers with water spray.


Hazardous Combustion Byproducts: May evolve oxides of carbon/sulfur, phosphine, phosphorus, and hydrogen gas.

Explosion Data – Sensitivity to Mechanical Impact: N/A

Explosion Data – Sensitivity to Static Discharge: N/A

Clean & Brite MSDS

CONTINUED



SECTION 05: REACTIVITY DATA

Unstable: No
If Unstable, Under Which Condition: N/A
Incompatible Materials: Alkalis, oxidizers, aldehydes and ketones.
Conditions of Reactivity: Sunlight or long-term exposure to ambient air in an open enclosure may cause product degradation however none should be hazardous.
Hazardous Decomposition Products: N/A

SECTION 06: TOXICOLOGICAL PROPERTIES/HEALTH HAZARD DATA

Routes of Entry/Exposure:
Skin Contact – Yes, **Skin Absorption** – Yes, **Eye Contact** – Yes, **Inhalation** – No
Ingestion – Yes.
Effects of Acute Exposure to Product: May cause inflammation or burns upon acute contact.
Effects of Chronic Exposure to Product: May cause dermatitis upon prolonged exposure to dilute solutions.
Exposure Limits: Phosphoric Acid: ACGIH 1mg/m³; 3mg/m³ STEL, NIOSH 1mg/m³ TWA 1000mg/m³ IDLH; OSHA – Final PELs 1mg/m³ TWA
Irritancy of Products: May cause irritation or burns to skin, eyes, and mucous membranes.
Sensitization to Product: Not expected to occur.
Carcinogenicity: Not listed by ACGIH, IARC, NIOSH, NTP, or OSHA.
Reproductive Toxicity: No adverse reproductive effects were seen in rats fed 0.4000 ppm in diet since weaning and mated at 32 wk & 43 wk or offspring fed the same diet after weaning. (Bonting. S.L. et al Voeding).
Teratogenicity: No data available.
Mutagenicity: EPA Genotox program 1988, Negative: cell transform – SA7/SHE activation negative (AL-anl. F. Y. Mutal Res. 1988) metabolic activation negative (Blofax data sheets 1970).
Names of Toxicologically Synergistic Materials: No data available.

SECTION 07: First Aid Measures

Inhalation: Immediately remove victim to fresh air. If breathing is difficult, have qualified personnel administer oxygen. If breathing has stopped, administer artificial respiration. Get immediate medical attention.
Skin: Immediately flush skin with water for 15 minutes while removing contaminated shoes and clothing.
Eyes: Immediately flush victims eye with large quantities of water for at least 15 minutes, holding the eyelids apart. Remove contact lenses if present. Get immediate medical attention.
Ingestion: Do not induce vomiting. If conscious, give victim plenty of water to dilute concentration. Get immediate medical attention. Small amounts of milk may be used after water is administered if requested.

**SECTION 08: Preventative Measures**

Engineering Controls: Use with general or adequate local exhaust ventilation to maintain exposures below the occupational exposure limits.

Personal Protective Equipment:

Protective Clothing: Wear chemically impervious long-gloves, aprons and boots such as nitrile, neoprene or butyl rubber

Eye Protection: Wear appropriate protective eyeglasses or chemical safety goggles described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European standard EN166.

Respiratory Protection: Follow the OSHA respirator regulations found in 29CFR 1910.134 or European Standard EN149. Always use a NIOSH or European standard EN 149 approved.

Storage Requirements: Store in a cool, dry place out of the sunlight in a well ventilated area away from the other types of chemicals.

Handling Procedures and Equipment: Avoid contact with eyes, skin, and clothes. Avoid breathing mist. Wear protective gear. Wash after handling. Keep closed when not in use.

Leak/Spill Clean-up: Wear protective gear. Small spills can be neutralized with diluted soda ash. Collect with absorbent and place into appropriate containers. Prevent spill from enter sewers and watercourses. Report release as required by local, provincial and federal authorities.

Waste Disposal: Dispose of in accordance with local, provincial and federal regulations. Do not reuse containers.

Special Shipping Information: Corrosive liquid (phosphoric acid) UN 1805, PG III Class 8

SECTION 09: Preparation Information

Prepared For: Timber Pro Coatings

Phone Number: 604-270-4244

Prepared On: Aug. 20,2008

CAS# 7664-38-2 is listed on Canada's DSL list.

This product has a WHMIS classification of E (corrosive).

CAS# 7664-38-2 is listed on Canada's Ingredient Disclosure List.

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

Disclaimer: While Timber Pro Coatings believes the data contained herein are accurate and derived from qualified sources, the data are not to be taken as a warranty or representation for which Timber Pro Coatings assumes legal liability. They are offered solely for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with Federal, State and Provincial and local laws and regulations.



Clean & Brite

Technical Data Sheet

March 19 2013

Description

Clean & Brite is a one-step maintenance cleaner for all your exterior wood surfaces. Clean & Brite will remove dirt, mold, mildew and mild graying from your wood surfaces. Clean & Brite is used as pretreatment cleaner prior to finishing wood with the Timber Pro UV coatings. It can be used on new wood for preparation prior to coating or for old coated surfaces to clean and prepare prior to coating.

Where to Use

The following are areas where the Clean & Brite may be used.

- sidings
- trims
- shakes
- decks
- timber & logs
- entry & garage door
- shutters

Features and Benefits

- Biodegradable water-based formula
- Cleans and brightens the wood in one step
- Does not contain harmful bleach

Color Range and Packaging

Color	Blue/green as supplied
Packaging	1 US gallon 5 US gallon pail



Clean & Brite

Technical Data Sheet
March 19 2013

Properties

Viscosity -	N/A
pH -	2.4
V.O.C. -	0 grams/L
Weight per gallon-	8.56 lbs/gal
S.G -	1.03

Shelf Life

Approximately two years in an unopened container

KEEP FROM FREEZING

Coverage

Smooth Wood: 300-400 square feet per gallon of concentrate

Application

Use a garden pump spray applicator and or nylon polyester brush

Product Disclaimer

The technical information and suggestions for use herein are based on Timber Pro Coatings Ltd research and experience and believed to be reliable. But such information and suggestions do not constitute a warranty. Since Timber Pro Coatings has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves by preliminary tests or otherwise the suitability of the product for their purposes.

Timber Pro Coatings Ltd
#140-12051 Horseshoe Way, Richmond, BC V7A 4V4
Ph: 604-270-4244 Fax: 604-270-4247 Toll Free: 1-877-666-4244
Email: canadainfo@timberprocoatings.com

PROCHAINEMENT