



# Ultra LS Formula

## Technical Data Sheet

Rev 1: November 1, 2016

**Clear**

**TR-Series**

**ST-Series**

**SS-Series**

### Description

Timber Pro Ultra LS Formula Natural Oil Wood finish is a premium exterior wood finish formulated with a unique blend of natural oils and resins. Ultra LS Formula not only accentuates the natural beauty of the wood but it also provides unsurpassed protection against the damaging UV rays from the sun and destructive effects of the elements.

### Where to Use

Timber Pro Ultra LS Formula can be used on all new and reconditioned wood exterior and interior vertical surfaces. The Ultra LS Formula can be used on all wood species such as cedar, fir, pine, cypress, redwood, spruce exterior grade plywood and pressure treated wood. The following are areas of use for the Ultra LS Formula.

- Log Homes
- exterior sidings
- doors/windows
- shingles
- shakes
- outdoor furniture
- trim
- planters

#### RESTRICTIONS

Always use a color from one of the color series before using the clear

- Do not use clear alone for exterior surfaces
- Do not thin
- Do not apply over previously coated surfaces

### Features and Benefits

- Can be used in interior and exterior wood surfaces
- Low V.O.C.
- Excellent UV protection
- Excellent weathering properties
- Large color range
- Easy soap and water cleanup



# Ultra LS Formula

## Technical Data Sheet

2016

Rev1: November 2,

|              |                  |                  |                  |
|--------------|------------------|------------------|------------------|
| <b>Clear</b> | <b>TR-Series</b> | <b>ST-Series</b> | <b>SS-Series</b> |
|--------------|------------------|------------------|------------------|

### Color Range and Packaging

**Color :** Clear

|              |                  |                     |
|--------------|------------------|---------------------|
| (TR series ) | Transparent      | 25 colors available |
| (ST series ) | Semi Transparent | 22 colors available |
| (SS series ) | Semi Solid       | 14 colors available |

**Packaging:** 1 US Gallon  
5 US gallon Pail

### Properties

|                           |  |
|---------------------------|--|
| <b>Viscosity -</b>        | 20-23 secs Zahn cup #2   |
| <b>Gloss Level -</b>      | Satin 25 - 35 GU @ 60 degree   |
| <b>Solids by Weight -</b> | 21.5 % +/- 1%  |
| <b>Solids by Volume -</b> | 21.8% +/- 1%   |
| <b>V.O.C. -</b>           | 86 g/l minus water   |
| <b>Weight per gallon-</b> | 8.4 lbs./Gal.  |
| <b>Specific Gravity-</b>  | 1.01   |
| <b>Dry Time -</b>         | 2-4 touch dry<br>16 hours through dry<br>Note dry times will be extended at low temperatures and high humidity |

### Shelf Life

Approximately two years in an unopened container

**KEEP FROM FREEZING**

### Coverage

Smooth Wood: 250-300 square feet per gallon

Rough Wood : 150 – 200 square feet per gallon

Hardwoods: 300-400 square feet per gallon

Note : Coverage will vary with the porosity of the wood



# Ultra LS Formula

## Technical Data Sheet

Rev3: November 2008

**Clear**

**TR-Series**

**ST-Series**

**SS-Series**

### Application

Use a spray applicator , Roller or nylon polyester brush

### Clean Up

With soap and mild detergent

### Product Disclaimer

The technical information and suggestions for use herein are based on Timber Pro Coatings Ltd research and experience and believed to be reliable. But such information and suggestions do not constitute a warranty. Since Timber Pro Coatings has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves by preliminary tests or otherwise the suitability of the product for their purposes.

#### **Timber Pro Coatings Ltd**

#140 – 12051 Horseshoe Way, Richmond, BC V7A4V4  
Ph: 604-270-4244 Fax: 604-270-4247 Toll Free: 1-877-666-4244  
Email: [canadainfo@timberprocoatings.com](mailto:canadainfo@timberprocoatings.com)