PALLISER ENCORE



MODEL#: 41757 D-BOX: DBX-2 Chair





PRODUCT FEATURES & BENEFITS

D-BOX is changing the way you watch movies by moving the body and sparking the imagination through motion. With D-BOX, you control the intensity so guests can move with the movie and feel every scene as if they were in it. Blur the line between your guests and the screen to create hyper-realistic, immersive, one-of-a-kind entertainment experiences that pull your guests into the story like never before.

- Our design incorporates flip seats for easy access to the motor. Save time on cleaning, maintenance and servicing with a quick lift of the seat.
- Heavy duty plastic protective outer back shell.
- Self-lubricating brass bushings for long lasting noise free performance.
- 7-gauge powder coated steel construction.
- Ultra-smooth rocking action.
- 9.75" (24.8 cm) floor to footrest clearance for fast and efficient cleaning between show times.
- Quick and easy 2-piece installation.
- Heavy duty polyurethane cover material with antimicrobial finish for easy cleaning and durability while providing the look and feel of leather.
- High-resiliency seat foam offers superior durability and comfort.
- Plywood frames and steel chassis mechanism offers exceptional durability and stability.





TECHNICAL SPECIFICATIONS:

CUSHIONING:

SEAT CUSHION: • High Resiliency (HR) polyurethane foam.

DENSITY: • 2.2 lbs., 35 kg/m³

BACK REST: • Polyester foam.

• Heavy duty plastic outer back shell.

FLAMMABILITY: • CAL TB 117-2013

NFPA 260 Class 1

• UFAC Class 1

MVSS 302 Pass

COVER MATERIAL: • Dillon Polyurethane

CONTENT: • 100% Polyurethane

BACKING: • 70% Polyester, 30% Cotton

FINISH: • Antimicrobial—Silver Based Ion Technology

ABRASION: • Heavy Duty—Exceeds 200,000 Cycles

(Wyzenbeek - #8 Cotton Duck Abradant) (ASTM D4157)

FRAME: • Constructed with hardwood and engineered wood products; joints are

pinned and glued for uniformity and strength.



ELECTRICAL SPECIFICATIONS:

POWER SUPPLY: (IF APPLICABLE)

- Input voltage 100-240 V, 50 Hz/60Hz, 1.8A
- Output voltage 29V==3A
- Duty cycle: max 10%; Max T_ON: 2 min.

LED LIGHTING: (IF APPLICABLE)


- Operating voltage: 29VDC +/- 5% (regulated)
- Required amperage at operating voltage: 16.5 mA +/- 5%
- Endurance: 100,000 hoursLight flux output: 120 lm
- Ambient operating temperature: +5°C to + 55°C (41°F to 131°F)


DBX-2 Chair Series



Arm Width: 5.5"/14 cm • Standard Seat Width: 21.5"/54.6 cm


FULL UPRIGHT POSITION






1N: Two Arm Non Recliner W: 32.5"/82.5cm


MINIMUM REQUIREMENTS



ELEVATION VIEWS



Level Floor Seat Options





AVAILABLE OPTIONS













REVISIONS

REVISION #	CHANGES MADE
1	Updated per Nelson & Ben's comments
2	Removed under seat light from options on page 6
3	CAD spec updated FO 07-28-2025