## 14K BLACKHAWK FULL DECK TILT BED



### STANDARD FEATURES

- Adjustable 2 5/16" Coupler
- 16" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- 4 D-Rings
- 2" x 6" #2 or Better Fir Decking
- Tube Tongue (longer than competition)
- 12K Drop Leg Tongue Jack
- Brakes on Both Axles

- Spare Tire Mount
- Heavy Duty Diamond Plate Fenders
- Cushioning Hydraulic Cylinder
- 30" Steel Rear Approach in Addition to Length
- · Stake Pockets and Heavy Duty Rub Rail
- Over Center Latch with Release
- 83" Between Fenders
- Front Diamond Plate Fender Steps

### **POPULAR OPTIONS**


- Tongue Box Steel or Aluminum Diamond Plate
- Cushioning Hydraulic Cylinder with Lock out Valve
- Tower Winch Mount/Bump Rail Mount
- 1/8" Steel Diamond Plate or Smooth
- · Removable Fenders
- · Pressure Treated Decking

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
<b>BHTB718TA5</b>	7' x 18' 14K Blackhawk Tandem Axle Full Tilt	14,000	2,530
<b>BHTB720TA5</b>	7' x 20' 14K Blackhawk Tandem Axle Full Tilt	14,000	2,680
ВНТВ722ТА5	7' x 22' 14K Blackhawk Tandem Axle Full Tilt	14,000	2,830
ВНТВ724ТА5	7' x 24' 14K Blackhawk Tandem Axle Full Tilt	14,000	2,980

# 14K BH FULL DECK TILT BED TRAILER SPEC SHEET

STANDARD SPECIFICATIONS				
GVWR	14,000#	GAWR	14,000#	
Frame	6" Channel	Cross Members	3" Channel, 16" on Center	
Axle	(2) 7,000# Posi-Lube Axles with Brakes	Cross Members		
Coupler	Adjustable 2 5/16" Coupler	Fenders	81 1/2" Between Fenders 10" x 72" Diamond Plate	
Coupler Height	Adjustable			
Deck Height	22"	Suspension	Multi-Leaf Spring	
Tongue	2" x 6" Rectangular Tube	Ramps	30" Steel Rear Approach	
Jack	12K Drop Leg	Uprights	N/A	
Safety Chain	36" x 3/8" 16.2K Capacity	Bump Rail	2" x 2" Rectangle Tube, 6" High	
Wheels	16 x 6 8 - 6.5 Mod (Black)	Lights	Sealed Beam LED D.O.T	
		Decking	2" x 6" #2 or Better Fir Decking	
Tires	ST 235/80 R16 Load Range E	Electric Plug	7-Way RV Molded Water Tight Plug	
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint	

## **STANDARD COLORS**



## **OPTIONAL COLORS**

