verifone

UX700-4G

Deliver full, secure self-service transactions with Verifone's robust all-weather unattended solution.

From vending machines to public transit to parking kiosks, the UX700 is built to handle a range of self-service and countertop applications. Its weather- and impact-resistant build, compact footprint, and full payment support make it suitable for high-volume environments, inside or outdoors.

Key Features

Customer experience

- Provide a complete customer experience with the **5" HD touchscreen** and **integration with POS and peripherals**
- Scan codes for loyalty, coupons, or APM with the dedicated **barcode camera**
- Robust design provide durability for both **indoor and outdoor use**

Power and performance

- **Qualcomm quad-core A53 processor** boosts apps performance
- Stay connected anywhere with **Wi-Fi and 4G LTE**
- **Connect to Verifone's cloud-based services** to enable application management.

Secure the sale

- Keep transactions safe with **PCI 7 compliance.**
- Run powerful apps with **Android 13**
- Verifone sets the standard for accessibility with **the award-winning Navigator app**.*

PERFORMANCE				
Processor	Qualcomm QCM2290 A53 quad-Core @ 2.0GHz	**Power**	• 9-43V DC power supply • Low power mode	
Memory	• 2GB RAM + 32GB Flash • MicroSD card slot	**OS**	Verifone Secure OS • Engage VOS3 • VAOS based on Android 13	
Display	5" color LCD with capacitive multi-touch	**Resolution**	720x1280 HD	
Camera	Top 5MP FF	**Scanner**	Bottom 2MP FF camera	
Multimedia	Speaker, buzzer, microphone, and headset jack	**Security**	PCI PTS 7.x approved	

CONNECTIVITY				
Wi-Fi	Wi-Fi 2.4GHz b/g/n 5GHz 802.11 a/n/ac	**Bluetooth**	Bluetooth® v5.0	
Cellular	4G LTE	**SIM**	• eSIM • SIM, SAM/SIM, 2x SAM slots	
Wired	Ethernet, MDB, USB-client, 3x USB-host, 2x RS232			

PAYMENT ACCEPTANCE				
Card Reader	• MSR ISO 7810, 7811, 7813 • Smartcard EMVCo approved	**Contactless**	• MiFare • EMVCo Approved	
NFC/CTLS schemes	Supports major NFC/CTLS schemes	**APM supported**	Supports advanced payment methods	

PHYSICAL				
Size	70mm x 106.6mm x 146mm	**Weight**	583g	
Impact rating	IK09	**IP rating**	IP65	
Operating temperature	-30º to 70ºC (-22º to 158ºF)	**Storage temperature**	-30º to 80ºC (-22º to 176ºF)	
Relative humidity	5% to 90%, Non-condensing			

ADDITIONAL FEATURES				
Accessibility	• Navigator software* • Navigator stencil	**Accessories**	• 3rd party mounting pole • Stylus	

*Navigator software is supported on Android-based terminals only; not available on standard deployments of Linux-based devices. Availability and solutions may vary by region.