



# S190 TRIPLE DECK SCREENER

Arguably the most popular screener in its class, the S190 Triple Deck pushes industry performance standards and leads the competition as one of the most advanced and innovative portable vibratory screening plant in operation today. The S190 Dual Power brings versatility to any site, while reducing operational costs and CO<sub>2</sub> emissions. This High Energy Screener clearly demonstrates McCloskey's focus on making customer focused features standard.

## FEATURES

- ✓ 6100mm x 1524mm (20' x 5') heavy duty high energy 2 bearing 3 deck screenbox.
- ✓ 98 kW (130Hp) engine
- ✓ Integrated hydraulic folding stockpiling conveyors
- ✓ Remote control tipping grid
- ✓ Fast on-site setup time – 15 minutes typically

## S190 TECH SPECS

Engine 98 kW (130Hp)

Stockpile Height  
Tail Conveyor 4.64m (15' 3")  
Side Conveyor 5.10m (16' 9")

Screenbox  
Top Deck 1.52m x 6.10m  
(5' x 20')  
Middle Deck 1.52m x 6.10m  
(5' x 20')  
Bottom Deck 1.52m x 5.49m  
(5' x 18')

## TRANSPORT

Height 3.45m (11' 4")  
Length  
12' Hopper 17.54m (57' 6")  
15' Hopper 18.45m (60' 6")  
Width  
500mm Conveyor 3.06m (10')  
650mm Conveyor 3.24m (10' 7")  
Weight 38,780kgs  
(85,495lbs)

## OPTIONS

Single or double deck live head | Single shaft shredder

DUAL POWER



Features such as the adjustable screenbox angles allow adaptability to a wide range of material applications including quarrying, mining, sand and gravel, coal screening, topsoil, and woodchip.

With the highest grade specifications and component parts, the S190 is easily the number one choice for high productivity, quality and value. The S190 has the highest combined true screening area across three decks.

This class leading screening area, along with its high energy screening action, ensure that the McCloskey triple deck models are the superior choice in aggregate material screening.

