



# S80 PORTABLE SCREENER

The S80 is designed for users who require less capacity than the S130 and S190 models offer, but are not willing to sacrifice the quality features found on the McCloskey® S-Range. These features include a High Energy Screenbox, large hopper, and large engine bay.

## FEATURES

- ✓ 3050mm x 1370mm (10' x 4.5') heavy duty high energy 2 bearing screenbox
- ✓ 98 kW (130Hp) engine
- ✓ Integrated hydraulic folding stockpiling conveyors
- ✓ Remote control tipping grid
- ✓ Fast on-site setup time – 10 minutes typically
- ✓ Track or wheel mobile

## S80 TECH SPECS

Engine	97 kW (130 Hp)
Screenbox Dimensions Top Deck	3050mm x 1370mm (10' x 4.5')
Screenbox Dimensions Bottom Deck	2440mm x 1370mm (8' x 4.5')
Stockpile Height Tail Conveyor Side Conveyor	3790mm (12' 5") 4110mm (13' 6")

## TRANSPORT

Transport Height	3.20m (10' 6") Tracked
Transport Length	13.21m (44' 4") Tracked
Transport Width	2.50m (8' 4")
Weight Tracked	19,250kgs (42,439 lbs)

## OPTIONS

2 Deck Live Head  
Single Shaft Shredder



The S80 can employ the steepest screen angle of any three- way-split screening plant currently available, ensuring best-in-class screening ability in materials like sand and peastone.

Users with smaller floats or in areas with strict transport regulations will benefit from the smaller transport dimensions.

