

RAVEN HP XL

DISSOLVABLE FRAC PLUG

DESCRIPTION

The Dissolvable RAVEN HP XL is a High-Pressure Frac Plug with predictable dissolve rates in as little as 1% brine fluid that isolate lower zone and to perform fracturing. By having a "Metal to Metal" seal, with a "Rubber Seal" as backup, makes it possible for operations in high-temperature wells.

The Plug in the "Ball-Drop" version come with the LARGEST Ball-drop ID on the market! Thats gives the tool its name "XL"

This large ID allows for unrestricted production directly after Stimulation has finished.

The Plug is set for conventional Setting Equipment.

The Raven is designed to be our shortest Dissolvable Frac Plug. By having only one set of slips and a unique expandable element.

The RAVEN HP XL is manufactured to fit the desired casing size.

FEATURES

- Can be engineered for most wellbore fluid conditions
- Minimal debris
- Engineered to dissolve
- High-pressure
- Largest ID on the Market



Casing size in - [mm]	Wall thickness Min-Max [mm]	Plug OD in - [mm]	Packer ID in - [mm]	Pressure Rating Psi - [Bar]
4.5 - [114.3]	0.29 - [7.37]	3.66 - [93]	2.5 - [63.5]	12500 - [862]
	0.337 - [8.56]	3.58 - [90.9]	2.5 - [63.5]	15000 - [1034]
	0.38 - [9.65]	3.5 - [88.9]	2.25 - [57.2]	15000 - [1034]
5 - [127]	0.362 - [9.19]	3.95 - [100.3]	2.77 - [70.4]	12500 - [862]
5.5 - [139.7]	0.361 - [9.17]	4.5 - [114.3]	3.35 - [85.1]	12500 - [862]
	0.415 - [10.54]	4.4 - [111.8]	3.35 - [85.1]	15000 - [1034]