


Intercom Specifications






Intercom

Specifications

2025



Power

DC 2-wire 24VDC

Power Over Ethernet 802.3bt with 50W+

Power Consumption Typical: 20W, max: 50W

Features

Intuitive user interface with tactile buttons

Receive audio calls at any US phone number

Receive video and audio calls in the Latch App (video requires external camera)

Remote unlock

Compatible with the Fanvil i10d in-unit PBX receiver

Flexible connectivity options: Ethernet, Wi-Fi, and Cellular



Screen

Brightness 1000 nits, automatic brightness adjustment

Viewing Angle 176 degrees

Size 7-inch diagonal

Protection Anti-reflection, anti-fingerprint. Made with Corning® Gorilla® Glass 3

Audio and Video

Loudness Automatic volume adjustment, 90dB max volume

Microphone Automatic sensitivity adjustment, dual microphone, echo cancellation, and noise reduction

Supported Cameras Works with Latch camera

Communication

Ethernet 10/100/1000 mbps

Wi-Fi 2.4/5 GHz, 802.11a/b/g/n/ac

Cellular Category 1

Bluetooth Bluetooth 4.2

IP Address DHCP or Static IP

Environmental

Operating Temperature -30°C to 60°C

Dust and water resistance IP65

Certifications

Certifications FCC Part 15 Subpart B/C/E, FCC Part 24, IC RSS-130/133/139/247, PTCRB,

UL62368-1, UL294, IP65

Compliance Complies with American Disabilities Act

Mechanical Specifications

Dimensions 12.82 x 6.53 x 1.38 inches | 325.6 x 166.0 x 35.1 mm

Materials Stainless steel, glass fiber reinforced resin, and impact-resistant glass