


## EdisonGrip™ Standard Locking Cable Ties

Reliable, high-strength Nylon 6.6 cable ties designed for fast, secure bundling in industrial, commercial and OEM applications. Excellent chemical resistance and certified performance ensure long-lasting durability indoors and outdoors.



### KEY BENEFITS

- **Strong grip** with smooth, low-insertion installation
- **Durable Nylon 6.6** — natural or UV-black (carbon-black UV stabilized)
- **Wide temperature range:** -40°C to +85°C (-40°F to +185°F), short-term to +110°C (230°F)
- **Resistant** to oils, greases, bases & chloride solvents
- **UL94 V-2 flammability**, plenum rated
- **Approvals:** UL 62275 (File E548357), EN 62275:2019, CE, UKCA, TÜV, DNV-GL, RoHS, REACH, PAHs-Free



\*All SKU's available in 100 packs

Miniature Cable Ties 18Lbs (80N)								Competitor Cross Reference		
EG Part Number	Length (In.)	Bundle Diameter (In.)	Width (In.)	*Standard Pack Size (EA)	Color	UV Resistant	cULus Listed	ABB - Thomas & Betts	Hellerman Tyton	Panduit
EG-S-3.1IN-18LB-NA-1000	3.1"	0.12 - 0.55"	0.01"	1000	Natural	No	✓ UL 62275 Type 21	-	T18S9M4 (3.3")	-
EG-S-3.1IN-18LB-BK-1000	3.1"	0.12 - 0.55"	0.01"	1000	Black	✓	✓ UL 62275 Type 21	-	T18S0M4 (3.3")	-
EG-S-4IN-18LB-NA-1000	4.0"	0.12 - 0.81"	0.01"	1000	Natural	No	✓ UL 62275 Type 21	TY23M (3.6")	T18R9M4 (4")	PLT1M-M (3.9")
EG-S-4IN-18LB-BK-1000	4.0"	0.12 - 0.81"	0.01"	1000	Black	✓	✓ UL 62275 Type 21	TY23MX (3.6")	T18R0M4 (4")	PLT1M-M0 (3.9")
EG-S-4.7IN-18LB-NA-1000	4.7"	0.12 - 1.06"	0.01"	1000	Natural	No	✓ UL 62275 Type 21	-	-	-
EG-S-4.7IN-18LB-BK-1000	4.7"	0.12 - 1.06"	0.01"	1000	Black	✓	✓ UL 62275 Type 21	-	-	-
EG-S-5IN-18LB-NA-1000	5"	0.12 - 1.18"	0.01"	1000	Natural	No	✓ UL 62275 Type 21	-	-	-
EG-S-5IN-18LB-BK-1000	5"	0.12 - 1.18"	0.01"	1000	Black	✓	✓ UL 62275 Type 21	-	-	-
EG-S-6IN-18LB-NA-1000	6"	0.12 - 1.44"	0.01"	1000	Natural	No	✓ UL 62275 Type 21	-	T18I9M4 (5.5")	PLT1.5M-M (5.6")
EG-S-6IN-18LB-BK-1000	6"	0.12 - 1.44"	0.01"	1000	Black	✓	✓ UL 62275 Type 21	-	T18I0M4 (5.5")	PLT1.5M-M0 (5.6")
EG-S-6.3IN-18LB-NA-1000	6.3"	0.12 - 1.57"	0.01"	1000	Natural	No	✓ UL 62275 Type 21	-	-	-
EG-S-6.3IN-18LB-BK-1000	6.3"	0.12 - 1.57"	0.01"	1000	Black	✓	✓ UL 62275 Type 21	-	-	-
EG-S-8IN-18LB-NA-1000	8"	0.12 - 2.07"	0.01"	1000	Natural	No	✓ UL 62275 Type 21	TY232M (8")	T18L9M4 (8")	PLT2M-M (8")
EG-S-8IN-18LB-BK-1000	8"	0.12 - 2.07"	0.01"	1000	Black	✓	✓ UL 62275 Type 21	TY232MX (8")	T18L0M4 (8")	PLT2M-M0 (8")
EG-S-10.2IN-18LB-NA-1000	10.2"	0.12 - 2.87"	0.01"	1000	Natural	No	✓ UL 62275 Type 21	-	-	-
EG-S-10.2IN-18LB-BK-1000	10.2"	0.12 - 2.87"	0.01"	1000	Black	✓	✓ UL 62275 Type 21	-	-	-
EG-S-15IN-18LB-NA-1000	15"	0.12 - 4.33"	0.01"	1000	Natural	No	✓ UL 62275 Type 21	TY234M (14")	-	-
EG-S-15IN-18LB-BK-1000	15"	0.12 - 4.33"	0.01"	1000	Black	✓	✓ UL 62275 Type 21	TY234MX (14")	-	-

Intermediate Cable Ties 40 Lbs (180N)								Competitor Cross Reference		
EG Part Number	Length (In.)	Bundle Diameter (In.)	Width (In.)	*Standard Pack Size (EA)	Color	UV Resistant	cULus Listed	ABB – Thomas & Betts	Hellerman Tyton	Panduit
EG-S-5.5IN-40LB-NA-1000	5.5"	0.14 - 1.30"	0.14"	1000	Natural	No	✓ UL 62275 Type 21	TY24M (5.5")	-	PLT1.5I-M (5.6")
EG-S-5.5IN-40LB-BK-1000	5.5"	0.14 - 1.30"	0.14"	1000	Black	✓	✓ UL 62275 Type 21	TY24MX (5.5")	-	PLT1.5I-M0 (5.6")
EG-S-6IN-40LB-NA-1000	6"	0.14 - 1.42"	0.14"	1000	Natural	No	✓ UL 62275 Type 21	-	-	-
EG-S-6IN-40LB-BK-1000	6"	0.14 - 1.42"	0.14"	1000	Black	✓	✓ UL 62275 Type 21	-	-	-
EG-S-7.1IN-40LB-NA-1000	7.1"	0.14 - 1.81"	0.14"	1000	Natural	No	✓ UL 62275 Type 21	-	-	-
EG-S-7.1IN-40LB-BK-1000	7.1"	0.14 - 1.81"	0.14"	1000	Black	✓	✓ UL 62275 Type 21	-	-	-
EG-S-8IN-40LB-NA-1000	8"	0.14 - 2.07"	0.14"	1000	Natural	No	✓ UL 62275 Type 21	TY242M (8.2")	-	PLT2I-M (8")
EG-S-8IN-40LB-BK-1000	8"	0.14 - 2.07"	0.14"	1000	Black	✓	✓ UL 62275 Type 21	TY242MX (8.2")	-	PLT2I-M0 (8")
EG-S-8.5IN-40LB-NA-1000	8.5"	0.14 - 2.24"	0.14"	1000	Natural	No	✓ UL 62275 Type 21	-	T40R9M4 (8.3")	-
EG-S-8.5IN-40LB-BK-1000	8.5"	0.14 - 2.24"	0.14"	1000	Black	✓	✓ UL 62275 Type 21	-	T40R0M4 (8.3")	-
EG-S-9.8IN-40LB-NA-1000	9.8"	0.14 - 2.68"	0.14"	1000	Natural	No	✓ UL 62275 Type 21	-	-	-
EG-S-9.8IN-40LB-BK-1000	9.8"	0.14 - 2.68"	0.14"	1000	Black	✓	✓ UL 62275 Type 21	-	-	-
EG-S-11IN-40LB-NA-1000	11"	0.14 - 3.07"	0.14"	1000	Natural	No	✓ UL 62275 Type 21	TY26M (11.2")	-	-
EG-S-11IN-40LB-BK-1000	11"	0.14 - 3.07"	0.14"	1000	Black	✓	✓ UL 62275 Type 21	TY26MX (11.2")	-	-
EG-S-11.8IN-40LB-NA-1000	11.8"	0.14 - 3.31"	0.14"	1000	Natural	No	✓ UL 62275 Type 21	-	T40I9M4 (11.6")	PLT3I-M (11.4")
EG-S-11.8IN-40LB-BK-1000	11.8"	0.14 - 3.31"	0.14"	1000	Black	✓	✓ UL 62275 Type 21	-	T40I0M4 (11.6")	PLT3I-M0 (11.4")
EG-S-14.6IN-40LB-NA-1000	14.6"	0.14 - 4.17"	0.14"	1000	Natural	No	✓ UL 62275 Type 21	TY244M (14.5")	T40L9M (14.6")	PLT4I-M (14.5")
EG-S-14.6IN-40LB-BK-1000	14.6"	0.14 - 4.17"	0.14"	1000	Black	✓	✓ UL 62275 Type 21	TY244MX (14.5")	T40L0M4 (14.6")	PLT4I-M0 (14.5")

Standard Cable Ties 50 Lbs (230N)								Competitor Cross Reference		
EG Part Number	Length (In.)	Bundle Diameter (In.)	Width (In.)	*Standard Pack Size (EA)	Color	UV Resistant	cULus Listed	ABB – Thomas & Betts	Hellerman Tyton	Panduit
EG-S-7IN-50LB-NA-1000	4.7"	0.14 - 0.94"	0.18"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-7IN-50LB-BK-1000	4.7"	0.14 - 0.94"	0.18"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-6.3IN-50LB-NA-1000	6.3"	0.14 - 1.44"	0.18"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-6.3IN-50LB-BK-1000	6.3"	0.14 - 1.44"	0.18"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-7IN-50LB-NA-1000	7"	0.14 - 1.69"	0.18"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-7IN-50LB-BK-1000	7"	0.14 - 1.69"	0.18"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-7.5IN-50LB-NA-1000	7.5"	0.14 - 1.81"	0.18"	1000	Natural	No	✓ UL 62275 Type 21/21S	TY25M (7.3")	-	PLT2S-M (7.4")
EG-S-7.5IN-50LB-BK-1000	7.5"	0.14 - 1.81"	0.18"	1000	Black	✓	✓ UL 62275 Type 21/21S	TY25MX (7.3")	-	PLT2S-M0 (7.4")
EG-S-8IN-50LB-NA-1000	8"	0.14 - 1.95"	0.18"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	T50R9M4 (8")	-

Standard Cable Ties 50 Lbs (230N)								Competitor Cross Reference		
EG Part Number	Length (In.)	Bundle Diameter (In.)	Width (In.)	*Standard Pack Size (EA)	Color	UV Resistant	cULus Listed	ABB – Thomas & Betts	Hellerman Tyton	Panduit
EG-S-8IN-50LB-BK-1000	8"	0.14 - 1.95"	0.18"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	T50R0M4 (8")	-
EG-S-8.5IN-50LB-NA-1000	8.5"	0.14 - 2.13"	0.18"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-8.5IN-50LB-BK-1000	8.5"	0.14 - 2.13"	0.18"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-10IN-50LB-NA-1000	10"	0.14 - 2.56"	0.18"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-10IN-50LB-BK-1000	10"	0.14 - 2.56"	0.18"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-11IN-50LB-NA-1000	11"	0.14 - 2.94"	0.18"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-11IN-50LB-BK-1000	11"	0.14 - 2.94"	0.18"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-11.8IN-50LB-NA-1000	11.8"	0.14 - 3.19"	0.18"	1000	Natural	No	✓ UL 62275 Type 21/21S	TY253M (11.4")	T50I9M4 (12")	PLT3S-M (11.5")
EG-S-11.8IN-50LB-BK-1000	11.8"	0.14 - 3.19"	0.18"	1000	Black	✓	✓ UL 62275 Type 21/21S	TY253MX (11.4")	T50I0M4 (12")	PLT3S-M0 (11.5")
EG-S-13.8IN-50LB-NA-1000	13.8"	0.14 - 3.82"	0.18"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-13.8IN-50LB-BK-1000	13.8"	0.14 - 3.82"	0.18"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-14IN-50LB-NA-1000	14"	0.14 - 3.94"	0.18"	1000	Natural	No	✓ UL 62275 Type 21/21S	TY28M (14.2")	-	-
EG-S-14IN-50LB-BK-1000	14"	0.14 - 3.94"	0.18"	1000	Black	✓	✓ UL 62275 Type 21/21S	TY28MX (14.2")	-	-
EG-S-15IN-50LB-NA-1000	15"	0.14 - 4.20"	0.18"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	-	PLT4S-M (14.5")
EG-S-15IN-50LB-BK-1000	15"	0.14 - 4.20"	0.18"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	-	PLT4S-M0 (14.5")
EG-S-15.5IN-50LB-NA-1000	15.5"	0.14 - 4.33"	0.18"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	T50L9M4 (15.4")	-
EG-S-15.5IN-50LB-BK-1000	15.5"	0.14 - 4.33"	0.18"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	T50L0M4 (15.4")	-
EG-S-17IN-50LB-NA-1000	17"	0.14 - 4.82"	0.18"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-17IN-50LB-BK-1000	17"	0.14 - 4.82"	0.18"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-18IN-50LB-NA-1000	18"	0.14 - 5.08"	0.18"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	-	PLT5S-M (17.5")
EG-S-18IN-50LB-BK-1000	18"	0.14 - 5.08"	0.18"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	-	PLT5S-M0 (17.5")
EG-S-19.7IN-50LB-NA-500	19.7"	0.14 - 5.71"	0.18"	500	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-19.7IN-50LB-BK-500	19.7"	0.14 - 5.71"	0.18"	500	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-21.7IN-50LB-NA-500	21.7"	0.14 - 6.30"	0.18"	500	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-21.7IN-50LB-BK-500	21.7"	0.14 - 6.30"	0.18"	500	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-24IN-50LB-NA-100	24"	0.14 - 7.08"	0.18"	100	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-24IN-50LB-BK-100	24"	0.14 - 7.08"	0.18"	100	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-29IN-50LB-NA-100	29"	0.14 - 8.66"	0.18"	100	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-29IN-50LB-BK-100	29"	0.14 - 8.66"	0.18"	100	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-36IN-50LB-NA-100	36"	0.14 - 10.94"	0.18"	100	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-36IN-50LB-BK-100	36"	0.14 - 10.94"	0.18"	100	Black	✓	✓ UL 62275 Type 21/21S	-	-	-

Light Heavy Cable Ties 120 Lbs (540N)								Competitor Cross Reference		
EG Part Number	Length (In.)	Bundle Diameter (In.)	Width (In.)	*Standard Pack Size (EA)	Color	UV Resistant	cULus Listed	ABB – Thomas & Betts	Hellerman Tyton	Panduit
EG-S-6IN-120LB-NA-1000	6"	0.33 - 1.38"	0.30"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-6IN-120LB-BK-1000	6"	0.33 - 1.38"	0.30"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-8IN-120LB-NA-1000	8"	0.33 - 2.00"	0.30"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	-	PLT2H-L (8.1")
EG-S-8IN-120LB-BK-1000	8"	0.33 - 2.00"	0.30"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	-	PLT2H-L0 (8.1")
EG-S-8.7IN-120LB-NA-1000	8.7"	0.33 - 2.20"	0.30"	1000	Natural	No	✓ UL 62275 Type 21/21S	TY272M (8.8")	T120S9H4 (8.9")	-
EG-S-8.7IN-120LB-BK-1000	8.7"	0.33 - 2.20"	0.30"	1000	Black	✓	✓ UL 62275 Type 21/21S	TY272MX (8.8")	T120S0H4 (8.9")	-
EG-S-10IN-120LB-NA-1000	10"	0.33 - 2.63"	0.30"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-10IN-120LB-BK-1000	10"	0.33 - 2.63"	0.30"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-11IN-120LB-NA-1000	11"	0.33 - 3.01"	0.30"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-11IN-120LB-BK-1000	11"	0.33 - 3.01"	0.30"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-11.8IN-120LB-NA-1000	11.8"	0.33 - 3.26"	0.30"	1000	Natural	No	✓ UL 62275 Type 21/21S	-	T120I9H4 (11.8")	-
EG-S-11.8IN-120LB-BK-1000	11.8"	0.33 - 3.26"	0.30"	1000	Black	✓	✓ UL 62275 Type 21/21S	-	T120I0H4 (11.8")	-
EG-S-13.8IN-120LB-NA-500	13.8"	0.33 - 3.88"	0.30"	500	Natural	No	✓ UL 62275 Type 21/21S	TY27M (13.4")	-	-
EG-S-13.8IN-120LB-BK-500	13.8"	0.33 - 3.88"	0.30"	500	Black	✓	✓ UL 62275 Type 21/21S	TY27MX (13.4")	-	-
EG-S-14.5IN-120LB-NA-500	14.5"	0.33 - 4.07"	0.30"	500	Natural	No	✓ UL 62275 Type 21/21S	-	-	PLT4H-L (14.5")
EG-S-14.5IN-120LB-BK-500	14.5"	0.33 - 4.07"	0.30"	500	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-15IN-120LB-NA-500	15"	0.33 - 4.25"	0.30"	500	Natural	No	✓ UL 62275 Type 21/21S	-	T120R9H4 (15.2")	-
EG-S-15IN-120LB-BK-500	15"	0.33 - 4.25"	0.30"	500	Black	✓	✓ UL 62275 Type 21/21S	-	T120R0H4 (15.2")	-
EG-S-15.7IN-120LB-NA-500	15.7"	0.33 - 4.51"	0.30"	500	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-15.7IN-120LB-BK-500	15.7"	0.33 - 4.51"	0.30"	500	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-18IN-120LB-NA-500	18"	0.33 - 5.14"	0.30"	500	Natural	No	✓ UL 62275 Type 21/21S	TY275M (18")	-	-
EG-S-18IN-120LB-BK-500	18"	0.33 - 5.14"	0.30"	500	Black	✓	✓ UL 62275 Type 21/21S	TY275MX (18")	-	-
EG-S-19.7IN-120LB-NA-500	19.7"	0.33 - 5.77"	0.30"	500	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-19.7IN-120LB-BK-500	19.7"	0.33 - 5.77"	0.30"	500	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-21.7IN-120LB-NA-500	21.7"	0.33 - 6.40"	0.30"	500	Natural	No	✓ UL 62275 Type 21/21S	-	-	PLT6LH-L (21.9")
EG-S-21.7IN-120LB-BK-500	21.7"	0.33 - 6.40"	0.30"	500	Black	✓	✓ UL 62275 Type 21/21S	-	-	PLT6LH-L0 (21.9")
EG-S-24IN-120LB-NA-100	24"	0.33 - 7.15"	0.30"	100	Natural	No	✓ UL 62275 Type 21/21S	TY277M (24.3")	-	PLT7LH-L (24.7")
EG-S-24IN-120LB-BK-100	24"	0.33 - 7.15"	0.30"	100	Black	✓	✓ UL 62275 Type 21/21S	TY277X (24.3")	-	PLT7LH-L0 (24.7")
EG-S-29.5IN-120LB-NA-100	29.5"	0.33 - 8.90"	0.30"	100	Natural	No	✓ UL 62275 Type 21/21S	TY29M (30.4")	T120L9K2 (30")	PLT9LH-L (30.5")
EG-S-29.5IN-120LB-BK-100	29.5"	0.33 - 8.90"	0.30"	100	Black	✓	✓ UL 62275 Type 21/21S	TY29MX (30.4")	T120L0K2 (30")	PLT9LH-L0 (30.5")

Heavy Cable Ties 175 Lbs (800N)								Competitor Cross Reference		
EG Part Number	Length (In.)	Bundle Diameter (In.)	Width (In.)	*Standard Pack Size (EA)	Color	UV Resistant	cULus Listed	ABB – Thomas & Betts	Hellerman Tyton	Panduit
EG-S-11.8IN-175LB-NA-500	11.8"	0.33 - 3.27"	0.35"	500	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-11.8IN-175LB-BK-500	11.8"	0.33 - 3.27"	0.35"	500	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-15.7IN-175LB-NA-500	15.7"	0.33 - 4.53"	0.35"	500	Natural	No	✓ UL 62275 Type 21/21S	-	T150R9X2 (15.4")	-
EG-S-15.7IN-175LB-BK-500	15.7"	0.33 - 4.53"	0.35"	500	Black	✓	✓ UL 62275 Type 21/21S	-	T150R0X2 (15.4")	-
EG-S-18IN-175LB-NA-500	18"	0.33 - 5.14"	0.35"	500	Natural	No	✓ UL 62275 Type 21/21S	-	-	PLT5H-L (17.7")
EG-S-18IN-175LB-BK-500	18"	0.33 - 5.14"	0.35"	500	Black	✓	✓ UL 62275 Type 21/21S	-	-	PLT5H-L0 (17.7")
EG-S-19.7IN-175LB-NA-100	19.7"	0.33 - 5.77"	0.35"	100	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-19.7IN-175LB-BK-100	19.7"	0.33 - 5.77"	0.35"	100	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-21.7IN-175LB-NA-100	21.7"	0.33 - 6.44"	0.35"	100	Natural	No	✓ UL 62275 Type 21/21S	-	T150M9X2 (21")	PLT6H-L (20.9")
EG-S-21.7IN-175LB-BK-100	21.7"	0.33 - 6.44"	0.35"	100	Black	✓	✓ UL 62275 Type 21/21S	-	T150M0X2 (21")	PLT6H-L0 (20.9")
EG-S-24IN-175LB-NA-100	24"	0.33 - 7.15"	0.35"	100	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-24IN-175LB-BK-100	24"	0.33 - 7.15"	0.35"	100	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-28IN-175LB-NA-100	28"	0.33 - 7.68"	0.35"	100	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-28IN-175LB-BK-100	28"	0.33 - 7.68"	0.35"	100	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-29.5IN-175LB-NA-100	29.5"	0.33 - 8.07"	0.35"	100	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-29.5IN-175LB-BK-100	29.5"	0.33 - 8.07"	0.35"	100	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-30IN-175LB-NA-100	30"	0.33 - 9.04"	0.35"	100	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-30IN-175LB-BK-100	30"	0.33 - 9.04"	0.35"	100	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-30.7IN-175LB-NA-100	30.7"	0.33 - 9.27"	0.35"	100	Natural	No	✓ UL 62275 Type 21/21S	-	-	PLT8H-L (30.6")
EG-S-30.7IN-175LB-BK-100	30.7"	0.33 - 9.27"	0.35"	100	Black	✓	✓ UL 62275 Type 21/21S	-	-	PLT8H-L0 (30.6")
EG-S-32IN-175LB-NA-100	32"	0.33 - 9.65"	0.35"	100	Natural	No	✓ UL 62275 Type 21/21S	-	T150L9X2 (32")	-
EG-S-32IN-175LB-BK-100	32"	0.33 - 9.65"	0.35"	100	Black	✓	✓ UL 62275 Type 21/21S	-	T150L0X2 (32")	-
EG-S-36IN-175LB-NA-100	36"	0.33 - 11.02"	0.35"	100	Natural	No	✓ UL 62275 Type 21/21S	-	T150LL9X2 (36")	-
EG-S-36IN-175LB-BK-100	36"	0.33 - 11.02"	0.35"	100	Black	✓	✓ UL 62275 Type 21/21S	-	T150LL0X2 (36")	-
EG-S-40IN-175LB-NA-100	40"	0.33 - 11.61"	0.35"	100	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-40IN-175LB-BK-100	40"	0.33 - 11.61"	0.35"	100	Black	✓	✓ UL 62275 Type 21/21S	-	-	-
EG-S-46IN-175LB-NA-100	46"	0.33 - 13.39"	0.35"	100	Natural	No	✓ UL 62275 Type 21/21S	-	T150XL9X2 (43.1")	PLT13H-Q (43.3")
EG-S-46IN-175LB-BK-100	46"	0.33 - 13.39"	0.35"	100	Black	✓	✓ UL 62275 Type 21/21S	-	T150XL0X2 (43.1")	PLT13H-Q0 (43.3")
EG-S-48IN-175LB-NA-100	48"	0.33 - 14.78"	0.35"	100	Natural	No	✓ UL 62275 Type 21/21S	-	T150XLL9X2 (52")	-
EG-S-48IN-175LB-BK-100	48"	0.33 - 14.78"	0.35"	100	Black	✓	✓ UL 62275 Type 21/21S	-	T150XLL0X2 (52")	-
EG-S-60IN-175LB-NA-100	60"	0.33 - 17.72"	0.35"	100	Natural	No	✓ UL 62275 Type 21/21S	-	-	-
EG-S-60IN-175LB-BK-100	60"	0.33 - 17.72"	0.35"	100	Black	✓	✓ UL 62275 Type 21/21S	-	-	-

Extra Heavy Cable Ties 250 Lbs (1200N)								Competitor Cross Reference		
EG Part Number	Length (In.)	Bundle Diameter (In.)	Width (In.)	*Standard Pack Size (EA)	Color	UV Resistant	cULus Listed	ABB – Thomas & Betts	Hellerman Tyton	Panduit
EG-9IN-250LB-NA-1000	9"	0.35 - 2.24"	0.49"	1000	Natural	No	✓ UL 62275 Type 21	-	T250S9X2 (9.1")	-
EG-9IN-250LB-BK-1000	9"	0.35 - 2.24"	0.49"	1000	Black	✓	✓ UL 62275 Type 21	-	T250S0X2 (9.1")	-
EG-11.4IN-250LB-NA-500	11.4"	0.35 - 2.99"	0.49"	500	Natural	No	✓ UL 62275 Type 21	-	-	-
EG-11.4IN-250LB-BK-500	11.4"	0.35 - 2.99"	0.49"	500	Black	✓	✓ UL 62275 Type 21	-	-	-
EG-15IN-250LB-NA-100	15"	0.35 - 4.07"	0.49"	100	Natural	No	✓ UL 62275 Type 21	-	-	-
EG-15IN-250LB-BK-100	15"	0.35 - 4.07"	0.49"	100	Black	✓	✓ UL 62275 Type 21	-	-	-
EG-19IN-250LB-NA-100	19"	0.35 - 5.35"	0.49"	100	Natural	No	✓ UL 62275 Type 21	-	T250R9X2 (20.3")	-
EG-19IN-250LB-BK-100	19"	0.35 - 5.35"	0.49"	100	Black	✓	✓ UL 62275 Type 21	-	T250R0X2 (20.3")	-
EG-21IN-250LB-NA-100	21"	0.35 - 6.14"	0.49"	100	Natural	No	✓ UL 62275 Type 21	-	-	-
EG-21IN-250LB-BK-100	21"	0.35 - 6.14"	0.49"	100	Black	✓	✓ UL 62275 Type 21	-	-	-
EG-22.8IN-250LB-NA-100	22.8"	0.35 - 6.61"	0.49"	100	Natural	No	✓ UL 62275 Type 21	-	T250M9X2 (22.3")	-
EG-22.8IN-250LB-BK-100	22.8"	0.35 - 6.61"	0.49"	100	Black	✓	✓ UL 62275 Type 21	-	T250M0X2 (22.3")	-
EG-25.6IN-250LB-NA-100	25.6"	0.35 - 7.68"	0.49"	100	Natural	No	✓ UL 62275 Type 21	-	-	-
EG-25.6IN-250LB-BK-100	25.6"	0.35 - 7.68"	0.49"	100	Black	✓	✓ UL 62275 Type 21	-	-	-
EG-28.7IN-250LB-NA-100	28.7"	0.35 - 8.50"	0.49"	100	Natural	No	✓ UL 62275 Type 21	-	T250I9X2 (28.7")	-
EG-28.7IN-250LB-BK-100	28.7"	0.35 - 8.50"	0.49"	100	Black	✓	✓ UL 62275 Type 21	-	T250I0X2 (28.7")	-
EG-34.6IN-250LB-NA-100	34.6"	0.35 - 10.35"	0.49"	100	Natural	No	✓ UL 62275 Type 21	-	T250L9X2 (34.7")	-
EG-34.6IN-250LB-BK-100	34.6"	0.35 - 10.35"	0.49"	100	Black	✓	✓ UL 62275 Type 21	-	T250L0X2 (34.7")	-
EG-39.4IN-250LB-NA-100	39.4"	0.35 - 12.40"	0.49"	100	Natural	No	✓ UL 62275 Type 21	-	T250XL9X2 (40.6")	-
EG-39.4IN-250LB-BK-100	39.4"	0.35 - 12.40"	0.49"	100	Black	✓	✓ UL 62275 Type 21	-	T250XL0X2 (40.6")	-