3.5K FALCON UTILITY





STANDARD FEATURES

- 2" Coupler with 2K Top Wind Tongue Jack
- 15" Wheels & Tires (Radial)
- Sealed Beam LED Lights
- PPG Primer and Paint
- 2" x 6" #2 or Better Fir Decking
- Tube Tongue (longer than competition)

- Front Fender Step with Light
- J-Hooks (4 per side, 1 in front)
- 24" Solid Metal Sides
- Square Tube Top Tie Rail 30" Total Height
- 4' Ramp

POPULAR OPTIONS

- Tongue Box Steel or Aluminum Diamond Plate
- · Pressure Treated Decking
- Swing up Tongue Jack with Wheel
- Nylon Reinforced Vinyl Tarp Complete with Aluminum Cross Supports and Nylon Stretch Tie Rope
- Solid Metal Rear Swing Gate
- Spare Tire and/or Mount
- Rear Barn Doors
- No Gap Stake Pocket Top
- Four Small D-Rings

MODEL	DESCRIPTION	GVWR	CURB WEIGHT
FU406SA	4' x 6' 3.5K Falcon Single Axle Utility	2,990	610
FU408SA	4' x 8' 3.5K Falcon Single Axle Utility	2,990	675
FU508SA	5' x 8' 3.5K Falcon Single Axle Utility	2,990	700
FU510SA	5' x 10' 3.5K Falcon Single Axle Utility	2,990	750
FU610SA	6' x 10' 3.5K Falcon Single Axle Utility	2,990	825
FU6610SA	6'6" x 10' 3.5K Falcon Single Axle Utility	2,990	850
FU612SA	6' x 12' 3.5K Falcon Single Axle Utility	2,990	945
FU6612SA	6'6" x 12' 3.5K Falcon Single Axle Utility	2,990	1,035
FU614SA	6' x 14' 3.5K Falcon Single Axle Utility	2,990	1,065
FU714SA	7' x 14' 3.5K Falcon Single Axle Utility	2,990	1,095

3.5K FALCON UTILITY TRAILER SPEC SHEET

STANDARD SPECIFICATIONS					
GVWR	2,990#	GAWR	3,500#		
Frame	2" x 2" Angle	Cross Members	2" x 2" Angle		
Axle	3,500# Posi-Lube Axles (Idler)	Fenders	9" x 32"		
Coupler	2" A-Frame	Suspension	Multi-Leaf Spring		
Coupler Height	16"	Ramps	48" Ramp 1 1/2" x 1 1/2" Square Tube		
Deck Height	18"	Uprights	2" x 1" Rectangle Tube		
Tongue	2" x 3" Rectangular Tube	Bump Rail	1 1/2" x 1 1/2" Square Tube		
Jack	2K Top Wind Tongue		24" 16 gauge Smooth Steel		
Safety Chain	30" x 1/4" 5.2K Capacity	Sidewalls	30" to Top of Rail		
Wheels	15 x 5 5 - 4.5 Mod (Silver)	Lights	Sealed Beam LED D.O.T		
		Decking	2" x 6" #2 or Better Fir Decking		
Tires	ST 205/75 D15 Load Range C	Electric Plug	Flat 4-Way Molded Water Tight Plug		
Finish	Steel is cleaned (wiped down) to ensure quality protective finish	Paint	PPG Primer and Paint		

STANDARD COLORS



OPTIONAL COLORS

