

5MP Quad Sensor Camera

One IP with four channels. Pan, tilt, rotation angle of each lens can be adjusted independently; suitable for a more complicated scene.



Camera	
Sensor	1/2.7" CMOS
Video Output	2880*1620@30fps in the main stream of each channel
Min. Illumination	Colour: 0.002 lux (F1.2,AGC ON) 0 lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
Shutter	Auto/Manual, 1 ~ 1/100000s
Adjustment Angle	Pan: 0° ~ 360°, Tilt: 0° ~ 65°, Rotate: 0° ~ 355
Lens	
Focal Length	2.7 ~ 13.5 mm
IRIS	F1.2 * 4
Field of View (H)	(W)110.3*~(T)31*
Field of View (V)	(W)57.1*~(T)17.5*
Lens Type	5X
Field of View (D)	(W)130.2*~(T)67.4*
Iris Type	Fixed
Illuminator	
Illumination Distance (IR)	50 m (164.0 ft)
Wavelength	850 nm
IR On/Off Control	Auto/Manual
Image	
White Balance	Auto; Outdoor; Fine Tune; Sodium Lamp; Locked; Auto2
Digital Noise Reduction	2D/3D DNR
Smart IR	Support
Flip	Normal; Flip Vertical; Flip Horizontal; 180°; 90° Clockwise, 90° Anti-clockwise
Defog	Digital Defog
Network	
Protocols	IPv4; IPv6; IGMP; ICMP; ARP; TCP; UDP; DHCP; PPPoE; RTP; RTSP; RTCP; RTMP; DNS; DDNS; NTP; FTP; UPnP; HTTP; HTTPS; SMTP; 802.1x; SNMP; QoS; SSL/TLS; SSH
Compatible Integration	ONVIF (Profile S, Profile G, Profile T, Profile M); API; SDK

Video	
Video Compression	Ultra 265; H.265; H.264; MJPEG
H.264 Code Profile	Baseline profile, Main profile, High profile
Video Bit Rate	128 Kbps ~ 16 Mbps * 4Channel
U-code	Support
ROI	Support
Video Stream	Triple Streams
Privacy Mask	Up to 8 * 4Channel
Audio	
Audio Compression	G.711U; G.711A
Two-way Audio	Support
Sampling Rate	8 KHz
Interface	
Audio I/O	1 Input: impedance 1kΩ; amplitude 2.5V [p-p]; 1 Output: impedance 600Ω; amplitude 2.5V [p-p]
Alarm I/O	3/2
Built-in Mic	Support
Network	10M/100M/1000M Base-TX Ethernet
Certification	
Protection	IP67 (IEC 60529), IK10 (IEC 62262)
General	
Power	DC 24V±25%, AC 24V±25%, PoE (IEEE802.3bt)
Built- in DC12V Output	Support
Power Consumption	Max 48.7W
Power Interface	Wires with cold-pressed terminal
Dimension	Φ 318 x 136.6 mm (Φ 12.52" x 5.38")(Φ x H)
Weight	4.77Kg (10.52lb)
Working Environment	-30 °C ~ 60 °C (-22 °F ~ 140 °F), Humidity: 5%~95% RH
Surge Protection	6KV