

Western Pacific Products, Inc.

Anything In Or On Your Tank – Ready to Ship

Over 8,000 Part Numbers – Over 26,000 Square Feet of Warehouse – We Ship Worldwide

Petroleum Hoses

T600AA T601AA*



MARINE EXHAUST HOSE

APPLICATION

Fuel, oil and hydraulic fluids suction and delivery with up to 50% aromatic content. Suitable for exhaust gas from water cooled stationary or marine diesel engines.

COVER

Black NBR/PVC blend — abrasion, ozone, hydrocarbon and fire resistant.

REINFORCEMENT

High tensile textile cords and 4 highly flexible steel helix wires.

TUBE

Black NBR — exhaust gas, fuel and fire resistant.

TEMPERATURE RANGE

-22°F to 212°F

STANDARD LENGTH

25, 50 or 100 feet

BRANDING

ALFAGOMMA – ITALY T600 4+4 SP PLUS MARINE EXHAUST/FUEL S & D – <SIZE> – USCG/SAE J1527 TYPE B2 (in red letters)

SERIES NO.	NOMINAL ID (in.) (mm)	NOMINAL OD (in.) (mm)	APPROX. WT. lb./100 ft.	MAX. REC. WP (PSI)	MIN. BEND RADIUS (in.)		
T600AA062	1/2"	16	9.98	25	32	60	2
T600AA075	1/2"	19	1.10	28	36	60	2 1/2
T600AA087	1/2"	22	1.22	31	41	60	3
T600AA100	1"	25	1.34	34	46	60	3
T600AA112	1 1/4"	28	1.46	37	58	60	3 1/2
T600AA125	1 1/2"	32	1.61	41	58	45	3 1/2
T600AA137	1 1/2"	35	1.73	44	60	45	4
T600AA150	1 1/2"	38	1.85	47	64	45	4 1/2
T600AA162	1 1/2"	42	2.00	51	78	45	5
T600AA175	1 1/2"	45	2.13	54	75	45	5 1/2
T600AA188	1 1/2"	48	2.24	57	79	45	5 1/2
T600AA200	2"	51	2.36	60	84	45	6
T600AA225	2 1/2"	57	2.60	66	93	45	6 1/2
T600AA238	2 1/2"	60	2.72	69	97	45	7
T600AA250	2 1/2"	63	2.83	72	102	45	7 1/2
T600AA275	2 1/2"	70	3.11	80	154	45	8
T600AA300	3"	76	3.39	86	166	45	8
T600AA350	3 1/2"	86	3.94	100	195	45	10 1/2
T600AA400	4"	102	4.41	112	219	45	12
T600AA450	4 1/2"	115	4.92	125	245	45	13 1/2
T600AA500	5"	127	5.35	141	352	45	14

COUPLING RECOMMENDATION

Contact fitting manufacturers for recommendation assistance.



OIL RIGGER/OIL FIELD SUCTION HOSE

APPLICATION

Oil field vacuum tank service, for handling crude oil only. **NOTE: NOT RECOMMENDED FOR REFINED PETROLEUM PRODUCTS.**

COVER

Black, SBR, abrasion, ozone, limited oil resistance.

REINFORCEMENT

High tensile textile cords and 4 highly flexible steel helix wires.

TUBE

Black nitrile – PVC blend, limited oil resistance, for oil field use.

TEMPERATURE RANGE

-22°F to 185°F

STANDARD LENGTH

100 feet: 2" through 6"

20 feet: 6" only

BRANDING

ALFAGOMMA – ITALY T601 4 + 4 SP 10 BAR (150 PSI) OIL RIGGER – OIL FIELD – S & D (in blue letters)

SERIES NO.	NOMINAL ID (in.) (mm)	NOMINAL OD (in.) (mm)	PLIES	APPROX. WT. lb./100 ft.	MAX. REC. WP (PSI)	MIN. BEND RADIUS (in.)	
T601AA200	2	51	2.40	61	4	150	10
T601AA300	3	76	3.48	86	4	172	15
T601AA400	4	102	4.57	116	4	221	20
T601AA500	5	152	6.81	168	4	449	30

COUPLING RECOMMENDATION

Combination nipples attached with bands.

★ Kuriyama offers a full size range of combination nipples. Refer to your individual coupling sheets for type and pricing.

★ Note: All T601AA hose is stocked at our Houston, Texas warehouse only.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.

800-677-3711

Signal Hill, (L.A.) CA
(562) 490-0030 • Fax (562) 490-0091

West Sacramento, CA
(916) 371-1622 • Fax (916) 371-4792

Dallas/Fort Worth, TX
(817) 740-8077 • (817) 740-1332

Portland, OR
(503) 221-0335 • Fax (503) 221-0911

www.tankparts.com

Western Pacific Products, Inc.

Anything In Or On Your Tank – Ready to Ship

Over 8,000 Part Numbers – Over 26,000 Square Feet of Warehouse – We Ship Worldwide

Petroleum Hoses

T604AA T605AA



SAE 100 R4 OIL RETURN HOSE

APPLICATION

Hydraulic suction and return hose for oil field, construction and farm equipment.

COVER

Smooth, black Nitrile – PVC/SBR rubber. Oil, ozone and abrasion-resistant.

REINFORCEMENT

Spiralled high tensile textile cords and 4 highly flexible steel helix wires.

TUBE

Black, smooth nitrile rubber for 50% aromatics.

TEMPERATURE RANGE

-40°F to 212°F

STANDARD LENGTH

100 feet

BRANDING

ALFAGOMMA – ITALY T604 – 4 + 4 SP 10 BAR (150 PSI)
SAE 100 R4 on silver stripe.

SERIES NO.	NOMINAL ID		NOMINAL OD		PLIES	APPROX. WT. lb./100 ft.	MAX. REC. WP (PSI)	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)				
T604AA075	3/4	19	1.14	29	4	39	300	4
T604AA100	1	25	1.38	35	4	48	250	5
T604AA125	1 1/4	32	1.65	42	4	60	200	6
T604AA150	1 1/2	38	1.93	49	4	79	150	7
T604AA200	2	51	2.44	62	4	89	100	10

COUPLING RECOMMENDATION

Combination nipples attached with bands.

★ Kuriyama offers a full size range of combination nipples. Refer to your individual coupling sheets for type and pricing.

BLACK PETROLEUM SUCTION HOSE

APPLICATION

For suction and discharge applications in truck and tank car transfer of gasoline, oil and other petroleum-based products with up to 50% aromatic content.

COVER

Black Nitrile PVC. Abrasion and ozone resistant.

REINFORCEMENT

High tensile textile cords and 4 highly flexible steel helix wires.

TUBE

Black conductive NBR.

TEMPERATURE RANGE

-40°F to 212°F

STANDARD LENGTH

100 feet: 3/4" through 6"
20 feet: 6"

WORKING PRESSURE

Constant Pressure 150 PSI

BRANDING

ALFAGOMMA – ITALY T605 – 4 + 4 SP 10 BAR (150 PSI)
PETROLEUM – S & D (in red letters)

★ T605 is not recommended for use on a reel.

SERIES NO.	NOMINAL ID		NOMINAL OD		PLIES	APPROX. WT. lb./100 ft.	MIN. BEND RADIUS (in.)
	(in.)	(mm)	(in.)	(mm)			
T605AA075	3/4	19	1.14	29	4	40	4
T605AA100	1	25	1.38	35	4	49	5
T605AA125	1 1/4	32	1.65	42	4	60	6
T605AA150	1 1/2	38	1.93	49	4	67	7
T605AA200	2	51	2.44	62	4	89	10
T605AA250	2 1/2	63	2.99	76	4	129	12
T605AA300	3	76	3.46	88	4	169	15
T605AA400	4	102	4.57	116	4	257	20
T605AA600	6	152	6.61	168	4	460	30

COUPLING RECOMMENDATION

Cam and groove, combination nipples attached with bands or internally expanded brass couplings with gasket seal attached with ferrules.

★ Kuriyama offers a full line of quick-couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.

800-677-3711

Signal Hill, (L.A.) CA

(562) 490-0030 • Fax (562) 490-0091

West Sacramento, CA

(916) 371-1622 • Fax (916) 371-4792

Dallas/Fort Worth, TX

(817) 740-8077 • (817) 740-1332

Portland, OR

(503) 221-0335 • Fax (503) 221-0911

www.tankparts.com

Western Pacific Products, Inc.

Anything In Or On Your Tank – Ready to Ship

Over 8,000 Part Numbers – Over 26,000 Square Feet of Warehouse – We Ship Worldwide

Petroleum Hoses

T605AH T650AH



RED PETROLEUM SUCTION HOSE

APPLICATION

For suction and discharge applications in truck and tank car transfer of gasoline, oil and other petroleum-based products with up to 50% aromatic content.

COVER

Red Nitrile PVC. Abrasion and ozone resistant.

REINFORCEMENT

High tensile textile cords and 4 highly flexible steel helix wires.

TUBE

Black conductive NBR.

TEMPERATURE RANGE

-40°F to 212°F

STANDARD LENGTH

100 feet

WORKING PRESSURE

Constant Pressure 150 PSI

BRANDING

ALFAGOMMA – ITALY T605 – 4+4 SP 10 BAR (150 PSI)
PETROLEUM – S & D (in yellow letters)

★ T605 is not recommended for use on a reel.

SERIES NO.	NOMINAL ID		NOMINAL OD		PLIES	APPROX. WT. Lbs./100 Ft.	MIN. BEND RADIUS (ft.)
	(in.)	(mm)	(in.)	(mm)			
T605AH150	1½	38	1.89	48	4	67	7
T605AH200	2	51	2.44	62	4	89	10
T605AH300	3	76	3.46	88	4	167	15
T605AH400	4	102	4.57	116	4	257	20

COUPLING RECOMMENDATION

Cam and groove, combination nipples attached with bands or internally expanded brass couplings with gasket seal attached with ferrules.

★ Kuriyama offers a full line of quick-couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

OIL DISCHARGE HOSE

APPLICATION

Oil discharge hose designed for use on trucks, docks or barges where a soft wall hose is required.

COVER

Red Nitrile/PVC blend — abrasion and ozone resistant.

REINFORCEMENT

Spiralled high tensile textile cords with embedded static wire.

TUBE

Black nitrile rubber for 50% aromatics.

TEMPERATURE RANGE

-20°F to 212°F

STANDARD LENGTH

100 feet

WORKING PRESSURE

Constant Pressure — 10 Bar (150 PSI)

BRANDING

ALFAGOMMA – ITALY T650 10 BAR (150 PSI) –
PETROLEUM DELIVERY (in yellow letters)

SERIES NO.	NOMINAL ID		NOMINAL OD		PLIES	APPROX. WT. Lbs./100 Ft.
	(in.)	(mm)	(in.)	(mm)		
T650AH150	1½	38	1.89	48	2	61
T650AH200	2	51	2.40	61	2	61
T650AH300	3	76	3.46	88	4	141
T650AH400	4	102	4.49	114	4	190

COUPLING RECOMMENDATION

Cam and groove or combination nipples attached with bands.

★ Kuriyama offers a full line of quick-couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.

800-677-3711

Signal Hill, (L.A.) CA

(562) 490-0030 • Fax (562) 490-0091

West Sacramento, CA

(916) 371-1622 • Fax (916) 371-4792

Dallas/Fort Worth, TX

(817) 740-8077 • (817) 740-1332

Portland, OR

(503) 221-0335 • Fax (503) 221-0911

www.tankparts.com