


Western Pacific Products, Inc.

Anything In Or On Your Tank – Ready to Ship

Over 8,000 Part Numbers – Over 26,000 Square Feet of Warehouse – We Ship Worldwide



120 VP

Temp. Range: -40°F to 158°F

Applications:
Gasoline vapor recovery only.

Construction:
Nitrile rubber, rigid PVC helix, smooth bore, corrugated O.D.

I.D., inches	O.D., inches	PITCH, inches	MINIMUM BENDING RADIUS 72°F, inches	WORKING PRESSURE 72°F, P.S.I.	BURSTING PRESSURE 72°F, P.S.I.	VACUUM RATING 72°F, in./Hg	WEIGHT, Lbs./ft.
2	2.35	.39	3.0				.56
3	3.48	.59	2.5				.92
4	4.60	.85	5.0				1.60



120 LT, ST 120 LT

Temp. Range: -30°F to 158°F

Applications:
Gasoline tank truck gravity drop hose for such items as naphtha, kerosene, light and heavy oil, and gasohol

Construction:
Nitrile rubber, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.

Features:

- Lightweight and flexible
- External helix provides for easy drag
- Flared for up to 40% aromatic content
- Available with static grounding wire: ST 120 LT

Note: Banding sleeves must be used for 3" and 4" sizes.



I.D., inches	O.D., inches	PITCH, inches	MINIMUM BENDING RADIUS 72°F, inches	WORKING PRESSURE 72°F, P.S.I.	BURSTING PRESSURE 72°F, P.S.I.	VACUUM RATING 72°F, in./Hg	WEIGHT, Lbs./ft.
3	3.62	.59	6.0	65	260		1.27
4	4.80	.85	8.0	65	260		2.00
2	2.68	.39	5.0	65	260		1.13
3	3.62	.59	6.0	65	260		1.37
4	4.80	.85	8.0	65	260		2.16



180 BL

Temp. Range: -40°F to 158°F

Applications:
Designed for suction and light blowing of lightweight abrasives such as rockwool, fiberglass, sawdust, grain, insulation and cement dust

Construction:
SBR rubber blended with static carbon black, rigid PVC helix, smooth bore, corrugated O.D.

2 1/2	2.87	.56	2.5				.71
3	3.40	.59	3.0				.92
4	4.44	.85	4.0				1.50
5	5.57	.87	5.0				1.68
6	6.67	.87	9.0				2.40
8	8.82	.91	12.0				4.40



180 AR

Temp. Range: -40°F to 158°F

Applications:
Heavy duty abrasion resistant suction hose for vacuum trucks or handling abrasives such as crushed rock, sand, pea gravel, cement powder, dry fertilizer, iron ore and grains

Construction:
SBR rubber blended with static carbon black, rigid PVC helix, smooth bore, corrugated O.D.

Features:

- Lightweight and flexible
- Static dissipating with no grounding wire
- Extremely abrasion resistant

Note: This hose was not designed for bulk handling such as unloading of rail cars.

1 1/2	1.57	.33	2.0	45	150	29.8	.31
1 1/2	1.82	.35	2.0	45	150	29.8	.37
2	2.35	.38	2.5	40	130	29.8	.50
2 1/2	2.87	.56	2.5	35	115	29.8	.88
3	3.50	.59	3.0	35	115	29.8	1.10
3 1/2	4.11	.84	4.0	30	100	29.8	1.35
4	4.63	.85	4.5	30	100	29.8	1.77
5	5.63	.87	5.0	30	100	28.0	2.47
6	6.73	.87	9.2	30	100	28.0	3.08
7	7.83	.87	14	30	100	27.0	4.10
8	9.04	.91	15	30	100	27.0	5.65
10	11.26	1.00	30	28	80	25.0	8.88
12	13.39	1.18	40	25	80	25.0	10.43

800-677-3711

Signal Hill, (L.A.) CA

(562) 490-0030 • Fax (562) 490-0091

West Sacramento, CA

(916) 371-1622 • Fax (916) 371-4792

Dallas/Fort Worth, TX

(817) 740-8077 • (817) 740-1332

Portland, OR

(503) 221-0335 • Fax (503) 221-0911

www.tankparts.com

Western Pacific Products, Inc.

Anything In Or On Your Tank – Ready to Ship

Over 8,000 Part Numbers – Over 26,000 Square Feet of Warehouse – We Ship Worldwide

I.D., inches	O.D., inches	PITCH, inches	MINIMUM BENDING RADIUS 72°F, inches	WORKING PRESSURE 72°F, P.S.I.	BURSTING PRESSURE 72°F, P.S.I.	VACUUM RATING 72°F, in. Hg	WEIGHT, lbs./ft.
4	4.68	.65	5.5	30	100	29.8	1.77
6	6.77	.87	9.8	30	100	29.9	3.50
8	8.93	.87	15.0	30	100	27.0	6.10

180 HR

Temp. Range: -40°F to 220°F

Applications:

Heavy duty suction applications where higher temperature and abrasion are factors such as vacuum trucks or the handling of fly ash, crushed rock, sand, pea gravel or cement powder

Construction:

EPDM rubber, polyethylene helix, metal helical wire, smooth bore, corrugated O.D.

Features:

- Lightweight and flexible
- Integral wire helix can be grounded
- External helix provides easy drag
- Rated up to 220°F



1 1/2	1.78	.35	3.0	90	200	29.8	.50
2	2.38	.39	4.0	90	200	29.8	.74
2 1/2	2.90	.58	5.0	90	200	29.8	1.01
3	3.41	.59	6.0	43	170	29.8	1.30
4	4.50	.65	9.0	38	150	29.8	2.01
6	6.67	.87	15.0	23	90	29.0	3.37

220 RS

Temp. Range: -40°F to 158°F

Applications:

Heavy duty liquid suction hose for use in construction dewatering, liquid waste, cesspool cleaning, septic handling, agricultural applications and marine use

Construction:

SBIR rubber, rigid PVC helix, smooth bore, smooth O.D.



1	1.34	.30	1.9	90	220	29.8	.23
1 1/4	1.65	.33	3.2	90	220	29.8	.34
1 1/2	1.84	.35	3.2	90	220	29.8	.40
2	2.43	.39	5.3	90	190	29.8	.67
2 1/2	2.94	.56	6.6	90	190	29.8	.92
3	3.52	.59	7.1	43	150	29.8	1.10
4	4.61	.65	11.0	38	140	29.8	1.84
6	6.69	.87	20.0	23	100	28.0	3.07

300 EPDM

Temp. Range: -40°F to 158°F

Applications:

Heavy duty liquid suction hose for use in construction dewatering, liquid waste, cesspool cleaning, septic handling, agricultural applications and marine use

Construction:

EPDM rubber, polyethylene helix, smooth bore, corrugated O.D.

Features:

- Lightweight and flexible
- External helix provides for easy drag
- Resistant to agricultural chemicals



1 1/4	1.60	.38	3.0	100		29.8	.45
1 1/2	1.87	.43	3.0	100		29.8	.50
2	2.47	.47	5.0	100		29.8	.73
3	3.54	.59	7.0	90		28.8	1.25

390 SD

Temp. Range: -40°F to 158°F

Applications:

Suction and discharge of liquids in the construction, rental and agricultural industries such as agricultural chemicals, liquid fertilizers and dewatering

Construction:

EPDM rubber, polyethylene helix, synthetic braiding, smooth bore, corrugated O.D.

Features:

- Lightweight and flexible
- Rated for both suction and discharge
- External helix provides for easy drag
- Resistant to agricultural chemicals
- Durable in construction applications



RUBBER HOSE

800-677-3711

Signal Hill, (L.A.) CA

(562) 490-0030 • Fax (562) 490-0091

West Sacramento, CA

(916) 371-1622 • Fax (916) 371-4792

Dallas/Fort Worth, TX

(817) 740-8077 • (817) 740-1332

Portland, OR

(503) 221-0335 • Fax (503) 221-0911

www.tankparts.com

Western Pacific Products, Inc.

Anything In Or On Your Tank – Ready to Ship

Over 8,000 Part Numbers – Over 26,000 Square Feet of Warehouse – We Ship Worldwide



100 CL

Temp. Range: -13°F to 158°F

Applications:

General water suction hose

Construction:

Flexible PVC, rigid PVC helix, smooth bore, corrugated O.D.

101 PS

Temp. Range: -13°F to 158°F

Applications:

- Methane gas recovery at landfills
- Connection between rigid pipes of the same size
- Repair of broken rigid lines

Construction:


Flexible PVC, rigid PVC helix, smooth bore, corrugated O.D.

100 CL

	I.D., inches	O.D., inches	W.T.H.K., inches	MINIMUM BENDING RADIUS 77°F, inches	WORKING PRESSURE 77°F, P.S.I.	BURSTING PRESSURE 77°F, P.S.I.	VACUUM RATING 77°F, in. Hg	WEIGHT, lbs./ft.
1	1.22	.30	1.2	50	155	28.8	.18	
1 1/4	1.48	.33	1.6	45	149	29.8	.22	
1 1/2	1.84	.35	2.0	45	149	29.8	.35	
2	2.36	.39	2.6	40	132	29.8	.50	
2 1/2	2.87	.56	2.8	35	115	29.8	.68	
3	3.50	.59	2.8	35	115	29.8	1.00	
4	4.63	.65	4.3	30	100	29.8	1.52	
6	6.73	.87	9.2	30	100	29.8	3.10	
8	9.04	.91	14.3	30	100	29.8	5.38	
10	11.26	1.02	30.0	30	80	29.8	8.88	

101 PS

2.375	2.76	.41	2.6	35	115	29.8	.68
3.500	4.00	.63	3.5	30	100	29.8	1.20
4.500	5.79	.87	6.5	30	100	29.8	1.70



110 CL, 110 GR

Temp. Range: -13°F to 158°F

Applications:

Heavy duty water suction hose

Construction:

Flexible PVC, rigid PVC helix, smooth bore, smooth O.D.

1/4	.95	.22	1.9	86	284	29.8	.18
1	1.23	.22	1.9	86	284	29.8	.26
1 1/4	1.52	.26	2.7	79	256	29.8	.37
1 1/2	1.78	.30	2.8	72	242	29.8	.44
2	2.38	.33	3.9	72	242	29.8	.74
2 1/2	2.92	.37	4.7	72	242	29.8	1.01
3	3.41	.37	6.1	62	199	29.8	1.21
4	4.50	.43	9.1	55	178	29.8	2.01
5	5.55	.45	14.0	33	120	29.8	2.45
6	6.67	.53	15.6	33	120	29.8	3.37
8	8.83	.70	20.0	28	105	29.8	5.80



112 CL, 112 AG

Temp. Range: -13°F to 158°F


Applications:

Economical heavy duty water suction hose

Construction:

Flexible PVC, rigid PVC helix, smooth bore, smooth O.D.

1 1/4	1.50	.26	3.0	80	256	29.8	.29
1 1/2	1.79	.30	3.0	70	242	29.8	.39
2	2.32	.33	4.0	65	200	29.8	.63
2 1/2	2.84	.37	5.0	65	196	29.8	.87
3	3.31	.37	8.0	55	170	29.8	1.05
4	4.45	.43	10.0	50	170	29.8	1.80



KANALINE SR

Temp. Range: -13°F to 158°F

Applications:

Heavy duty suction and discharge hose for use in fish suction and rental/construction pumping

Construction:

Flexible PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.

Features:

- Lightweight and flexible
- External helix provides for easy drag
- Rated for both suction and discharge
- Clear sidewall permits visual check of material flow

1 1/2	2.01	.37	2.0	110	360	29.8	.47
2	2.56	.43	4.0	100	300	29.8	.70
3	3.60	.59	6.3	100	290	29.8	1.13
4	4.72	.65	7.1	75	230	29.8	1.74
6	7.17	.80	10.2	70	230	29.8	3.88
8	9.33	1.07	15.7	60	200	29.8	5.54
10	11.63	1.22	24.8	40	130	29.8	8.68

800-677-3711

Signal Hill, (L.A.) CA

(562) 490-0030 • Fax (562) 490-0091

West Sacramento, CA

(916) 371-1622 • Fax (916) 371-4792

Dallas/Fort Worth, TX

(817) 740-8077 • (817) 740-1332

Portland, OR

(503) 221-0335 • Fax (503) 221-0911

www.tankparts.com

Western Pacific Products, Inc.

Anything In Or On Your Tank – Ready to Ship

Over 8,000 Part Numbers – Over 26,000 Square Feet of Warehouse – We Ship Worldwide

I.D., inches	O.D., inches	WTCK, inches	MINIMUM BENDING RADIUS 72", inches	WORKING PRESSURE 72", P.S.I.	SUCKING PRESSURE 72", P.S.I.	VACUUM RATING 72", in.Hg	WEIGHT, Lbs./Ft.
1	1.22	.30	1.2	50	155	29.8	.18
1 1/4	1.48	.33	1.6	45	149	29.8	.22
1 1/2	1.64	.35	2.0	45	149	29.8	.26
2	2.36	.39	2.6	40	132	29.8	.50
2 1/2	2.87	.56	3.6	35	115	29.8	.68
3	3.50	.58	2.8	35	115	29.8	1.00
4	4.63	.85	4.3	30	100	29.8	1.52

200 SFG


Temp. Range: -13°F to 158°F

Applications:

Food grade suction hose for use in canning, dairy and bottling

Construction:

Produced entirely of compounds in compliance with FDA and 3-A nontoxic specifications, flexible PVC, rigid PVC helix, smooth bore, corrugated O.D.



1 1/2	1.88	.35	2.0	45	149	29.8	.44
2	2.36	.38	2.6	40	132	29.8	.58
2 1/2	2.87	.56	2.6	35	115	29.8	.75
3	3.50	.58	2.8	35	115	29.8	1.07
4	4.59	.85	4.3	30	100	29.8	1.52

ST 200 SFG

Temp. Range: -13°F to 158°F

Applications:

Pneumatic conveying of lightweight solids such as powders and plastic pellets

Construction:

Produced entirely of compounds in compliance with FDA and 3-A nontoxic specifications, flexible PVC, rigid PVC helix, multi-strand copper static grounding wire, smooth bore, corrugated O.D.



1/4	.96	.22	1.9	86	284	29.8	.16
1	1.24	.22	1.9	86	284	29.8	.26
1 1/4	1.54	.26	2.7	79	258	29.8	.37
1 1/2	1.82	.30	2.8	72	242	29.8	.44
2	2.39	.33	3.9	72	242	29.8	.74
2 1/2	2.93	.37	4.7	72	242	29.8	1.01
3	3.43	.37	6.1	62	199	29.8	1.21
4	4.53	.43	9.1	55	179	29.8	2.01

210 HFG

Temp. Range: -13°F to 158°F

Applications:

Heavy duty food grade suction hose for bottling and dairy industries

Construction:

Produced entirely of compounds in compliance with FDA and 3-A nontoxic specifications, flexible PVC, rigid PVC helix, smooth bore, smooth O.D.



1 1/2	1.82	.30	2.0	66	218	29.8	.44
2	2.39	.33	2.5	66	218	29.8	.74

212 MK

Same as 1-1/2" and 2" 210 HFG, only more flexible. Designed for milk hauling (tank truck) and pick-up.

1 1/2	2.01	.39	2.0	110	360	28.0	.56
2	2.58	.41	4.0	100	300	28.0	.75
3	3.60	.59	6.3	100	280	28.0	1.20
4	4.72	.85	7.1	75	220	28.0	1.74

KANALINE FW

Temp. Range: -13°F to 158°F

Applications:


Heavy duty food grade suction and discharge hose for bottling, wine making, canning, dairy, brewing and liquid foods

Construction:

Produced entirely of compounds in compliance with FDA and 3-A nontoxic specifications, flexible PVC, rigid PVC helix, synthetic braiding, smooth bore, corrugated O.D.

Features:

- Lightweight and flexible
- External helix provides for easy drag
- Rated for both suction and discharge
- Clear sidewall permits visual check of material flow



PVC HOSE

800-677-3711

Signal Hill, (L.A.) CA

(562) 490-0030 • Fax (562) 490-0091

West Sacramento, CA

(916) 371-1622 • Fax (916) 371-4792

Dallas/Fort Worth, TX

(817) 740-8077 • (817) 740-1332

Portland, OR

(503) 221-0335 • Fax (503) 221-0911

www.tankparts.com

Western Pacific Products, Inc.

Anything In Or On Your Tank – Ready to Ship

Over 8,000 Part Numbers – Over 26,000 Square Feet of Warehouse – We Ship Worldwide



150 CL

Temp. Range: -13°F to 158°F

Applications:

Lightweight general ducting for ventilation and grass clippings, leaves, dust and fumes

Construction:

Flexible PVC, rigid PVC helix, smooth bore, corrugated O.D.

I.D., inches	O.D., inches	PITCH, inches	MINIMUM BENDING RADIUS 72°F, inches	WORKING PRESSURE 72°F, P.S.I.	BLASTING PRESSURE 72°F, P.S.I.	VACUUM RATING 72°F, in.Hg	WEIGHT, lbs./ft.
2 1/2	3.74	.43	2.5				.37
3	3.37	.47	3.0				.49
4	4.43	.57	4.0				.71
5	5.59	.79	5.0				1.05
6	6.53	.79	6.0				1.29
7	7.29	.83	7.0				1.38
8	8.55	.89	8.0				1.71



620 WD

Temp. Range: -40°F to 220°F

Applications:

General ducting and blower applications. For use with lightweight abrasives such as sawdust, grass clippings, street refuse and cotton pickers

Construction:

EPDM rubber, metal wire helix, smooth bore, slightly corrugated O.D.

Features:

- Rated to 220°F
- Abrasion resistant yet very flexible
- 100% rubber sidewall (no fabric)

2 1/2	3.00	.58	3.0				.44
3	3.07	.60	3.0				.55
4	4.35	.65	4.0				.73
5	5.33	.68	5.0				.84
6	6.33	.67	6.0				1.04
7	7.30	.69	7.0				1.19
8	8.33	.62	8.0				1.38
10	10.47	1.02	10.0				2.40
12	12.26	1.20	12.0				2.50



620 WD WS

Temp. Range: -40°F to 220°F

Applications:

Same as 620 WD, but external wearstrip makes it ideal for "light dragging" applications

Construction:

EPDM rubber, metal wire helix, wearstrip, smooth bore, corrugated O.D.

2 1/2	3.17	.58	3.0				.48
3	3.43	.60	3.0				.61
4	4.57	.65	4.0				.85
5	5.51	.68	5.0				.90
6	6.50	.67	6.0				1.17
7	7.55	.69	7.0				1.27
8	8.58	.62	8.0				1.50
10	10.63	1.02	10.0				2.67
12	12.65	1.20	12.0				2.80



630 ED

Temp. Range: -40°F to 158°F

Applications:

Medium-duty blower and ducting applications such as hay baling, street refuse, grain dust, cotton pickers, wood chips, straw blowing, leaf and grass collection

Construction:

EPDM rubber, polypropylene helix, smooth bore, corrugated O.D.

Features:

- Thicker sidewall for more abrasion resistance
- External helix acts as a scuff guard
- 100% rubber sidewall (no fabric)

4	4.32	.67	4.0				.70
6	6.50	.63	6.0				1.05
8	8.46	.67	8.0				1.46

800-677-3711

Signal Hill, (L.A.) CA

(562) 490-0030 • Fax (562) 490-0091

West Sacramento, CA

(916) 371-1622 • Fax (916) 371-4792

Dallas/Fort Worth, TX

(817) 740-8077 • (817) 740-1332

Portland, OR

(503) 221-0335 • Fax (503) 221-0911

www.tankparts.com