

# Western Pacific Products, Inc.

*Anything In Or On Your Tank – Ready to Ship*

*Over 8,000 Part Numbers – Over 26,000 Square Feet of Warehouse – We Ship Worldwide*

## Material Handling Hoses

# T760AA T763AA



### LIGHT WEIGHT DRY POWDER DELIVERY HOSE

#### APPLICATION

Discharge of dry powders under low pressure, such as cement powder in light duty applications.

#### COVER

Black conductive SBR/NR blend — abrasion and ozone resistant.

#### REINFORCEMENT

Spiralled high tensile textile cords.

#### TUBE

3/16" thick black static conducting natural rubber, compounded to resist cutting by abrasive materials.

#### TEMPERATURE RANGE

-30°F to 185°F

#### STANDARD LENGTH

100 feet

#### WORKING PRESSURE

Constant Pressure — 5 Bar (75 PSI)

#### BRANDING

ALFAGOMMA – ITALY T760 5 BAR (75 PSI)

BULK MATERIAL DELIVERY (in white letters)

★ Excessive bending during operation may cause premature wear.

SERIES NO.	NOMINAL ID		NOMINAL OD		PLIES	APPROX. WT. Lbs./100 Ft.
	(in.)	(mm)	(in.)	(mm)		
T760AA00	4	102	4.53	115	2	181

#### COUPLING RECOMMENDATION

Cam and groove, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of quick-couplings, pin lug shank couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

### HEAVY WEIGHT DRY POWDER DELIVERY HOSE

#### APPLICATION

Discharge of dry powders under low pressure. Pneumatic transfer of dry materials and abrasive slurries.

#### COVER

Black conductive SBR/NR blend — abrasion and ozone resistant.

#### REINFORCEMENT

Spiralled high tensile textile cords.

#### TUBE

1/4" thick black static conducting natural rubber, compounded to resist cutting by abrasive materials.

#### TEMPERATURE RANGE

-30°F to 185°F

#### STANDARD LENGTH

100 feet

#### WORKING PRESSURE

Constant Pressure — 5 Bar (75 PSI)

#### BRANDING

ALFAGOMMA – ITALY T763 5 BAR (75 PSI)

BULK MATERIAL DELIVERY (in green letters)

★ Excessive bending during operation may cause premature wear.

SERIES NO.	NOMINAL ID		NOMINAL OD		PLIES	APPROX. WT. Lbs./100 Ft.
	(in.)	(mm)	(in.)	(mm)		
T763AA00	4	102	4.72	120	2	199
T763AA00	5	127	5.71	145	4	297

#### COUPLING RECOMMENDATION

Cam and groove, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of quick-couplings, pin lug shank couplings and combination nipples. Refer to your individual coupling sheets for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS WITHOUT PRIOR NOTICE.

## 800-677-3711

Signal Hill, (L.A.) CA

(562) 490-0030 • Fax (562) 490-0091

West Sacramento, CA

(916) 371-1622 • Fax (916) 371-4792

Dallas/Fort Worth, TX

(817) 740-8077 • (817) 740-1332

Portland, OR

(503) 221-0335 • Fax (503) 221-0911

[www.tankparts.com](http://www.tankparts.com)

6-10