

TECHNICAL Data Sheet

Petroleum Treat (PT)



environmental products for a greener planet

Key Benefits

- **High-CFU Performance:** consistent microbial activity in wastewater and soil remediation
- **Broad Contaminant Coverage:** diesel, gasoline, kerosene, heating oil, jet fuel, lubricating oils, and PAHs
- **Biosurfactant & Enzyme Production:** improves hydrocarbon bioavailability for faster breakdown
- **Proven in Multiple Systems:** effective in refinery, petrochemical, and industrial operations including API/CPI separators, DAF/IGF units, aeration basins, clarifiers, lift stations, stormwater, and soils
- **Consistent in Harsh Conditions:** performs under variable pH, temperature, and hydrocarbon loads
- **Flexible Formats:** available in powder, liquid, block, and tablet

Packaging Options

- **Powder:** Supplied in
 - 22 lb (10 kg) pails
 - 44 lb (20 kg) pails
 - 340 lb (155 kg) drums
- **Liquid:** Available in
 - Quart, liter, gallon containers
 - 55-gallon (208 liter) drums
- **Blocks:** 2lb blocks in cases of 4
- **Tablets:** All tab sizes packed in pails

Concentration (CFU/g):

- Powder: 2, 50, 100 billion CFU/g dry powder
- Liquid: 13.5 billion CFU/ml liquid
- Blocks: 4 billion CFU/g
- Tabs: 2 billion CFU/g

Custom concentrations available upon request



Product Description

Petroleum Treat (PT) is a high-CFU blend of petroleum-degrading bacteria for wastewater treatment and petroleum-contaminated soil bioremediation. Designed for the petrochemical, industrial, and environmental remediation sectors, PT accelerates the breakdown of aliphatics, aromatics (including PAHs), petroleum distillates, lubricating oils, and fats, oils, and greases (FOG). Natural biosurfactants and broad-spectrum enzymes increase hydrocarbon bioavailability for faster, more complete degradation. PT delivers consistent results in both wastewater and soil applications, improving stability, reducing TPH, and cutting remediation timelines even under variable field conditions.

Applications

- Wastewater Treatment Plants
- Oil Spills
- Soil Remediation
- Wash Water Recyclers
- Parts Washers
- Oil Water Separators

Shelf Life & Storage

- 2 years at room temperature
- 3 years refrigerated
- Store in a cool, dry location away from direct sunlight.
- Reseal container tightly after each use.

www.biogp.com

Application Guidelines

	Range	Optimal
pH Range	5.0 – 9.5	6.0 – 8.0
Temperature	45 - 120°F (7-49°C)	59 - 104°F (15-40°C)

Application Rates

Powder

PPM	Grams per million L/day	Grams per million gal/day	Notes
0.04	40	150	Starting Dose
0.08	80	300	After 2 weeks

Liquid

PPM	ml per million L/day	ml per million gal/day	Notes
0.04	150	570	Starting Dose
0.08	300	1140	After 2 weeks

Blocks

One 900g (2lb) block typically treats ~1,500m³ (1.5 million liters) of water and slowly dissolves over ~30 days. Dissolve rate fluctuates with water temperature and flow rate.

Tabs

One 85g (3oz) tab typically treats ~150m³ (150,000 liters) of water and slowly dissolves over ~30 days. Dissolve rate fluctuates with water temperature and flow rate.

Fast-Dissolve Tabs

Tablets dissolve completely within 1 hour in water. Tablet sizes vary (5g, 28g, 130g).

Bio-Based Cleaners and Degreasers

Usage rates vary. Reference dose:

- 0.75 - 1.5 grams of 50B powder per liter of ready-to-use product
- 2.75 - 5.5 grams of 50B powder per gallon of ready-to-use product.

Disclaimer: Results may vary depending on environmental conditions, application rates, and management practices. The manufacturer makes no guarantee of specific results. Seller's liability is limited to replacement of product or refund of purchase price. Manufacturer is not responsible for misuse, mishandling, or application under adverse conditions beyond its control. This product is not registered for pesticidal use with the U.S. Environmental Protection Agency. It is intended as a soil amendment / microbial inoculant only. Keep out of reach of children.

Contact Information

P: +1 (262) 285-4390

E: gogreen@biogp.com

A: 520 Progress Drive, Belgium, WI 53004, USA