










## **Parameters**

m	2.97mm	3 <b>.</b> 47mm	3.91mm
Star N	ationStar	NationStar	NationStar
115	SMD1415	SMD1415	SMD1415
В	1R1G1B	1R1G1B	1R1G1B
24	168*21	144*24	128*16
5mm 50	0*62.5mm	500*83.28mm	500*62.5mm
Front Access			
/384 33	6*168/336	288*216/288	256*128/256
/1000 1000	0*500/1000	1000*750/1000	1000*500/1000
16	2*8/2*16	2*9/2*12	2*8/2*16
56	112896	82944	65536
ó	42%	45%	50%
g	12kg	11kg	10kg
Hz	3840Hz	2800Hz	3840Hz
an	21 Scan	16 Scan	16 Scan
Aluminum			
140°/140°			
≤5000			
14-16bit			
Universal			
AC: 110V~240V、50~60Hz			
800			
240			
	Star N 415 9 118 224 55mm 50 7384 33 71000 1000 116 36 66	Star NationStar  415 SMD1415  1B 1R1G1B  24 168*21  5mm 500*62.5mm  Front /  /384 336*168/336 /1000 1000*500/1000  16 2*8/2*16  56 112896  6 42%  8g 12kg  Hz 3840Hz  an 21 Scan  Alum  140°/  ≤50  14-1  Univ  AC: 110V~244	Star         NationStar         NationStar           415         SMD1415         SMD1415           18         1R1G1B         1R1G1B           24         168*21         144*24           5mm         500*62.5mm         500*83.28mm           Front Access           /384         336*168/336         288*216/288           /1000         1000*500/1000         1000*750/1000           *16         2*8/2*16         2*9/2*12           56         112896         82944           6         42%         45%           4g         11kg           Hz         3840Hz         2800Hz           an         21 Scan         16 Scan           Aluminum           140°/140°         ≤5000           14-16bit         Universal           AC: 110V~240V, 50~60Hz         800





# Higher transparency and infinite possibilities

O-CLEAR series is based on positive—lighting technology, its high transparency able to reach 80%.




### **High Brightness**

Peak brightness up to 5000NITS, even if installed in a glass window exposed to direct sunlight, it can be viewed clearly.


#### Modular design

Easy for maintenance, modules can be individually replaced to reduce maintenance costs.









# Light and reliable aluminum architecture

Aluminum cabinet architecture results in advanced heat dissipation and management and longevity of live, Only 11 kg per square meter, fixtures on cabinet are strengthened to improve reliability and protect cabinet from erosion.

### Flexible Frame Design

Supports curved installation to match the project requirements at the installation site.





## Easy Maintain Easy Installation

Quick lock disassembly, Only one person can maintain it independently.

