

Street Co flexible mesh screen E18

Product Introduction/Product Release



Product Introduction (Parameters)



Specification	Rated Power	Rated voltage	Control modes	Gray level	Led numbers	Beam angle	Appliance level	IP level	Flame retardant level	Outer color	Work Temp	Storage Temp
RGB (2leds)	0.5W	DC12V	SPI	65536	3535*2	110°	class III	IP67	94-V0	Black/Gray white	-20 to 60	-40 to 75
RGB (4leds)	1W	DC24V	SPI	65536	2727*4	110°	class III	IP67	94-V0	Black/Gray white	-20 to 60	-40 to 75
RGB (6leds)	1.4W	DC24V	SPI	65536	2727*6	110°	class III	IP67	94-V0	Black/Gray white	-20 to 60	-40 to 75

Regular brightness value

Pixel pitch	P31.25	P40	P50	P55	P62.5	P80	P100	P125	P150
Pixel dot/SQM	1024	625	400	331	256	156	100	64	44
Transmission rate	43.8%	60.3%	70.6%	74.0%	78.0%	83.8%	87.6%	90.5%	92.3%
E18(2leds 12V)	3277	2000	1280	1058	819	500	320	205	142
E18(4leds 24V)	6554	4000	2560	2116	1638	1000	640	410	284
E18(6leds 24V)	9759	5956	3812	3150	2440	1489	953	610	424

36V brightness value

Specification	P 31.25	P40	P50	P55	P62.5	P80	P100	P125	P150
RGB (1led 1.4W 36V)	15200	9300	6000	4850	3800	2320	1490	950	660

单位: nit