

SPECIFICATION

Model	P3.91	P5	P6.25	P8	P10
Module (mm)	250x1000 / 250x1200 / 250x1500				
Transparency	>70%	>75%	>82%	>88%	>93%
Weight (Kg/m ²)	<6 KGS	<6 KGS	<6 KGS	<6 KGS	<6 KGS
Thickness (mm)	≤2	≤2	≤2	≤2	≤2
Pixel Pitch (mm)*	3.91	5	6.25	8	10
LED Type	1515	1515	1515	1921/2727	1921/2727
Brightness	2000 nits - Max 1.5m length module 5000 nits - Max 1m length module				
Average Power Consumption (w/m ²)	240	240	240	240	240
Maximum Power Consumption (w/m ²)	800	800	800	800	800
Color Uniformity	± 0.003	± 0.003	± 0.003	± 0.003	± 0.003
Viewing Angle (°)	140(H)/140(V)	140(H)/140(V)	140(H)/140(V)	140(H)/140(V)	140(H)/140(V)
Refresh-rate (Hz)	≥3840	≥3840	≥3840	≥3840	≥3840
Color Resolution	16	16	16	16	16
Operating Temperature (°C)	-20°C-65°C	-20°C-65°C	-20°C-65°C	-20°C-65°C	-20°C-65°C
Operating Humidity (RH)	10%-90%	10%-90%	10%-90%	10%-90%	10%-90%
Driving Mode	1/6	1/6	1/6	1/6	1/6
Processing System	NOVA	NOVA	NOVA	NOVA	NOVA

※ Specification is subject to changes without prior notice for product improvement.

